

– A, REFER TO <u>____</u>___ TABLE. – B, REFER TO TABLE. - 12" SUBGRADE

BASE COURSE MUST CONSIST OF GRADED AGGREGATE COMPACTED TO AT LEAST 100% OF THE MAXIMUM DRY DENSITY AS DETERMINED BY THE MODIFIED PROCTOR (ASTM D1557)

2. SOIL SUBGRADE SHOULD BE COMPACTED TO AT LEAST 95% OF THE MAXIMUM DRY DENSITY AS DETERMINED BY THE MODIFIED PROCTOR (ASTM D1557)

3. PROVIDE JOINTS BETWEEN CONCRETE SECTIONS IN ACCORDANCE WITH DETAILS ON CS503

PORTLAND CEMENT CONCRETE (PCC) PAVEMENT SECTION TABLE								
	A	В						
CONCRETE APRONS LOADING DOCKS	MINIMUM 7 INCHES OF PCC WITH MINIMUM 4,000 POUNDS PSI COMPRESSIVE STRENGTH	6 INCHES OF CLASS 7 AGGREGATE BASE COURSE.						



CONCRETE PAVEMENT SECTION SCALE N.T.S.



- 1. ALL STEEL POSTS AND BRACKETS MUST BE CUT, BENT, AND HOLES PUNCHED AND DRILLED BEFORE GALVANIZING. GALVANIZING MUST BE IN CONFORMANCE WITH CURRENT ASTM SPECIFICATIONS A123. 2. THE MINIMUM VEWRTICAL CLEARANCE REQUIRED FOR SIGNS ARE 7
- FEET MINIMUM FROM GROUND LINE TO BOTTOM OF SIGN. 3. SHOP DRAWINGS MUST BE SUBMITTED FOR ALL SIGNS.
- 4. ALL SIGNS EXCEPT STOP SIGNS MUST HAVE A 1" OUTSIDE CORNER RADIUS, A 1" BORDER AND 1/2" DISTANCE BETWEEN EDGE OF SIGN AND OUTSIDE EDGE OF BORDER.
- 5. ALL SIGNS MUST BE RETRO-REFLECTIVE.



A, REFER TO TABLE.

	 	 	 		\sim				 			$\overline{\mathbf{x}}$	₹			
				$\overline{}$	$\sum_{i=1}^{n}$	/	\mathcal{H}) //.	\mathcal{H}		///. ///.			—— B, F	REFER	ΤΟ ΤΑΒ
		R		P		K	Ŷ	E C		ję			3	C, R	EFER	ΤΟ ΤΑΒ
												X		— 12" SUB	GRADI	Ξ
TE			0.0			–	~ F	~				~~				TED

NO BASE COURSE MUST CONSIST OF GRADED AGGREGATE COMPACTED TO AT LEAST 100% OF THE MAXIMUM DRY DENSITY AS DETERMINED BY THE MODIFIED PROCTOR (ASTM D1557)

2. SOIL SUBGRADE SHOULD BE COMPACTED TO AT LEAST 95% OF THE MAXIMUM DRY DENSITY AS DETERMINED BY THE MODIFIED PROCTOR (ASTM D1557)

ASPHALT PAVEMENT SECTION TABLE										
	A	В	С							
PARKING AREAS	MINIMUM 2 INCHES HOT MIX ASPHALT CONCRETE (HMAC) SURFACE COURSE	3 INCHES OF HMAC BINDER COURSE	6 INCHES OF CLASS 7 AGGREGATE BASE COURSE.							
ROADWAYS	MINIMUM 2 INCHES OF HMAC SURFACE COURSE	4 INCHES OF HMAC BINDER COURSE	8 INCHES OF CLASS 7 AGGREGATE BASE COURSE.							
SHOULDER	MINIMUM 4 INCHES OF HMAC SURFACE COURSE	0 INCHES OF HMAC BINDER COURSE	6 INCHES OF CLASS 7 AGGREGATE BASE COURSE.							



ASPHALT PAVEMENT SECTION SCALE N.T.S.



CONCRETE V-DITCH A5 SCALE N.T.S.

