

WINDOW SCHEDULE									
TYP	MTL	FIN	WT	HT	DETAILS			REMARKS	
					HEAD	JAMB	SILL		
W1	ALUM	AN	3'-0"	5'-0"	C4/A-514	B4/A-514	A4/A-514		
W2	ALUM	AN	7'-8"	4'-0"	C3/A-514	B3/A-514	A3/A-514	SHATTER PROOF PLASTIC GLAZING	

WINDOW TYPES

ALUMINUM WINDOW SYSTEM

W1

ALUMINUM WINDOW SYSTEM

W2

DOOR SCHEDULE																			
NO	TYPE	DOOR SIZE			FRAME			DETAILS			STRUCTURE	FIRE RATING	ASSEMBLY		EXPLOSION PROOF	EXTERIOR WEATHER HOOD	REMARKS		
		WT	HT	THK	MATL	TYPE	MATL	FIN	HEAD	JAMB	SILL		HDWR	INSULATED					
GROUND FLOOR																			
101A	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D5/A-804	C5/A-804	A1/A-803		9	X					
101B	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D3/A-804	C3/A-804	A2/A-803		12						
102A	FV	3'-0"	7'-0"	2"	STL	1	HM	FF	D3/A-804	C3/A-804	A2/A-803		12						
102B	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D6/A-804	C5/A-804	A1/A-803		6	X					
103	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D2/A-804	C2/A-804	A3/A-803		20						
104	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D2/A-804	C2/A-804	A3/A-803		20						
105	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D3/A-804	C3/A-804	A2/A-803		18						
106	FV	3'-0"	7'-0"	2"	STL	1	HM	FF	D3/A-804	C3/A-804	A2/A-803		18						
107A	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D5/A-804	C5/A-804	A1/A-803		9	X					
107B	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D3/A-804	C3/A-804	A2/A-803		12						
108	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D3/A-804	C3/A-804	A2/A-803		16						
109	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D3/A-804	C3/A-804	A2/A-803		16						
110	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D3/A-804	C3/A-804	A2/A-803		16						
111	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D3/A-804	C3/A-804	A2/A-803		16						
112A	FV	3'-0"	7'-0"	2"	STL	1	HM	FF	D3/A-804	C3/A-804	A2/A-803		13	X					
112B	PF	6'-0"	7'-0"	2"	STL	2	HM	FF	D4/A-804	D4/A-804 (SIM)	A1/A-803		2	X					
113	FV	3'-0"	7'-0"	2"	STL	1	HM	FF	D3/A-804	C3/A-804	A2/A-803		12						
114	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D4/A-804	D4/A-804 (SIM)	A1/A-803		4	X					
115A	OH	12'-1"	12'-0"	6"	STL	3	STL	FF	C5/A-803	A2/A-804	B1/A-803	STL	21	X	X				MOTORIZED
115B	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D4/A-804	D4/A-804 (SIM)	A1/A-803		4	X					
115C	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D4/A-804	D4/A-804 (SIM)	A2/A-803		180 MIN	14					
115D	OH	12'-1"	12'-0"	6"	STL	3	STL	FF	C3/A-803	B1/A-804	A4/A-803 (SIM)	CONC	STL			X			HURRICANE RATED PERFORMANCE, MOTORIZED
115E	OH	12'-1"	12'-0"	6"	STL	3	STL	FF	C1/A-803	A1/A-804	A4/A-803 (SIM)	CONC	STL						MOTORIZED
115F	FV	3'-0"	7'-0"	2"	STL	1	HM	FF	D3/A-804	C3/A-804	A2/A-803		14						
116A	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D4/A-804	D4/A-804 (SIM)	A1/A-803		8	X					
116B	F	3'-0"	7'-0"	2"	STL	1	HM	FF	B3/A-804	B3 & B4/A-804 (SIM)	A2/A-803		180 MIN	6					
116C	F	3'-0"	7'-0"	1"	STL	1	HM	FF	B3/A-804	B3 & B4/A-804 (SIM)	A2/A-803		180 MIN	6					
116D	F	3'-0"	7'-0"	1"	STL	1	HM	FF	B3/A-804	B3 & B4/A-804 (SIM)	A2/A-803		180 MIN	6					
117A	F	3'-0"	7'-0"	1"	STL	1	HM	FF	B3/A-804	B3 & B4/A-804 (SIM)	A2/A-803		180 MIN	14					
117B	PFV	6'-0"	7'-0"	2"	STL	1	HM	FF	D3/A-804	C3/A-804	A2/A-803		10						
118A	OH	12'-1"	12'-0"	6"	STL	3	STL	FF	C3/A-803	B1/A-804	A4/A-803 (SIM)	CONC	180 MIN						HURRICANE RATED PERFORMANCE, MOTORIZED
118B	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D4/A-804	D4/A-804 (SIM)	A1/A-803		14	X					
119	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D5/A-804	C5/A-804	A1/A-803		5	X					
120	PF	6'-0"	7'-0"	2"	STL	2	HM	FF	D5/A-804	C5/A-804	A1/A-803		3	X					
121A	PF	6'-0"	7'-0"	2"	STL	2	HM	FF	D3/A-804	C3/A-804	A2/A-803		11						
121B	OH	12'-1"	12'-0"	6"	STL	3	STL	FF	C1/A-803	A2/A-804	A4/A-803	STL	21	X					MOTORIZED
122A	F	3'-0"	7'-0"	1"	STL	1	HM	FF	B3/A-804	B3 & B4/A-804 (SIM)	A2/A-803		180 MIN	14					
122B	OH	12'-1"	12'-0"	6"	STL	3	STL	FF	C3/A-803	B1/A-804	A4/A-803 (SIM)	CONC	180 MIN			X			HURRICANE RATED PERFORMANCE, MOTORIZED
122C	OH	12'-1"	12'-0"	6"	STL	3	STL	FF	C3/A-803	B1/A-804	A4/A-803 (SIM)	CONC	180 MIN						HURRICANE RATED PERFORMANCE, MOTORIZED
123A	F	3'-0"	7'-0"	2"	STL	1	HM	FF	B5/A-804	A6 & B5/A-804	A1/A-803		180 MIN	4	X				
123B	OH	12'-1"	12'-0"	6"	STL	3	STL	FF	B1/A-803	B1/A-804 (SIM)	A4/A-803	CONC	21	X			X		HURRICANE RATED PERFORMANCE, MOTORIZED
123C	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D4/A-804	D4/A-804 (SIM)	A1/A-803		4	X					
123D	OH	12'-1"	12'-0"	6"	STL	3	STL	FF	B1/A-803	B1/A-804 (SIM)	A4/A-803	CONC	21	X			X		HURRICANE RATED PERFORMANCE, MOTORIZED
123E	F	3'-0"	7'-0"	2"	STL	1	HM	FF	B5/A-804	A6 & B5/A-804	A1/A-803		180 MIN	4	X				
123F	F	3'-0"	7'-0"	2"	STL	1	HM	FF	B5/A-804	B5/A-804 (SIM)	A1/A-803		6	X					
123G	F	3'-0"	7'-0"	2"	STL	1	HM	FF	B5/A-804	B5/A-804 (SIM)	A1/A-803		6	X					
124A	PF	6'-0"	7'-0"	2"	STL	2	HM	FF	B3/A-804	B3/A-804 (SIM)	A2/A-803		10						
124B	F	3'-0"	7'-0"	2"	STL	1	HM	FF	B5/A-804	B5/A-804 (SIM)	A1/A-803		4	X					
125A	PFV	6'-0"	7'-0"	2"	STL	2	HM	FF	D3/A-804	C3/A-804	A2/A-803		11						
125B	PF	6'-0"	7'-0"	2"	STL	2	HM	FF	D4/A-804	D4/A-804 (SIM)	A1/A-803		1	X					
126	F	3'-0"	7'-0"	2"	STL	1	HM	FF	B5/A-804	B5/A-804 (SIM)	A1/A-803		6	X					
128A	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D4/A-804	D4/A-804 (SIM)	A1/A-803		4	X					
128B	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D4/A-804	D4/A-804 (SIM)	B5/A-803		4	X					
128C	OH	12'-1"	12'-0"	6"	STL	3	STL	FF	C1/A-803	A2/A-804	B1/A-803	STL	21	X	X				MOTORIZED
128D	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D4/A-804	D4/A-804 (SIM)	A1/A-803		4	X					
128E	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D4/A-804	D4/A-804 (SIM)	A1/A-803		4	X					
130	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D5/A-804	C5/A-804	A1/A-803		5	X					
131	PF	6'-0"	7'-0"	2"	STL	2	HM	FF	D5/A-804	C5/A-804	A1/A-803		3	X					
132	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D4/A-804	D4/A-804 (SIM)	A1/A-803		4	X					
133A	OH	14'-1"	17'-0"	6"	STL	3	STL	FF	C1/A-803 (SIM)	A1/A-804 (SIM)	A4/A-803 (SIM)	STL				X			HURRICANE RATED PERFORMANCE, MOTORIZED
133B	FV	3'-0"	7'-0"	2"	STL	1	HM	FF	B6/A-804	B6/A-804 (SIM)	A2/A-803		6						
133C	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D4/A-804	D4/A-804 (SIM)	A1/A-803		4	X					
134A	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D4/A-804	D4/A-804 (SIM)	A1/A-803		7	X					
134B	OH	8'-1"	8'-0"	0"	STL	2	HM	FF	C5/A-803	A2/A-804	A4/A-803	STL	21	X					HURRICANE RATED PERFORMANCE
O-01A	OH	17'-1"	17'-0"	6"	STL	3	STL	FF	C1/A-803 (SIM)	A1/A-804 (SIM)	A4/A-803 (SIM)	STL		X	X				MINERAL WOOL INSULATION, MOTORIZED
O-01B	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D6/A-804	C6/A-804	A1/A-803		6	X					
O-02A	OH	17'-1"	17'-0"	6"	STL	3	STL	FF	C1/A-803 (SIM)	A1/A-804 (SIM)	A4/A-803 (SIM)	STL		X	X				MINERAL WOOL INSULATION, MOTORIZED
O-02B	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D6/A-804	C6/A-804	A1/A-803		6	X					
O-03A	OH	17'-1"	17'-0"	6"	STL	3	STL	FF	C1/A-803 (SIM)	A1/A-804 (SIM)	A4/A-803 (SIM)	STL		X	X				MINERAL WOOL INSULATION, MOTORIZED
O-03B	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D6/A-804	C6/A-804	A1/A-803		6	X					
O-04A	OH	17'-1"	17'-0"	6"	STL	3	STL	FF	C1/A-803 (SIM)	A1/A-804 (SIM)	A4/A-803 (SIM)	STL		X	X				MINERAL WOOL INSULATION, MOTORIZED
O-04B	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D6/A-804	C6/A-804	A1/A-803		6	X					
O-05A	OH	17'-1"	17'-0"	6"	STL	3	STL	FF	C1/A-803 (SIM)	A1/A-804 (SIM)	A4/A-803 (SIM)	STL		X	X				MINERAL WOOL INSULATION, MOTORIZED
O-05B	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D6/A-804	C6/A-804	A1/A-803		6	X					
O-06A	OH	17'-1"	17'-0"	6"	STL	3	STL	FF	C1/A-803 (SIM)	A1/A-804 (SIM)	A4/A-803 (SIM)	STL		X	X				MINERAL WOOL INSULATION, MOTORIZED
O-06B	F	3'-0"	7'-0"	2"	STL	1	HM	FF	D6/A-804	C6/A-804	A1/A-803		6	X					

DOOR TYPES

FRAME TYPES

GENERAL SHEET NOTES

- A. REFER TO SPECIFICATION SECTION 08 71 00 FOR DOOR HARDWARE SCHEDULE.
- B. PROVIDE WEATHER STRIPPING AND RAIN DRIP AT ALL EXTERIOR DOORS.
- C. COORDINATE DOOR HARDWARE WITH FINAL SECURITY DESIGN AND LOCKING SCHEMES.
- D. ALL EXTER