

LUMINAIRE SCHEDULE									
TYPE MARK	DESCRIPTION	VOLTAGE	COLOR TEMPERATURE	CRI	LAMP	LUMINAIRE WATTS	DELIVERED LUMENS	MOUNTING TYPE	REMARKS
A1	HIGH BAY LIGHTING; RATED CLASS I DIVISION 2, HOLOPHANE LIGHTING: PXHH-24000LM-MD0-MVOLT-40K-80CRI	MVOLT	4000K	80	LED	165	24,000	SUSPENDED	
A2	HIGH BAY LIGHTING; RATED CLASS II DIVISION 1, HOLOPHANE LIGHTING: HPLED-42LED-L5H-MVOLT-40K-UNM-530MA-40C	MVOLT	4000K	70	LED	75	7,500	SUSPENDED	
B1	HIGH BAY LIGHTING; RATED WET LOCATION, CORROSION, SEALED AND GASKET, HOLOPHANE LIGHTING: PXHW-24000LM-MDO-MVOLT-40K-80CRI	MVOLT	4000K	80	LED	165	24,000	SUSPENDED	
C1	2X2 TROFFER PANEL, DIMMING, COOPER LIGHTING: 22FP3240C	120	4000K	80	LED	29	3,333	RECESSED	
D1	2X4 TROFFER PANEL, DIMMING, COOPER LIGHTING: 24FP470C	120	4000K	80	LED	41	4,556	RECESSED	
F1	CAN DOWNLIGHT, DIMMING, PORTFOLIO LIGHTING: LD4D-20-R60-90-40	120	4000K	80	LED	24	2,000	RECESSED	
F2	CAN DOWNLIGHT, DIMMING, PORTFOLIO LIGHTING: LD4D-15-R60-90-35	120	3500K	90	LED	16	1,500	RECESSED	
G1	4FT LINEAR INDUSTRIAL, METALUX LIGHTING: 4SNX-60SL-LC-UNV-L840-CD-1	120	4000K	80	LED	42	6,400	SUSPENDED	
G2	4FT LINEAR INDUSTRIAL, METALUX LIGHTING: 4SNX-20SL-LC-UNV-L835-CD-1	120	3500K	80	LED	12	3,300	RECESSED	
H1	EXPLOSION PROOF CLASS I DIVISION 1 ROUND, LED LIGHTING SUPPLY: MLLG-E-LED-EXPLC-100-50-C1D1-140F	MVOLT	5000K	70	LED	100	14,000	SURFACE	
J1	4FT VAPORTIGHT LINEAR INDUSTRIAL, METALUX LIGHTING: 4VT2-LD5-4-DR-UNV-L840-CD1-WL-	120	4000K	80	LED	30	4,000	SURFACE	
K1	FLOODLIGHT, HOLOPHANE LIGHTING: PMLED-P1-40K-MVOLT-55-GHSDP-WL	120	4000K	80	LED	265	38,000	SURFACE	
L1	INDIRECT LINEAR 4 FT, CORELITE LIGHTING: SQ4-150U-OD-830-1-D-UNV-STD-W-4	120	3000K	80	LED	52	1,500	SUSPENDED	
L2	DIRECT/INDIRECT LINEAR 4 FT, CORELITE LIGHTING: SQ4-50U-100D-840-1-D-UNV-STD-W-4	120	4000K	80	LED	45	500 UP; 1,000 DOWN	SUSPENDED	
L3	DIRECT LINEAR 4 FT, CORELITE LIGHTING: SQ4-0U-100D-840-1-D-UNV-STD-W-4	120	4000K	80	LED	33	1,000	SURFACE	
M1	LINEAR; RATED CLASS I DIVISION 2, HOLOPHANE LIGHTING: HEXS-L2-MV-4K-T6M-FG	MVOLT	4000K	70	LED	40	3,520	SURFACE	
W1	WALL PACK WITH FULL CUTOFF, HOLOPHANE LIGHTING: HLWPC2-P20-40K-120-T3M-BZSDP-MASH-PE-EM	120	4000K	80	LED	47	5,000	SURFACE	
X1	EXIT SIGN WITH BATTERY BACKUP, HOLOPHANE LIGHTING: MEX-1-R-SD	120			LED			UNIVERSAL	
X2	EXIT SIGN WITH BATTERY BACKUP, HOLOPHANE LIGHTING: MEX-1-R-SD	120			LED			UNIVERSAL	
X3	EXIT SIGN HAZARDOUS RATED, HOLOPHANE LIGHTING: HDXE-1-R-12/27-PW	120			LED			UNIVERSAL	

NOTES:

1. SELECT PRODUCTS THAT MEET ALL LUMINAIRE PERFORMANCE CRITERIA AND, AT A MINIMUM, HAVE AN EFFICACY (LUMENS PER WATT) NO LESS THAN THE BASIS OF DESIGN.
2. PROVIDE BATTERY BACKUP FOR LIGHTING FIXTURES WITH TYPE MARK WITH SUFFIX 'E' UNLESS OTHERWISE NOTED.
3. NO BATTERY BACK-UP NEEDED FOR GMLRS BLDG SINCE TYPE MARK WITH SUFFIX "E" LIGHTING FIXTURES ARE CONNECTED TO LIFE SAFETY GENERATOR

[illegible]