MOUNT 1/2" X 1
MOUNT 1/2" X 1 TACK W SPACE F INSTALI NOTES: 1. STYLE A (BLADE STACK
SUBMIT SUPPORTING E 2. FDs SHALL HAVE A RAT SHALL BE RATED FOR 1 3. IN WOOD CONSTRUCT 4. ACCESS DOOR SHALL B DOORS MAY BE FACTOR 5. PROVIDE FIRE CAULK A ASSEMBLY COMES IN C
SURFACE. HILTI FS -ON
slee Sam Gau Duc (Min
 MOUNTING ANGLE MINIMUM 1 1 STYLE A (BLADE STACK IN SUPPORTING DATA FOR E FDs SHALL HAVE A RATING RATED FOR 1 1/2 HOURS I IN WOOD CONSTRUCTION ACCESS DOOR SHALL BE I BE FACTORY MOUNTED. A PROVIDE FIRE CAULK APP ASSEMBLY COMES IN CON HILTI FS -ONE SP606 OR E
HORIZONTA
VERTICAL F
TURN ROOFING AND DUCT OVER CURB
ROOFING
мото
POWER ROC

COPYRIGHT AND NOTES: THE COPYRIGHT FOR THIS PROJECT IS VESTED IN THE ARCHITECT. VERIFY ALL DIMENSIONS AND LEVELS ON SITE. DISCREPANCIES TO BE REPORTED IMMEDIATELY TO THE ARCHITECT. DRAWINGS TO BE READ IN CONJUNCTION WITH THE SPECIFICATION. DO NOT SCALE OFF DRAWINGS.

