

SECTION 10 28 00 - TOILET AND BATH ACCESSORIES

PART 1 - GENERAL

1.01 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 1 Specification Sections, apply to this Section.

1.02 SUMMARY

- A. This Section includes toilet accessory items as scheduled or specified below.

1.03 RELATED SECTIONS

Section 06 01 00 - Rough Carpentry

1.04 SUBMITTALS

- A. General: Submit the following according to Conditions of Contract and Division 1 Specifications Sections.
- B. Product data for each toilet accessory item specified, including construction details relative to materials, dimensions, gages, profiles, mounting method, specified options, and finishes.
- C. Schedule indicating types, quantities, sizes, and installation locations (by room) for each toilet accessory item to be provided for project.

1.05 QUALITY ASSURANCE

- A. Inserts and Anchorages: Furnish accessory manufacturers' standard inserts and anchoring devices that must be set in concrete or built into masonry. Coordinate delivery with other work to avoid delay.

1.06 PROJECT CONDITIONS

- A. Coordination: Coordinate accessory locations, installation, and sequencing with other work to avoid interference with and ensure proper installation, operation, adjustment, cleaning, and servicing of toilet accessory items.

PART 2 - PRODUCTS

2.01 ACCESSORIES

- A. Grab Bars - Stainless Steel Type: Provide grab bars with wall thickness not less than 0.05" and as follows:

1. Mounting: Concealed, manufacturer's standard flanges and anchorages.
 2. Clearance: 1-1/2" clearance between wall surface and inside face of bar.
 3. Gripping Surfaces: Smooth, satin finish.
 4. Heavy-Duty Size: Outside diameter of 1-1/2".
 5. Grab bars shall be 42", 36", and/or 18" long as shown on Drawings.
- B. Mirror: Bobrick 165 Series Mirror with stainless steel angled frame. Size to be as shown on Drawings, or equal.
- C. Paper Towel & Dispenser: By Owner
- D. Soap Dispenser: By Owner.
- E. Toilet Tissue Dispenser: By Owner.
- F. Mop Rack: Bobrick, 223 36.
- G. Shower Curtain Rod: Bobrick B-6107.
- H. Coat Hook: Bobrick, 212. To be located in each restroom with a shower.

PART 3 – EXECUTION

3.01 INSTALLATION

- A. Install toilet accessory units according to manufacturers' instructions, using fasteners appropriate to substrate as recommended by unit manufacturer. Install units plumb and level, firmly anchored in locations and at heights indicated.
- B. Install grab bars to withstand a downward load of at least 250 lbf, complying with ASTM F 446.

3.02 ADJUSTING AND CLEANING

- A. Adjust toilet accessories for proper operation and verify that mechanisms function smoothly. Replace damaged or defective items.
- B. Clean and polish all exposed surfaces strictly according to manufacturer's recommendations after removing temporary labels and protective coatings.

END OF SECTION