

## SECTION 10 28 13

### TOILET AND BATH ACCESSORIES

#### PART 1 GENERAL

##### 1.1 SUMMARY

- A. The work to be completed under this heading consists of furnishing all labor, materials, equipment and services necessary for and reasonably incidental to the furnishing and application of all miscellaneous items as shown and as specified.
- B. All items shall be delivered in sound condition, properly installed and shall be clean, undamaged, and in proper working order.

##### 1.2 SUBMITTALS

- A. Comply with requirements of Section 01 33 00.

##### 1.3 REFERENCES

- A. Comply with State of Arkansas Adopted ADA Accessible Guidelines in regard to accessible or handicapped features.

#### PART 2 PRODUCTS

##### 2.1 OWNER FURNISHED TOILET ACCESSORIES:

- A. Owner will furnish soap dispensers, tissue dispensers, paper towel dispensers, and sanitary napkin disposals. These items are to be installed by contractor.

##### 2.2 TOILET ACCESSORIES:

- A. Mop Racks: (One for each mop or service sink shown on drawings.)
  - 1. Stainless steel, satin finish; anti-slip mop holders with spring loaded, rubber cam w/3 holders.
    - a. Bobrick Washroom Equipment, Inc., Model B-223 x 24
    - b. Bradley Corp. Model 9953.
    - c. Approved alternate.
- B. Pre-manufactured Wall Mounted Mirrors:
  - 1. Standard Stainless Steel Mirrors:
    - a. Surface mounted, center over each lavatory, 304 stainless steel, satin finish frame with No. 1 quality 1/4" glass, mirror warranted against silver spoilage for 15yrs. Galvanized steel back, 18"x36". Secure to concealed wall hanger with theft-resistant mounting. Mounting height as scheduled on Drawings.
    - b. Acceptable Products:

10 28 13-1

Bobrick Washroom Equipment, Inc. - Model B-290-1836  
Bradley Corporation, Model 780-1836

- C. Grab Bar-Toilet Rooms: (One set at each handicapped water closet.)
  - 1. 18 gage stainless steel; 1 1/2" diameter, safety grip surface; concealed mounting. One at each handicapped water closet.
    - a. Model No. B6806.99 x 42, B6806.99 x 36 & B6806.99 x 18 by Bobrick.
    - b. Model No. 8122-00142, 8122-00136 & 8122-00118 by Bradley.
    - c. Or approved alternate.
- D. Grab Bar-Shower Stall: (One at each site-built shower stall.)
  - 1. 18 gage stainless steel; 1 1/2" diameter, safety grip surface; concealed mounting. One at each handicapped shower.
    - a. Model No. B-6861 (one piece, mounted on two walls, 15 7/8 x 26 7/8) by Bobrick, Bradley, or approved alternate.
  - 2. at walk-in
- E. Shower Curtain Rod: (one, each site-built shower.)
  - 1. Model No. B6107 x 56" by Bobrick
  - 2. Model No. 9531 x 56" by Bradley
  - 3. Or approved alternate.
- F. Shower Curtains
  - 1. 80" high, 6 gauge vinyl, white, manufactured by Gary Manufacturing, 800-775-0804, or approved alternate.
  - 2. Provide with non-rusting hooks and aluminum grommets.
  - 3. Width as required to close opening of each shower stall.
- G. Folding Shower Seat (one each site-built handicapped shower)
  - 1. Acceptable Products
    - a. Bobrick Washroom Equipment, Inc., Model B-5181; B5171 (verify left hand or right hand seat) - phenolic slats.
    - b. Approved alternate.
- H. Towel Hooks (1 for each shower stall)
  - 1. Acceptable Products
    - a. Bobrick Washroom Equipment, Inc., Model B-211
    - b. Approved alternate
- I. Shower Soap Holder (each shower)
  - 1. 16 gauge stainless steel with (2) drain holes.
  - 2. Acceptable Products
    - a. Model No. B-6807 by Bobrick
    - b. Model No. 9014 by Bradley
    - b. Approved alternate

- J. Hand/Hair Dryer (refer to enlarged floor plans for location and quantity).
  - 1. a operation, surface mounted installation, swivel nozzle, white finish, 115V, 15 amp.
    - a. Model B1, manufactured by World Dryer.
    - b. Approved alternate
- K. Hand Dryer (refer to enlarged floor plans for location and quantity.)
  - 1. Automatic operation, surface mounted installation, white finish, 120V, 500 watt.
    - a. "Xlerator "XL" series, high speed, manufactured by Excel Dryer, 357 Chestnut Street, East Longmeadow, MA 01028 Ph: (413) 525-4531.
    - b. Approved alternate
  - 2. Colors to be selected from manufacturer's standard selections.

## PART 3 EXECUTION

### 3.1 FABRICATION:

- A. Stamped names or labels on exposed faces of toilet accessory units are not permitted. Wherever locks are required for particular type of accessory, provide same keying throughout project. Furnish two keys for each lock, properly identified.
- B. Surface Mounted Accessories: Fabricate units with tight seams and joints, exposed edges rolled. Hang doors or access panels with continuous piano hinge or minimum of two 1 1/2" pin hinges of same metal as unit cabinet. Provide concealed anchorage wherever possible.

### 3.2 INSTALLATION:

- A. Install toilet accessory units in accordance with manufacturer's instructions, using fasteners appropriate to substrate and recommended by manufacturer of unit.
- B. Install units at location and heights as shown on drawings. Install as to comply with all national, state, and local codes and regulations. Units shall be plumb and level, firmly anchored.
- C. If mirrors are installed on ceramic tile, coordinate tile pattern and layout to accommodate mirrors. Mirror to be installed on single plane.
- D. Molly-type anchors are not acceptable for securing accessories to walls or partitions. Secure to gypsum board partitions with screws anchored in wood blocking. Anchor accessories to masonry walls with screws set in epoxy.

### 3.3 ADJUSTING AND CLEANING:

- A. Adjust toilet accessories for proper operation and verify that mechanisms function smoothly.
- B. Clean and polish all exposed surfaces after removing protective coatings.

END OF SECTION

10 28 13-3