

SECTION 10 11 00

VISUAL DISPLAY SURFACES

PART 1 GENERAL

1.1 SUMMARY

- A. Section includes:
 - 1. Porcelain Enamel Steel Markerboards

1.2 RELATED SECTIONS

- A. Section 05 41 00 - Cold Formed Framing
- B. Section 06 10 00 - Rough Carpentry - Blocking
- C. Section 06 41 16 - Cabinetwork & Shelving
- D. Section 06 40 23 - Interior Architectural Woodwork
- E. Section 09 29 00 - Drywall

1.3 SHOP DRAWINGS/SUBMITTALS

- A. Complete materials list of all items proposed to be furnished under this section.
- B. Comply with Section 01 33 00.
- C. Manufacturer's recommended installation procedures.
- D. Samples: Provide Manufacturer's color charts and composition samples of face, core, backing and trim to illustrate finish, color and texture, where required.

1.4 DELIVERY AND STORAGE

- A. Deliver all manufactured materials in original containers bearing manufacturer's name and brand. Store materials within building in locations directed by Owner.

1.5 WARRANTY

- A. Provide a manufacturer's standard "Life-Of-Building" warranty for markerboard surface.

10 11 00-1

PART 2 PRODUCTS

2.1 GENERAL REQUIREMENTS

- A. The Manufacturer of products used in this section must have an established reputation and experience in production similar apparatus for at least five or more years in the United States, with a history of satisfactory production acceptable to the Architect.
- B. Conforms to applicable code for flame/smoke rating in tack boards in accordance with ASTM E84.

2.2 PRODUCTS

- A. Markerboards and tackboards specified are to be manufactured by Claridge Products and Equipment, Inc., Peter Pepper Products, Gamco, Greensteel, or approved alternate. Items specified herein will be Claridge models.
- B. Fixed Markerboard
 - 1. Arrangement as shown on drawings, Series 4, 4'-0" high Length as scheduled on drawings. Frame color to be standard anodized aluminum.
 - At Marker boards - Provide with continuous flat tray and 1" map rail with cork insert at markerboard only.
 - 2. Markerboard to be LCS³ #100 Low Gloss White (marker and projection surface), 24-gauge, white porcelain enamel steel.

PART 3 EXECUTION

3.1 PREPARATION

- A. Coordinate installation of all concealed blocking in wall for attachment.

3.2 INSTALLATION

- A. Comply with manufacturer's instructions. Provide all accessories as required for complete installation
- B. Hang units true and plumb.
- C. All attachments are to be concealed. No exposed fastener clips.

3.3 PROTECTION

- A. Protect units after installation from other trades.

3.4 SCHEDULES

- A. Refer to drawings for sizes and locations

END OF SECTION

10 11 00-2