

**WILLIAM J CLINTON  
PRESIDENTIAL  
CENTER**

LITTLE ROCK, ARKANSAS

Architect  
POLSHEK PARTNERSHIP LLP  
320 West 13th Street  
New York, New York 10014  
212.607.7171

Coordinating Architects  
POLK STANLEY YEARY ARCHITECTS Ltd  
700 South Schlar Street  
Little Rock, Arkansas 72201  
501.378.0878

WITSELL EVANS RASCO  
501 West Third Street  
Little Rock, Arkansas 72201  
501.374.5300

WOODS CARADINE ARCHITECTS  
2200 South Main Street  
Little Rock, Arkansas 72206  
501.374.4060

Landscape Architects  
HARGREAVES ASSOCIATES  
118 Magazine Street  
Cambridge, Massachusetts 02139  
617.651.0070

LANDSCAPE ARCHITECTURE Inc.  
2300 Cottondale Lane Suite 202  
Little Rock, Arkansas 72202  
501.374.5610

Structural Engineer  
LESLIE E. ROBERTSON ASSOC. RLLP  
30 Broad Street, 47th Floor  
New York, New York 10004  
212.750.9000

MEP Engineers  
FLACK + KURTZ Inc.  
475 Fifth Avenue  
New York, New York 10017  
212.532.9600


CROMMELL ARCHITECTS ENGINEERS  
101 South Spring Street  
Little Rock, Arkansas 72201  
501.372.2800

Curtainwall Consultant  
R. A. HEINTGES ARCHITECTS  
126 Fifth Avenue, 9th Floor  
New York, New York 10011  
212.652.2868

Seal



100% Construction Documents	09/27/02
90% Progress Printing	08/30/02
100% Struct./CD Progress	07/01/02
100% Design Development	03/01/02
Issue	Date



Job No. 9908  
Scale AS NOTED  
Date September 27, 2002  
Title

**PARTITION  
TYPES**

Sheet No.

**A400**

FOR OFFICIAL USE ONLY

**F** APPLIED FURRING  
SCALE 1/2" = 1'-0"

ADDITIONAL CONSTRUCTION FOR GALLERY WALL TYPES  
SCALE 1/2" = 1'-0"

**E** FURRING WALL  
SCALE 1/2" = 1'-0"

**D** SHAFT WALL  
SCALE 1/2" = 1'-0"

**C** CHASE WALL  
SCALE 1/2" = 1'-0"

**B** STUD WALL  
SCALE 1/2" = 1'-0"

**A** CMU WALL  
SCALE 1/2" = 1'-0"

TYPE	NOMINAL SIZE	MAX HEIGHT	INSUL GAUGE	FIRE RATING	REMARKS
F00	VARIES	3/4"	N/A	N/A	N/A
F02	VARIES	3/4"	N/A	N/A	N/A
E00	VARIES	8'-3"	25	NONE	GWB TO 6" ABOVE CEILING
E02	VARIES	8'-3"	25	NONE	N/A
E04	VARIES	8'-3"	25	NONE	N/A
E10	VARIES	11'-0"	20	NONE	GWB TO 6" ABOVE CEILING
E12	VARIES	11'-0"	20	NONE	N/A
E14	VARIES	17'-0"	20	NONE	N/A
E20	VARIES	14'-6"	20	NONE	GWB TO 6" ABOVE CEILING
E22	VARIES	14'-8"	20	NONE	N/A
E24	VARIES	14'-8"	20	NONE	N/A
E30	VARIES	20'-0"	20	NONE	GWB TO 6" ABOVE CEILING
E32	VARIES	20'-0"	20	NONE	N/A
E34	VARIES	20'-0"	20	NONE	N/A
D00	2 1/2"	14'-0"	20	1 HOUR	VERIFY AT ELEV CORES
D02	2 1/2"	15'-3"	20	2 HOUR	VERIFY AT ELEV CORES
D04	2 1/2"	15'-3"	20	2 HOUR	VERIFY AT ELEV CORES
D10	4"	17'-6"	20	1 HOUR	VERIFY AT ELEV CORES
D12	4"	18'-2"	20	2 HOUR	VERIFY AT ELEV CORES
D14	4"	18'-2"	20	2 HOUR	VERIFY AT ELEV CORES
D20	6"	24'-3"	20	1 HOUR	VERIFY AT ELEV CORES
D22	6"	25'-7"	20	2 HOUR	VERIFY AT ELEV CORES
D24	6"	25'-7"	20	2 HOUR	VERIFY AT ELEV CORES
C00	2 1/2"	13'-3"	25	NONE	GWB TO 6" ABOVE CEILING
C02	2 1/2"	13'-3"	25	NONE	N/A
C04	2 1/2"	14'-6"	25	2 HOUR	N/A
C10	2 1/2"	17'-6"	20	NONE	N/A
C12	2 1/2"	17'-6"	20	1 HOUR	N/A
C14	2 1/2"	19'-0"	20	2 HOUR	N/A
C20	3 1/2"	22'-9"	20	NONE	N/A
C22	3 1/2"	22'-9"	20	1 HOUR	N/A
C24	3 1/2"	23'-6"	20	2 HOUR	N/A
B00	2 1/2"	13'-0"	20	NONE	GWB TO 6" ABOVE CEILING
B02	2 1/2"	13'-10"	20	NONE	N/A
B04	2 1/2"	13'-10"	20	1 HOUR	N/A
B06	2 1/2"	16'-1"	20	2 HOUR	N/A
B10	3 1/2"	17'-3"	20	NONE	GWB TO 6" ABOVE CEILING
B12	3 1/2"	17'-11"	20	NONE	N/A
B14	3 1/2"	17'-11"	20	1 HOUR	N/A
B16	3 1/2"	17'-11"	20	3/4 HR	N/A
B18	3 1/2"	20'-2"	20	2 HOUR	N/A
B20	6"	25'-6"	20	NONE	N/A
B22	6"	26'-7"	20	NONE	N/A
B24	6"	26'-1"	20	1 HOUR	N/A
B26	6"	26'-1"	20	3/4 HR	N/A
B28	6"	28'-6"	20	2 HOUR	N/A
B30	6"	28'-6"	20	4 HOUR	NON-LOAD BEARING
B32	6"	20'-2"	20	3 HOUR	NON-LOAD BEARING
B34	6"	20'-2"	20	N/A	"C" WALL SUPPORT

**GENERAL NOTES**

- SEE PARTITION DETAIL DRAWING XXXX AND PROJECT SPECIFICATIONS FOR SEISMIC DETAILS AND PERFORMANCE CRITERIA FOR ALL STUD AND MASONRY PARTITIONS
- INSTALL CEMENTITIOUS BACKER BOARD IN LIEU OF GYPSUM WALL BOARD AT LOCATIONS INDICATED TO RECEIVE WALL TILE
- INSTALL WATER RESISTANT GYPSUM WALL BOARD AT SURFACES IN TOILET ROOMS, JANITORS CLOSETS, AND SIMILAR WET AREAS NOT INDICATED TO RECEIVE WALL TILE
- INSTALL TYPE "X" FIRE RATED GWB AT ALL FIRE RATED PARTITIONS
- INSTALL BLUEBOARD® GYPSUM WALL BOARD AT PARTITIONS INDICATED TO RECEIVE VENEER PLASTER
- STC RATINGS PROVIDE ONLY A GENERAL INDICATION OF ACOUSTIC PERFORMANCE UNDER LABORATORY TEST CONDITIONS. CONSTRUCTION DETAILS DESCRIBED IN THE DRAWINGS AND SPECIFICATIONS DEFINE THE SPECIFIC REQUIREMENTS FOR THE WORK.
- EXTRA LAYER OF GYPSUM WALL BOARD AT ASYMMETRICAL PARTITIONS IS TO BE INSTALLED ON SIDE OF PARTITION WHICH TYPE KEY IS SHOWN