



LEGEND

- INDICATES BRACED FRAME ELEVATION (SHEET LOCATION)
- INDICATES BRACED FRAME LOCATION
- INDICATES STRUCTURAL FRAMING MEMBER SIZE
- INDICATES MAXIMUM FACTORED AXIAL LOAD IN KIPS
- INDICATES MAXIMUM FACTORED VERTICAL REACTION IN KIPS (PER END)
- INDICATES STRUCTURAL FRAMING MEMBER LOCATION
- INDICATES MOMENT CONNECTION WHERE OCCURS (SEE S-402)
- INDICATES DECK SPAN DIRECTION

- NOTES:**
1. 4" SOLID TONGUE AND GROOVE DECK SINGLE SPAN DECKING. SEE NOTE 5 ON S103 FOR PLYWOOD SHEATHING OVER WOOD DECK.
 2. 3" SOLID TONGUE AND GROOVE DECK RUN DECKING MIN 2 SPAN CONTINUOUS. SEE NOTE 5 ON S103 FOR PLYWOOD SHEATHING OVER WOOD DECK.
 3. W-19-4 (1 1/2 x 1/8) GALVANIZED STEEL GRATING. FABRICATE GRATING IN FULL WIDTH INDICATED. ANCHOR TO SUPPORTS EACH END WITH REMOVABLE CLIPS. PROVIDE BANDING BARS AT LONG SIDES AND EXPOSED ENDS.
 4. W-19-4 (2 1/2 x 3/16) GALVANIZED STEEL GRATING. FABRICATE GRATING IN FULL WIDTH WITH A SIMPLE SPAN. ANCHOR TO SUPPORTS EACH END WITH REMOVABLE CLIPS. PROVIDE BANDING BARS AT LONG SIDES AND EXPOSED ENDS.
 5. TAPER BEAM ENDS (SEE 31A/414)
 6. ATTACH GLULAM TO STEEL BEAMS WITH 1/2" LAG SCREWS, TWO EACH END THEN STAGGERED EQUALLY ALONG STEEL BEAM FLANGE.

1 HIGH ROOF FRAMING PLAN
1/8" = 1'-0"
TOP OF STEEL BEAMS = DECK BEARING - 1 1/2" (U.N.O.)

