

INTERIOR MATERIAL LEGEND						
MARK	DESCRIPTION	MANUFACTURER	SIZE	MODEL NAME	COLOR	REMARKS
FLOOR						
EXCONC	EXISTING CONCRETE	EXISTING	N/A	EXISTING	EXISTING	EXISTING CONCRETE TO BE CLEANED AND PREPPED PER MANUFACTURER RECOMMENDATIONS FOR INSTALLATION OF NEW MATERIALS.
LVT1	LUXURY VINYL TILE	J&J FLOORING	9 IN X 48 IN (5MM)	TIMELESS II - 5MM	RARITY 1091	FOLLOW MANUFACTURERS TECHNICAL DATA SHEETS FOR PREP OF SLAB AND INSTALLATION INSTRUCTIONS. 1/3 BROKEN JOINT STAGGER INSTALL METHOD.
LVT2	LUXURY VINYL TILE	J&J FLOORING	9 IN X 48 IN	TIMELESS II - 5MM	BENCHMARK1088	FOLLOW MANUFACTURERS TECHNICAL DATA SHEETS FOR PREP OF SLAB AND INSTALLATION INSTRUCTIONS. 1/3 BROKEN JOINT STAGGER INSTALL METHOD.
CPT1	CARPET TILE - 1ST FLOOR BEDROOMS	J&J FLOORING	24 IN X 24 IN	CRAFTWORK 7099	POTTER 2100	ASHLAR INSTALLATION METHOD
CPT2	CARPET TILE - 1ST FLOOR COMMON AREAS	J&J FLOORING	24 IN X 24 IN	OBSDIAN 7718	FELDSPAR 2960	ASHLAR INSTALLATION METHOD
CPT3	CARPET TILE - 2ND FLOOR BEDROOMS	J&J FLOORING	24 IN X 24 IN	CRAFTWORK 7099	METAL SMITH 3318	ASHLAR INSTALLATION METHOD
CPT4	CARPET TILE - 2ND FLOOR COMMON AREAS	J&J FLOORING	24 IN X 24 IN	OBSDIAN 7718	MARBLE 2966	ASHLAR INSTALLATION METHOD
CPT5	CARPET TILE - 3RD FLOOR BEDROOMS	J&J FLOORING	24 IN X 24 IN	CRAFTWORK 7099	QUILTER 2205	ASHLAR INSTALLATION METHOD
CPT6	CARPET TILE - 3RD FLOOR COMMON AREAS	J&J FLOORING	24 IN X 24 IN	OBSDIAN 7718	SHALE 2967	ASHLAR INSTALLATION METHOD
PT1	PORCELAIN TILE - FLOOR	TILEBAR	12 IN X 24 IN	BRONX	SILVER ARGENT	INSTALL PARALLEL TO DOOR THRESHOLD: 1/3 BROKEN JOINT STAGGER; FOLLOW MANUFACTURER'S TECHNICAL DATA SHEET FOR PREP OF SLAB AND PRODUCT INSTALLATION.
CONC / H	CONCRETE HARDNER SEALER	SHERWIN WILLIAMS	N/A	CEMLACK DENSIFIER	CLEAR	FOLLOW MANUFACTURER'S TECHNICAL DATA SHEETS FOR PREP OF SLAB, PRIME AND PRODUCT APPLICATION.
MT1	MARBLE FLOOR TRANSITION	TN MARBLE COMPANY	VARIES	MARBLE FLOOR TRANSITION	QUAKER GRAY	FOLLOW MANUFACTURER'S TECHNICAL DATA SHEETS FOR PREP OF SLAB, PRIME AND PRODUCT APPLICATION. 2 IN - 4 IN WIDE MECHANICALLY OR ADHESIVE ATTACHED EXTRUDED ALUMINUM TRANSITIONS REQUIRED AT ALL FLOOR TYPES AND STAIRS CHANGES EXCLUDING BEDROOMS LVT TO CPT.
MT2	METAL FLOOR TRANSITION	WOOSTER PRODUCTS	2IN - 4IN X MAX 5/16 IN H	ALUMOGRIT CAST THRESHOLD 110	STANDARD	FOLLOW MANUFACTURER'S TECHNICAL DATA SHEETS FOR PRODUCT APPLICATION. 2 IN - 4 IN WIDE MECHANICALLY OR ADHESIVE ATTACHED EXTRUDED ALUMINUM TRANSITIONS REQUIRED AT ALL FLOOR TYPE TRANSITIONS AND STAIRS. THIS EXCLUDES BEDROOMS LVT TO CPT.
MT3	METAL FLOOR TRANSITION	SCHLUTER	VARIES	VINPRO U	BRUSHED STAINLESS	LVT TO CARPET APPLICATIONS. FOLLOW MANUFACTURER'S TECHNICAL DATA SHEETS FOR PRODUCT APPLICATION.
ESP	EPOXY SHOWER PAN	SEE PLUMBING	VARIES	EPOXY SHOWER PAN	TBD	ABA APPROACH REQUIRED.
WALL						
GWB	GYPSUM WALL BOARD	DUROCK	5/8 IN	GYPSUM WALL BOARD	WHITE	LEVEL 4 FINISH.
CGWB	GYPSUM WALL BOARD - CONCRETE	DUROCK	5/8 IN	CONCRETE GYPSUM WALL BOARD	WHITE	WET, TILED SURFACES AND SHOWERS. LEVEL 4 FINISH.
RB	RUBBER BASE	TARKETT	4 IN	BASEWORKS - TRADITIONAL TOE	GATEWAY TA4	CONTINUOUS ROLL STOCK SEAMED AT CORNERS.
P1	PAINT - TYPICAL PAINT	SHERWIN WILLIAMS	N/A	PROMAR 200 ZERO VOC PRIMER - ONE COAT + PROMAR 200 ZERO VOC - 2 COATS - SATIN FINISH	TOQUE WHITE SW 703	FOLLOW MANUFACTURER'S TECHNICAL DATA SHEETS FOR PRIMING AND PAINTING. LEVEL 4 FINISHES ALL ON GYPSUM BOARD WALLS.
P2	PAINT - ACCENT WALL	SHERWIN WILLIAMS	N/A	PROMAR 200 ZERO VOC PRIMER - ONE COAT + PROMAR 200 ZERO VOC - 2 COATS - EGGSHELL FINISH	DEBONAIR SW 9139	FOLLOW MANUFACTURER'S TECHNICAL DATA SHEETS FOR PRIMING AND PAINTING. LEVEL 4 FINISHES ALL ON GYPSUM BOARD WALLS.
P3	PAINT - TYPICAL PAINT	SHERWIN WILLIAMS	N/A	PROMAR 200 ZERO VOC PRIMER - ONE COAT + PROMAR 200 ZERO VOC - 2 COATS - SEMI GLOSS FINISH	TOQUE WHITE SW 703	FOLLOW MANUFACTURER'S TECHNICAL DATA SHEETS FOR PRIMING AND PAINTING. LEVEL 4 FINISHES ALL ON GYPSUM BOARD WALLS.
P6	PAINT - TYPICAL PAINT	SHERWIN WILLIAMS	N/A	LOXON CMU PRIMER - ONE COAT + PROMAR 200 ZERO VOC - 2 COATS - SEMI GLOSS FINISH	TOQUE WHITE SW 703	FOLLOW MANUFACTURER'S TECHNICAL DATA SHEETS FOR PRIMING AND PAINTING. LEVEL 4 FINISHES ALL ON GYPSUM BOARD WALLS.
CT1	CERAMIC TILE - WALL FIELD	TILEBAR / US CERAMIC TILE	6 IN X 6 IN	COLOR COLLECTION	U761 TENDER GRAY BRIGHT	HORIZONTAL 1/2 RUNNING BOND : FOLLOW MANUFACTURER'S TECHNICAL DATA SHEET FOR PREP OF SLAB AND PRODUCT INSTALLATION.
CT2	CERAMIC TILE - WALL FIELD	TILEBAR / US CERAMIC TILE	6 IN X 6 IN	COLOR COLLECTION	U769 DARK GRAY BRIGHT	VERTICAL STACKED PRIVATE BATH INSTALLATION. HORIZONTAL 1/2 RUNNING BOND BREAKROOM INSTALLTION : FOLLOW MANUFACTURER'S TECHNICAL DATA SHEET FOR PREP OF SLAB AND PRODUCT INSTALLATION.
PT2	PORCELAIN TILE - BASE	TILEBAR	6 IN X 12 IN	BRONX	SILVER ARGENT	LINE JOINTS UP WITH WALL TILE: FOLLOW MANUFACTURER'S TECHNICAL DATA SHEET FOR PREP OF SLAB AND PRODUCT INSTALLATION.
FRP	FIBERGLASS REINFORCED PANEL	MARLITE	STANDARD	PEBBLED CLASS A	P145 SILVER	
WJ	WALL JOLLY	SCHLUTER	VARIES	JOLLY	ALUMINUM	FOLLOW MANUFACTURER'S TECHNICAL DATA SHEETS FOR PREP, PRIME AND PRODUCT APPLICATION. SEE ELEVATIONS FOR PLACEMENT.
CEILINGS						
GWB	GYPSUM WALL BOARD	DUROCK	5/8 IN	GYPSUM WALL BOARD	WHITE	LEVEL 4 FINISH.
ACOUST	EXISTING ACOUSTICAL CEILING TILE	ARMSTRONG	EXISTING	EXISTING	MATCH EXISTING	EXISTING ACOUSTICAL CEILING TO BE REMOVED, SUBSTRATES TO BE REPAIRED AND NEW ACT TO BE INSTALLED PER MANUFACTURERS RECOMMENDATIONS.
ACT	ACOUSTICAL CEILING TILE - TYP	ARMSTRONG	24 IN X 24 IN X 15/16 IN	FINE FISSURED HIGH NRC - TEGULAR BP17568	WHITE	
P4	PAINT - CEILING	SHERWIN WILLIAMS	N/A	PROMAR 200 ZERO VOC PRIMER - ONE COAT + PROMAR 200 ZERO VOC - 2 COATS - SEMI GLOSS	SNOWBOUND SW 7004	FOLLOW MANUFACTURER'S TECHNICAL DATA SHEETS FOR PRIMING AND PAINTING. LEVEL 4 FINISHES ALL ON GYPSUM BOARD WALLS.
EXP/P	PAINT - EXPOSED CEILING	SHERWIN WILLIAMS	N/A	PRO INDUSTRIAL WATERBORNE ACRYLIC DRYFALL	SNOWBOUND SW 7005	FOLLOW MANUFACTURER'S TECHNICAL DATA SHEETS FOR PRIMING AND PAINTING; ALL AREAS EXPOSED TO BE PAINTED INCLUDING BUT NOT LIMITED TO CEILING/STRUCTURE/CONDUIT. NOT INCLUDING LOBBY AREA.
ADDITIONAL FINISHES						
SS1	SOLID SURFACE- BREAKROOM	WILSONART	1/2 IN	SOLID SURFACE	TUMBLD STONE	
SS2	SOLID SURFACE- BATHROOM	WILSONART	1/2 IN	SOLID SURFACE	CLIFFSIDE TRAVERTINE	
SS3	SOLID SURFACE- WINDOW SILLS	WILSONART	1/2 IN	SOLID SURFACE	MOON GEYSER 9209CM	
P5	PAINT - HM DOOR / DOOR FRAME	SHERWIN WILLIAMS	N/A	PR-CRYL UNIVERSAL WATER BASED PRIMER - ONE COAT + WB ALKYD EUROTHANE ENAMEL - TWO COATS - SEMI GLOSS	URBANE BRONZE SW 7048	FOLLOW MANUFACTURER'S TECHNICAL DATA SHEETS FOR PRIMING AND PAINTING
WD	WOOD DOOR (FACTORY FINISH)	VT INDUSTRIES	SEE DOOR SCHEDULES	WHITE BIRCH	CHOCOLATE CH18	
WS1	WOOD STAIN FOR CUSTOM BIRCH MILLWORK & WOOD DOORS	TO MATCH MINWAX	N/A	MINWAX	MATCH MS DARK WALNUT MW2716 / CHOCOLATE CH18 DOORS	COLOR MATCH CASEWORK TO DOORS COLOR CHOCOLATE CH18. ALL MILLWORK FINISHED: WS1 STAIN, WS2 FAST DRY SANDER SEALER AND WV WOOD VARNISH TOP COAT.
WS2	WOOD SANDER SEALER	MINWAX	N/A	FAST DRY SANDER SEALER	CLEAR	TO TOP WS1 STAIN.
WV	WOOD VARNISH	MINWAX	N/A	FAST DRY VARNISH	CLEAR	TO TOP WS1 STAIN AND WS2 FAST DRY SANDING SEALER.
CG	CORNER GUARDS	KOROGARD	TO CEILING	100/G10E	MIST 33 / DUNE TEXTURE	ALL EXTERIOR CORNERS
TG	TILE GROUT - FLOOR AND WALL TILE	CUSTOM BLDG PRODUCTS	1/8 IN	CEG-LITE	OYSTER GRAY #386	
DP	DRAWER PULLS	HICKORY	4 IN	4" WIRE PULLS	SATIN NICKEL	BREAKROOM
SI	SIGNAGE - INTERIOR	APCO	VARIES	ELEMENT II	ARCHITECTURAL BROWN A44 BACKGROUND WITH WHITE REFLECTIVE TEXT	SEE I-114 FOR DETAILS.
SR/H	SHOWER ROD/HOOK	BRADLEY CORP	VARIES	9538 1" CONCEALED MOUNT SHOWER ROD / 9536 STEEL SPRING HOOK	STAINLESS STEEL	75 H AFF / ABOVE SHOWER PAN INSTALLATION.
SC	SHOWER CURTAIN	BRADLEY CORP	MIN 72 IN H, WIDTH VARIES	9537 ANTIMICROBIAL VINYL SHOWER CURTAIN	STAINLESS STEEL	

		AIR MOBILITY COMMAND 19TH CIVIL ENGINEER SQUADRON LITTLE ROCK, ARKANSAS		MATERIAL LEGEND		NKAK 22-1076 B718 DORM LITTLE ROCK AFB		APPROVED _____ C-CHIEF ENGINEER _____ APPROVED _____ CIVIL ENGINEER _____		REV # _____ DATE _____ DESCRIPTION _____ APP'D _____	
DATE: JULY 2026 DESIGNED BY: ABV DRAWN BY: ABV BUILDING NO.: _____		PROJECT NO.: _____		SHEET REF.: _____		A-603		SHEET NO.: 1 OF XX			