

GENERAL NOTES

1. THERMOSTATS SHALL BE LOCATED IN REPRESENTATIVE SPACES, MOUNTED APPROXIMATELY 48 INCHES ABOVE FINISHED FLOOR, AWAY FROM DIRECT SUNLIGHT, EXTERIOR WALLS, SUPPLY AIR DIFFUSERS, AND HEAT-PRODUCING EQUIPMENT.
2. EACH ZONE SHALL BE INDEPENDENTLY CONTROLLED BY A DEDICATED THERMOSTAT OR APPROVED CONTROL DEVICE AS INDICATED ON THE PLANS.

APP'D	DESCRIPTION	DATE	REV #	APPROVED
				NKAK 22-1076
				B718 DORM
				LITTLE ROCK AFB
				CHIEF ENGINEER
				APPROVED
				DETAILS (1)
				CIVIL ENGINEER



AIR MOBILITY COMMAND
19TH CIVIL ENGINEER SQUADRON
LITTLE ROCK, ARKANSAS

DATE: JULY 2026
DESIGNED BY: SAH
DRAWN BY: B WHR
BUILDING NO.:
PROJECT NO.:
SHEET REF.:
M-101
SHEET NO.: 1 OF XX

LEVEL 3, ZONE AND PRESSURIZATION PLAN



SCALE



1

LEVEL 3 MECHANICAL ZONE AND PRESSURIZATION PLAN

SCALE: 1/8" = 1'-0"

AIR MOBILITY COMMAND
19TH CIVIL ENGINEER SQUADRON
LITTLE ROCK, ARKANSAS

DATE: JULY 2026
DESIGNED BY: SAH
DRAWN BY: BWHR
BUILDING NO.:
PROJECT NO.:
SHEET REF.:
M-101
SHEET NO.: 1 OF XX

[illegible]