

1	ONE (1) 36" GRAB BAR BEHIND THE TOILET, ONE (1) 42" GRAB BAR ADJACENT TO TOILET. GRAB BARS SHALL BE MOUNTED 33" - 36" A.F.F. TO THE TOP OF THE GRIPPING SURFACE. GRAB BARS SHOULD HAVE 1/4" MIN. 2" MAX O.D. AND 1 1/2" CLEARANCE OFF WALL. GRAB BAR BLOCKING AND ANCHORS SHALL SUPPORT A CONCENTRATED LOAD OF 250 POUNDS APPLIED AT ANY POINT IN ANY DIRECTION. REFER TO AND COMPLY WITH ADA 609 AND STATE BUILDING CODE. BARS SHALL BE EQUAL TO BRADLEY 812 (PEENED, NON-SLIP SURFACE). COORDINATE GRAB BAR WITH TOILET TYPE & LOCATION
2	WALL MOUNTED SOAP DISPENSER EQUAL TO TRIPLE-S SSS FOAMCLEAN DISPENSER, GRAY G/1000ML
3	WALL MOUNTED MECHANICAL HANDS FREE ROLL TOWEL DISPENSER EQUAL TO SAN JAMAR CLASSIC SIMPLICITY ESSENCE T7400TBK
4	STAINLESS STEEL DOUBLE ROBE HOOK EQUAL TO BOBRICK B-6727 MOUNTED AT 70" A.F.F. IN TYPICAL DORM BATHROOMS. 48" A.F.F. MAX. IN ADA DORM BATHROOMS 128 & 129
5	SURFACE MOUNTED DOUBLE ROLL TOILET PAPER HOLDER EQUAL TO BOBRICK SURFACE-MOUNTED TWIN JUMBO-ROLL TOILET TISSUE DISPENSER B-2892
6	SURFACE MOUNTED TOILET ROLL HOLDER EQUAL TO BOBRICK FINO COLLECTION TOILET ROLL HOLDER B-9543
7	RECESSED STEEL MEDICINE CABINET WITH GLASS MIRROR (ADA COMPLIANT) EQUAL TO BOBRICK B-398
8	SURFACE MOUNTED 24" SATIN FINISH STAINLESS STEEL TOWEL BAR EQUAL TO BOBRICK B-6737 AT 48" A.F.F.
9	SOLID PHENOLIC FOLDING SHOWER/DRESSING AREA SEAT WITH STAINLESS STEEL FRAME EQUAL TO BOBRICK B-5193
10	STAINLESS STEEL HEAVY DUTY SHOWER CURTAIN ROD EQUAL TO BOBRICK B-6107 WITH VINYL SHOWER CURTAIN AND STAINLESS STEEL SHOWER CURTAIN HOOKS EQUAL TO BOBRICK 204
11	STAINLESS STEEL MOP AND BROOM HOLDER WITH 3 HOLDERS EQUAL TO BRADLEY MODEL 9953
12	STAINLESS STEEL FIXED TILT MIRROR WITH WELDED CORNERS EQUAL TO BRADLEY 740



PROVIDE AND INSTALL 2X4 WOOD BLOCKING AS REQUIRED TO FRAME NICHE

WALL TILE AS SCHEDULED (BEYOND COORDINATE PATTERN)

COORDINATING CERAMIC TILE BULLNOSE @ PERIMETER

NICHE MAX A.F.F. 4'-0"

5/8" CEMENTITIOUS BOARD. APPLY WATERPROOF MEMBRANE. SHIM BOTTOM LEDGE AS REQUIRED TO SLOPE 1/4" PER FOOT.

WALL AS SCHEDULED

Architectural drawing of a bathroom stall. The drawing includes the following callouts and specifications:

- CURTAIN NOT SHOWN FOR CLARITY
- CEILING AS SCHEDULED
- LIGHT FIXTURE RE: ELECTRICAL
- CERAMIC WALL TILE AS SCHEDULED
- FIXTURES RE: PLUMBING
- MILLWORK (STAIN) RE: 8/A5.01
- TERRAZZO SHOW PAN RE: PLUMBING INSTALL PER MANUFACTURER'S RECOMMENDATIONS OVER WATERPROOF MEMBRANE RE: PROJECT MANUAL
- CERAMIC FLOOR TILE AS SCHEDULED
- 10
- 115-8
- 5'-0" MAX
- 3'-0"

CERAMIC WALL TILE AS SCHEDULED

LIGHT FIXTURE RE: ELECTRICAL

MILLWORK (STAIN)

4" SOLID SURFACE SIDESPLASH WITH EASED EDGE. SEAL BUTT JOINTS WITH MANUFACTURER'S COLOR MATCH SEALANT. RE: PROJECT MANUAL

FIXTURES RE: PLUMBING

CERAMIC FLOOR TILE AS SCHEDULED

2'-9"

1'-2"

2'-6"

7'-6"

3'-10"

2'-6"

CEILING AS SCHEDULED

FIXTURES RE: PLUMBING

(4) FIXED WOOD SHELVES (STAIN)

CERAMIC WALL TILE AS SCHEDULED

RECESSED SHOWER NICHE

TERRAZZO SHOWER PAN RE: PLUMBING INSTALL PER MANUFACTURER'S RECOMMENDATION OVER WATERPROOF MEMBRANE RE: PROJECT MANUAL

CERAMIC FLOOR TILE AS SCHEDULED

9

A4.03

1'-0"

7'-6" MAX.

1'-4"

1'-0"

± 3'-11 1/2"

5 1/2"

1'-2"

VERIFY OPENING WITH SHOWER PAN MANF.

CURTAIN NOT SHOWN FOR CLARITY

10

A5.01

7'-6"

7'-6"

1'-2"

2'-6"

3'-10"

± 5'-5"

3'-0"

± 8'-5"

MILLWORK (STAIN)
RE: 5/A5.01

CEILING AS SCHEDULED

10
CURTAIN NOT SHOWN FOR CLARITY

CT-3A

CT-3B

CT-3C

CERAMIC WALL TILE
INSTALL CT-3A,
CT-3B, & CT-3C IN
RANDOM PATTERN
AT ACCENT WALL
ONLY (TYP)

TOILET
RE: PLUMBING

TERRAZZO SHOWER PAN
RE: PLUMBING
INSTALL PER
MANUFACTURER'S
RECOMMENDATION OVER
WATERPROOF MEMBRANE
RE: PROJECT MANUAL

CERAMIC FLOOR TILE

Architectural floor plan of a bathroom showing a shower pan, toilet, and various fixtures. The plan includes dimensions and callouts for materials and fixtures.

Callouts and Dimensions:

- CEILING AS SCHEDULED**
- LIGHT FIXTURE RE: ELECTRICAL**
- CERAMIC WALL TILE AS SCHEDULED**
- FIXTURE RE: PLUMBING**
- 4" SOLID SURFACE SIDE SPLASH WITH EASED EDGE. SEAL BUTT JOINTS WITH MANUFACTURER'S COLOR MATCH SEALANT RE: PROJECT MANUAL**
- MILLWORK (STAIN)**
- CERAMIC FLOOR TILE AS SCHEDULED**
- CURTAIN NOT SHOWN FOR CLARITY**
- RECESSED SHOWER NICHE RE: 9/A4.03**
- 36" GRAB BAR REFER TO TOILET ACCESSORY SCHEDULE FOR MODEL TYPE**
- VERIFY OPENING WITH SHOWER PAN MANF. 10'-0"**
- 2'-10" MAX. ABOVE PAN FLOOR**

Dimensions:

- 1'-6"
- ± 2'-7 1/2"
- 2'-6" MIN.
- 5 1/2"
- 10'-0"
- 27" MAX.
- 8"
- 1'-0"
- 1'-0"
- 3'-6"
- 6"
- 2'-10" MAX.

Notes:

- 7 A5.01
- 6 A5.01
- 10
- 1
- 9

Architectural floor plan of a bathroom. The plan includes a shower pan, toilet, and vanity. Dimensions are provided for various elements: a 3'-0" wide vanity, a 2'-6" deep vanity, a 1'-0" wide toilet, and a 2'-10" wide shower area. A 24" grab bar is indicated. The plan also shows a curtain not shown for clarity, millwork (stain), and a 5' AS 81' dimension. Annotations include 'CEILING AS SCHEDULED', 'CERAMIC WALL TILE AS SCHEDULED', 'TERRAZZO SHOWER PAN RE: PLUMBING INSTALL PER MANUFACTURER'S RECOMMENDATION OVER WATERPROOF MEMBRANE RE: PROJECT MANUAL', 'CERAMIC FLOOR TILE AS SCHEDULED', and 'FIXTURES RE: PLUMBING'. A note 'FOR CLARITY' is also present.

Architectural drawing of a bathroom stall showing plumbing and tile details. The drawing includes the following labels and dimensions:

- MILLWORK (STAIN) RE: 5/A5.01
- CEILING AS SCHEDULED
- 10"
- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17
- 18
- 19
- 20
- 21
- 22
- 23
- 24
- 25
- 26
- 27
- 28
- 29
- 30
- 31
- 32
- 33
- 34
- 35
- 36
- 37
- 38
- 39
- 40
- 41
- 42
- 43
- 44
- 45
- 46
- 47
- 48
- 49
- 50
- 51
- 52
- 53
- 54
- 55
- 56
- 57
- 58
- 59
- 60
- 61
- 62
- 63
- 64
- 65
- 66
- 67
- 68
- 69
- 70
- 71
- 72
- 73
- 74
- 75
- 76
- 77
- 78
- 79
- 80
- 81
- 82
- 83
- 84
- 85
- 86
- 87
- 88
- 89
- 90
- 91
- 92
- 93
- 94
- 95
- 96
- 97
- 98
- 99
- 100
- 101
- 102
- 103
- 104
- 105
- 106
- 107
- 108
- 109
- 110
- 111
- 112
- 113
- 114
- 115
- 116
- 117
- 118
- 119
- 120
- 121
- 122
- 123
- 124
- 125
- 126
- 127
- 128
- 129
- 130
- 131
- 132
- 133
- 134
- 135
- 136
- 137
- 138
- 139
- 140
- 141
- 142
- 143
- 144
- 145
- 146
- 147
- 148
- 149
- 150
- 151
- 152
- 153
- 154
- 155
- 156
- 157
- 158
- 159
- 160
- 161
- 162
- 163
- 164
- 165
- 166
- 167
- 168
- 169
- 170
- 171
- 172
- 173
- 174
- 175
- 176
- 177
- 178
- 179
- 180
- 181
- 182
- 183
- 184
- 185
- 186
- 187
- 188
- 189
- 190
- 191
- 192
- 193
- 194
- 195
- 196
- 197
- 198
- 199
- 200
- 201
- 202
- 203
- 204
- 205
- 206
- 207
- 208
- 209
- 210
- 211
- 212
- 213
- 214
- 215
- 216
- 217
- 218
- 219
- 220
- 221
- 222
- 223
- 224
- 225
- 226
- 227
- 228
- 229
- 230
- 231
- 232
- 233
- 234
- 235
- 236
- 237
- 238
- 239
- 240
- 241
- 242
- 243
- 244
- 245
- 246
- 247
- 248
- 249
- 250
- 251
- 252
- 253
- 254
- 255
- 256
- 257
- 258
- 259
- 260
- 261
- 262
- 263
- 264
- 265
- 266
- 267
- 268
- 269
- 270
- 271
- 272
- 273
- 274
- 275
- 276
- 277
- 278
- 279
- 280
- 281
- 282
- 283
- 284
- 285
- 286
- 287
- 288
- 289
- 290
- 291
- 292
- 293
- 294
- 295
- 296
- 297
- 298
- 299
- 300
- 301
- 302
- 303
- 304
- 305
- 306
- 307
- 308
- 309
- 310
- 311
- 312
- 313
- 314
- 315
- 316
- 317
- 318
- 319
- 320
- 321
- 322
- 323
- 324
- 325
- 326
- 327
- 328
- 329
- 330
- 331
- 332
- 333
- 334
- 335
- 336
- 337
- 338
- 339
- 340
- 341
- 342
- 343
- 344
- 345
- 346
- 347
- 348
- 349
- 350
- 351
- 352
- 353
- 354
- 355
- 356
- 357
- 358
- 359
- 360
- 361
- 362
- 363
- 364
- 365
- 366
- 367
- 368
- 369
- 370
- 371
- 372
- 373
- 374
- 375
- 376
- 377
- 378
- 379
- 380
- 381
- 382
- 383
- 384
- 385
- 386
- 387
- 388
- 389
- 390
- 391
- 392
- 393
- 394
- 395
- 396
- 397
- 398
- 399
- 400
- 401
- 402
- 403
- 404
- 405
- 406
- 407
- 408
- 409
- 410
- 411
- 412
- 413
- 414
- 415
- 416
- 417
- 418
- 419
- 420
- 421
- 422
- 423
- 424
- 425
- 426
- 427
- 428
- 429
- 430
- 431
- 432
- 433
- 434
- 435
- 436
- 437
- 438
- 439
- 440
- 441
- 442
- 443
- 444
- 445
- 446
- 447
- 448
- 449
- 450
- 451
- 452
- 453
- 454
- 455
- 456
- 457

Technical drawing of a wall and floor assembly. The wall is 7'-6" high and features a grid of ceramic wall tiles. The floor is covered with ceramic floor tiles. A 4" solid surface side splash with eased edge is shown at the bottom right, with a sealant applied to the butt joints. A receptacle for electrical is indicated. The drawing includes callouts for various materials and components:

- CERAMIC WALL TILE AS SCHEDULED. INSTALL CT-3A, CT-3B, AND CT-3-C IN RANDOM PATTERN AT ACCENT WALL ONLY (TYP.)
- CEILING AS SCHEDULED
- CT-3A
- CT-3B
- CT-3C
- RECEPTACLE RE: ELECTRICAL
- 4" SOLID SURFACE SIDE SPLASH WITH EASED EDGE. SEAL BUTT JOINTS WITH MANUFACTURER'S COLOR MATCH SEALANT. RE: PROJECT MANUAL
- MILLWORK (STAIN) RE: 7 / A5.01
- CERAMIC FLOOR TILE AS SCHEDULED

0' 6" 1' 2'

SCALE: 1" = 1'-0"

0' 1' 2' 4'

SCALE: 1/2" = 1'-0"



10 KITCHEN 205 NORTH WALL
1/2" = 1'-0"