

GYPSUM BOARD

3/4"

1 x 4 ROUGH CEDAR TRIM

3 1/2"

3/4" BLACK SLAT WALL ON 5/8" FRT PLYWOOD ON METAL STUD FRAMING

PART AS SCHEDULED

Diagram illustrating the cross-section of the fireplace mantel assembly, showing the following components from top to bottom:

- WILSONART 1595 BLACK LAMINATE ON 3/4" PLYWOOD ON MTL. STUD FRAMING.
- 1 x 4 ROUGH CEDAR TRIM
- 1/2" SHIM
- 3/4" BLACK SLAT WALL ON 1/2" FRM. PLYWOOD ON MTL. STUD FRAMING.

GENERAL:

- 1. MILLWORK TO BE INSTALLED AFTER TILE ON FLOOR.
- 2. SUPPLY ACCESS PANELS AS REQUIRED. FIELD VERTY EXACT LOCATIONS.
- 3. WHERE APPLICABLE CABINETS WILL BE LINE BUILT FOR ADJUSTABLE SHELVING.
- 4. ALL MILLWORK IN COFFIN, POCKET, AND ICE AREAS SHALL BE CONSTRUCTED USING 19" BULKHEAD, KOMATEK™ INTEGRAL FOAM SHEETS UNLESS NOTED OTHERWISE.
- 5. PROVIDE THE VERY BEST QUALITY MILLWORK IN BASE CABS. CONT. FROM FRONT TO BACK 48" O.C. MAX.
- 6. BAG RACKS ARE TO BE SUPPLIED BY OWNER. INSTALLED BY CONTRACTOR.
- 7. GROMMETS TO BE 2" DIA. VERTY ALIGNMENT WITH OWNER.

HARDWARE:

- 1. **HINGES:** BLUM, CLIP TOP PLUMATION SOFT CLOSE, STEEL W/ POLISHED FINISH.
- 2. **PULLS:** HAFELLE ALUMINUM HANDLE, D40, RUBBER BRONZE ITEM # 124.02.032
- 3. **CATCHES:** CATCHO MAGNETIC
- 4. **LED LIGHTS:** HAFELLE "XOXY" 1W/5" STRIP
- 5. 1/4" PLEX-GLAS INSERT (PVC) WITH ADJUSTABLE PARTITIONS

COLORS:

- 1. ALL SOLID SURFACE TO BE SSP-1, UNLESS OTHERWISE NOTED.
- 2. ALL LAMINATE TO BE EXTERIOR EXPOSED SURFACE AREAS TO RECEIVE PL-1, UNLESS OTHERWISE NOTED.
- 3. INTERIOR CABINETS EXPOSED SURFACES TO BE PL-3, UNLESS OTHERWISE NOTED.

NOTE: FIELD VERIFY THE ABOVE FINISHES, CONFIRM WITH OWNER.

- ① T-1 TILE AS SCHEDULED.
- ② T-3 TILE AS SCHEDULED.
- ③ T-4 TILE AS SCHEDULED. A
- ④ SOLID SURFACE- W/ BULLNOSE EDGES
- ⑤ POXY WALL ASSEMBLY. CERAMIC TILE AS SCHEDULED. OVER 18" CEMENT BOARD, OVER 18 GA MTL. STUD FRAMING @ 16" O.C.
- ⑥ CABLE CHASE BEYOND. PROVIDE 1/4 BEND OFFSETS IN CORNER CASE.
- ⑦ ACCESS PANEL
- ⑧ 12"x12" ACCESS PANEL
- ⑨ RAW PLYWOOD FOR TILE
- ⑩ GROMMET 2 3/8"
- ⑪ SCHEDULED SAFE
- ⑫ LINE OF CIGARETTE SHELVING
- ⑬ EQUIPMENT. -- RE: SCHEDULE
- ⑭ DROP-IN REFRIGERATED COLD WELLS.
- ⑮ 8" DIAMETER TRASH HOLE WITH 3" DEEP PVC SLEEVE BELOW SOLID SURFACE COUNTERTOP.
- ⑯ TRASH CAN, BY OTHERS.
- ⑰ 30-181" x 6-1/2" x 6-1/8" DOME COVE FOR INSERT TYPICAL.
- ⑱ LED LIGHTING "L.OOK" 12V STRIP LIGHTING TYP.
- ⑲ 1/4" PLEXI-GLASS INSERT 67Dx59X30"L W/ ADJUSTABLE PARTITIONS TYP. 6 / A8.00
- ⑳ 1/4"x8" ROUTED OPEN AIR VENTS
- ㉑ FLOOR SINK RE: PLUMBING
- ㉒ PROVIDE ACCESS PANEL FOR FLOOR SINK IN THE FIELD. V.I.F. AND COORDINATE AS REQUIRED.
- ㉓ 1-1/2" RADIUS @ ALL CORNERS
- ㉔ COMPLY NATIONAL CAM LOCK. ITEM C8053-14A, KEYING TO C415A W/ D8783 BLANK.
- ㉕ MILLWORK DOOR WITH SCHEDULED HARDWARE.
- ㉖ 3/8" x 18" ROUTED OPEN AIR VENTS @ 1-1/4" SPACING.
- ㉗ DOORS AT ONE SIDE FACING DELT. WITH SCHEDULED HARDWARE.
- ㉘ REMOVABLE MILLWORK INSERT. FUTURE SAFE LOCATION.
- ㉙ DRAWER PULLS. HAFELE. DARK OIL RUBBERED BRONZE. ITEM 116.07.319 @ FILE CABINET ONLY.
- ㉚ DOVETAIL JOINTS AT DRAWER CORNERS.
- ㉛ SOFT CLOSE CABINET DRAWER GUIDES. KNAPE-VOGT MODEL G38850.
- ㉜ SCHEDULED LAMINATE ON EXTERIOR OF CABINET AND PL-3 ON INTERIOR OF CABINET.
- ㉝ HANGING FOLDING RAIL. FULL LENGTH OF DRAWER.
- ㉞ EMERGENCY FUEL SHUT OFF. ONLY AT CASHIER 5 RE: FUEL SYSTEM DRAWINGS.
- ㉟ 12"x4" STAINLESS STEEL SURFACE MOUNTED LOUVERED VENT.
- ① ALUMINUM ROUNDED BULL NOSE TRIM AS SCHEDULED. TYP @ ALL TILED MILLWORK CORNERS.

NOT ALL NOTES ARE USED ON THIS SHEET

A DEVELOPMENT OF

Buc-ee's Benton, LLC
Saline County, Arkansas

TEL: (979) 230-2920

BUC-EE'S TRAVEL CENTER
BENTON, ARKANSAS
74K - L - 2025 -Q1
INTERSTATE 30 & STATE HIGHWAY 229
BENTON, ARKANSAS 72019

LAWRENCE S.
LEVINSON, A.I.A.

7800 Washington Ave., Suite 600
main: 713.600.3600

ISSUE/REVISION LOG:

No.	DESCRIPTION	DATE
1	OWNER CHANGES	09/09/2024
3	OWNER CHANGES	04/23/2025



04/23/2025

ISSUED FOR REVIEW: 04/26/2024

ISSUED FOR BID: 05/14/2024

ISSUED FOR PERMIT: 05/14/2024

Copyright 2024 Lawrence S. Levinson, AIA. Warning: This document is protected by U.S. Copyright Law Under Section 102 of the U.S. Copyright and the Architectural Works Copyright Protection Act of 1990. Unauthorized reproduction and distribution of this document or any portion of it, other than for use of this particular project, is prohibited and may result in severe civil and criminal penalties, and will be prosecuted to maximum extent possible under the law.

A8.01

TYPICAL MILLWORK DETAILS

LAARC PROJECT NUMBER: 2024-107.000

BENTON, ARKANSAS

WALL TILE ON 5/8" CEMENT
BD. ON MTL STUD
FRAMING @ 16" O.C.

GROUT JOINT

WILSONART 1595 BLACK
LAMINATE ON 3/4" PLYWOOD
ON MTL. STUD FRAMING.

[illegible][illegible]

24"

BACK SPLASH RETURN AT END WALL CONDITIONS

COUNTER TOP W/ BACK SPLASH AND BULLNOSE EDGE

PLYWOOD WITH PLASTIC LAMINATE LINER (1/2")

COUNTER TOP BRACKET (BLACK), 32" O.C. ANCHOR TO STUDS

1 1/2"

1 1/2"

3 1/4" X OFFICE MILLWORK

48" X STORAGE & WAREHOUSE MILLWORK

SCHEDULED PARTITION

SCHEDULED BASE

11	SLAT WALL CAP DETAIL	3" = 1'-0"
----	----------------------	------------

7	COUNTER TOP EDGE (BACK)	3" = 1'-0"
---	-------------------------	------------

3	TYP. MILLWORK SECTION	3/4" = 1'-0"
---	-----------------------	--------------

Diagram illustrating the construction detail for a wall assembly, showing the transition from a masonry wall to a wood stud framing.

Labels and Dimensions:

- WALL TILE ON 5/8" CEMENT BD. ON MTL. STUD FRAMING.
- GROUT JOINT
- 1 x 4 ROUGH CEDAR TRIM
- SHIM FLUSH WITH FACE OF TILE FINISH.
- 3/4" BLACK SLAT WALL ON 5/8" FR. PLYWOOD ON MTL. STUD FRAMING
- Dimensions: 1/2" (gap between tile and trim), 3 1/2" (height of trim)

Technical drawing of a cabinet corner showing dimensions and material specifications:

- SOLID SURFACE WITH BULLNOSE EDGES**
- WILSONART COLOR 9036 AE PEBBLE**
- 6"** (Overall height)
- 1/2"** (Top edge thickness)
- 1/2"** (Side edge thickness)
- 1/4"** (Inner corner radius)
- 1 1/2"** (Inner corner depth)
- 3 1/4"** (Cable chase width)
- 2 1/4"** (Cable chase depth)
- 4"** (Cable chase offset)
- 3 1/4"** (Cable chase depth)
- 3/4"** (Cable chase offset)
- 4"** (Cable chase depth)
- CABLE CHASE, FULL LENGTH OF MILLWORK CASE. 4"x3 1/4" W/ OPENING THROUGH SIDES OF CASE.**
- CERAMIC TILE AS SCHEDULED. RE: MILLWORK ELEVATIONS FOR PATTERN.**
- RAW PLYWOOD FACE FOR TILE.**
- INTERIOR CABINETS EXPOSED SURFACES TO BE WHITE LAMINATE LINER.**

[illegible]

10	SLAT WALL HEAD DETAIL	3" = 1'-0"
----	-----------------------	------------

6	COUNTER TOP EDGE (FRONT)	3" = 1'-0"
---	--------------------------	------------

2	TYP. CASHIER COUNTER ELEVATION	3/4" = 1'-0"
---	--------------------------------	--------------

Technical drawing of a window assembly showing dimensions and components. The drawing includes a side elevation and a top elevation. Key dimensions and components are labeled:

- Side Elevation Dimensions:**
 - Overall height: 59"
 - Top section height: 34"
 - Bottom section height: 12"
 - Bottom section height: 6 1/2"
 - Top section width: 11 1/2"
 - Bottom section width: 47 3/4"
 - Overall width: 59 1/4"
- Top Elevation Dimensions:**
 - Overall width: 117 7/8"
 - Top section width: 109"
 - Top section width: 112"
 - Top section width: 8 7/8"
 - Top section width: 5 7/8"
 - Top section width: 1 1/2"
 - Top section width: 1 1/2"
 - Top section width: 1 1/2"
- Components and Labels:**
 - SS-1:** Label for the top section of the window.
 - 4:** Label for the top section of the window.
 - 25:** Label for the top section of the window.
 - EQ:** Label for the middle section of the window.
 - T-3:** Label for the bottom section of the window.
 - B-1:** Label for the bottom section of the window.

Technical drawing of a door frame assembly. The drawing shows a cross-section of the door frame and the door itself. The door is labeled "3/4\" BLACK SLAT WALL ON SPS PART PLYWOOD ON MTL STUD FRAMING". The frame is labeled "1 x 4 ROUGH CEDAR TRIM". The wall is labeled "GYPSUM BOARD". The floor is labeled "FINISHED FLOOR". Dimensions are indicated: "5\" FROM F.F." (from finished floor to the bottom of the frame), "3 1/2\"" (height of the frame), and "5 1/2\"" (height of the door). A red dashed line outlines the door and frame assembly. A red circle with the number "3" is located near the top left corner of the door.

[illegible]

9	SLAT WALL BASE DETAIL	3" = 1'-0"
---	-----------------------	------------

5	TYP. MILLWORK SECTION 3	3/4" = 1'-0"
---	-------------------------	--------------

1	TYP. CASHIER COUNTER ELEVATION	3/4" = 1'-0"
---	--------------------------------	--------------