T.R.U./SWEET ST. GENERAL NOTES

SOLID SURFACE TOP AS SCHEDULED, WITH BULL

PLASTIC LAMINATE AS SCHEDULED.

KOMATEX BD, WITH FRT PLYWOOD

ON ONE (19 MM) LAYER OF

FRAMING @ 16" O.C. TYP.

BASE AS SCHEDULED.

FLOOR TILE AS SCHEDULED.

4 T.R.U. WALL DETAIL

26"

PL-3

<u>(6E)</u>

68" CLEAR

98 1/2"

3 3/4" 1 1/2"

FINISHED FLOOR ____

1 1/2" = 1'-0"

NOSE EDGES ON ALL

SIDES.

SOLID SURFACE TOP AS

SCHEDULED, WITH BULL

PLASTIC LAMINATE AS SCHEDULED,

KOMATEX BD, WITH FRT PLYWOOD

ON ONE (19 MM) LAYER OF

FRAMING @ 16" O.C. TYP.

BASE AS SCHEDULED.

FINISHED FLOOR

1 1/2" = 1'-0"

FLOOR TILE AS SCHEDULED.

5 T.R.U. WALL DETAIL

98 1/2" COUNTER LENGTH

PL-3 (19)

S.ST. - MILLWORK SECTION

NOSE EDGES ON ALL

SIDES.

THE CONTRACTOR & SUB-CONTRACTORS SHALL VERYFY ALL EXISTING CONDITIONS PRIOR TO PERFORMING ANY WORK & SHALL NOTIFY THE ARCHITECT IMMEDIATELY OF ANY CONDITIONS THAT MAY EXIST, THAT ARE NOTE COVERED UNDER THESE PLANS. THE CONTRACTOR AND ALL SUB-CONTRACTORS SHALL NOT DAMAGE ANY INSTRUMENTS OR EQUIPMENT DURING THE COURSE OF THE PROJECT. THE CONTRACTOR AND ALL SUB-CONTRACTORS SHALL RETURN ANY INSTRUMENTS OR EQUIPMENT THAT ARRIVES DAMAGED. METAL STUD FRAMING SHALL BE 18 GA. @ 16" O.C. UNLESS OTHERWISE NOTED. RE: STRUCRURAL FOR DETAILS. WALL, MILLWORK, & EQUIPMENT ELEVATIONS ARE MEASURED FROM FINISHED FLOOR, UNLESS OTHERWISE NOTED. DIMENSIONS ARE TO FINISH FACE OF MATERIAL, UNLESSS OTHERWISE NOTED. PROVIDE DOUBLE STUDS, BLOCKING, BRACING & STEEL BACK-UP PLATES REQUIRED TO SUPPORT EQUIPMENT, MISCELLANEOUS ITEMS, E.G. CASEWORK, CABINETS, FIXTURES, SIGNS WALL MOUNTED EQUIPMENT, ETC. TYPICAL. ALL SYMBOLS, ABBRIVIATIONS, & NOTES MARKED "TYPICAL," OR "TYP," SHALL APPLY IN ALL SIMILAR CIRCUMSTANCES. REFERENCE MECHANCIAL, ELECTRICAL, PLUMING, TECHNOLOGY, & REFRIGERATION

T.R.U./SWEET ST. COLOR LEGEND

DRAWINGS FOR MECHANICAL, POWER, LIGHTING, DATA, PLUMING, & REFRIGERATION

REFERENCE FOOD SERVICE DRAWINGS FOR SCHEDULED EQUIPMENT.

DO NOT SCALE DRAWINGS.

1 1/2" = 1'-0"

1 1/2" = 1'-0"

1 1/2" = 1'-0"

3/4" = 1'-0"

PLUMBING FIXTURES & LOCATIONS ELECTRICAL FIXTURES & LOCATIONS DATA FIXTURES & LOCATIONS LIGHTING FIXTUES & LOCATIONS REFRIGERATION FIXTURES & LOCATIONS SPECIAL MILLWORK ITEMS EQUIPMENT BUMPERS

T.R.U./SWEET ST. MILLWORK NOTES

<u>SENERAL:</u>
1. MILLWORK WALLS TO BE INSTALLED PRIOR TO TILE ON FLOOR. MILLWORK CABINETS TO BE INSTAILED AFTER TILE ON FLOOR & WALLS, SUPPLY ACCESS PANELS AS REQUIRED. FIELD VERIFY EXACT LOCATIONS. WHERE APPLICABLE CABINETS WILL BE LINE BORED FOR ADJUSTABLE SHELVING. ALL MILLWORK IN TEXAS ROUND UP & FUDGE AREAS SHALL BE CONSTRUCTED USING 19MM (3/4") "KOMATEX" INTEGRAL FOAM SHEETS UNLESS NOTED OTHERWISE. PROVIDE 3/4" THK. VERTICAL SUPPORTS IN BASE CABINETS CONT. FROM FRONT TO BACK @ HINGES: BLUM, CLIP TOP BLUMOTION SOFT CLOSE, STEEL W/ POLISHED FINISH.

PULLS: HAFELE, ALUMINUM HANDLE, DARK OIL-RUBBED BRONZE ITEM # 124.02.332 **CATCHES:** EPCO MAGNETIC LED LIGHTS: HAFELE, "LOOX" 12V STRIP. 1/4" PLEXI-GLASS INSERT 6"W x 5"H x 30"L WITH ADJUSTABLE PARTITIONS.

ALL SOLID SURFACE TO BE SSF-1, UNLESS OTHERWISE NOTED. ALL LAMINATE AT EXTERIOR EXPOSED SURFACE AREAS TO BE PL-1, UNLESS OTHERWISE NOTED. INTERIOR CABINETS EXPOSED SURFACES TO BE PL-3, UNLESS OTHERWISE NOTED. NOTE: FIELD VERIFY THE ABOVE FINISHES, CONFIRM WITH OWNER.

SWEET ST. MILLWORK - KEYED NOTES

1 SOLID SURFACE TOP AS SCHEDULED WITH BULLNOSE EDGE PROFILE , & 1 1/2" RADIUS AT ALL

 $\langle 2 \rangle$ JOIN SOLID SURFACE COUNTERS WITH CONTINUOUS BULLNOSE EDGE PROFILE & 1 1/2" RADIUS AT ALL CORNERS, ON 3/4" KOMATEX SUBSTRATE. $\sqrt{3}$ 2 3/8" GROMMET WITH COVER.

WALL CAP. SOLID SURFACE AS SCHEUDLED. SQUARE EDGE PROFILE ON EQUIPMENT SIDE & BULLNOSE PROFILE SIDES ON ALL OTHER SIDES, & 1 1/2" RADIUS AT ALL CORNERS. UNLESS NOTED OTHERWISE.

igg(6igg) PONY WALL ASSEMBLY. RE: SWEET ST. DETAIL SHEET FOR WALL HEIGHT, THICKNESS, & FINISHES. $\overline{7}$ MILLWORK CASE. RE: SWEET ST. MILLWORK SHEETS FOR DIMENSIONS & FINSHES.

 $\langle 4 \rangle$ 8" DIAMETER TRASH HOLE WITH 3" DEEP PVC SLEEVE BELOW SOLID SURFACE COUNTER.

8 MILLWORK SUPPORT LEG. RE: 14 / A8.76 & - / ---9 HAND LAVATORY STATION.

10 POT FILL SINK.

(11) CUT OUT FOR SINK FIXTURES.

(12) WOOD PLANK FINISH AS SCHEDULED.

(13) BASE AS SCHEDULED.

(14) FLOOR TILE AS SCHEDULED.

(15) WALL TILE AS SCHEDULD, ON 5/8" CEMENT BOARD, ON 18 GA METAL STUD FRAMING @ 16" O.C.

(16) WALL TILE AS SCHEDULED, ON KOMATEX BOARD.

(17) BACKSPLASH. SOLID SURFACE AS SCHEDULED.

(18) PLASTIC LAMINATE AS SCHEDULED ON ALL EXTERIOR SURFACES. (19) PLASTIC LAMINATE AS SCHEDULED ON ALL INTERIOR & UNDER-COUNTER SURFACES.

(20) ADJUSTABLE SHELF WITH LINE BORED HOLES @ 1" O.C.

(21) MILLWORK DOOR WITH SCHEDULED HARDWARE.

(22) FIXED DISPLAY SHELF.

(23) 27"h x 43"w x 1/4"t, TEMPERED CLEAR GLASS.

(24) HAFELE "LOOX" 12V LED LIGHTING TYP. (25) 2 1/2" x 1" FULL LENGTH, STEEL TUBE REINFORCING.

(26) OPENING FOR ELECTRICAL WIRING.

(27) UTILITY CHASE IN MILLWORK CASE FOR ELECTRICAL & PLUMBING. (28) ACCESS PANEL IN BACK OF MILLWORK CASE FOR ELECTRICAL & PLUMBING CONNECTIONS & VALVE BOXES.

(29) MAKE EDGE OF SCHEDULED SOLID SURFACE TOP FLUSH WITH FINISH.

30 3" BLACK PLASTIC TRIM BAND FASTEN WITH FLUSH COUNTERSUNK SCREWS. PAINT SCREW HEADS BLACK.

(31) EQUIPMENT POWER LOCATION. COORDINATE FINAL LOCAITON WITH FOOD SERIVICE EQUIPMENT REQUIREMENTS.

(32) DATA LOCATION. (33) WATER VALVE BOX.

34 ATTACH EQUIPMENT ELECTRICAL CABLES & PLUMNBING TUBING TO UNDERSIDE OF COUNTER &

 $\langle 35
angle$ ALUMINUM ROUNDED BULL NOSE TRIM WITH 1/8" GROUT JOINT EACH SIDE

36 STONE SLAB, BY OWNER.

(37) 25" HIGH SNEEZE GUARD. MFR. ADM, MODEL RING EP-5, BRUSHED STAINLESS STEEL, FLANGE WITH COVER, & 1/4" TEMPERED GLASS.

3 BAY 17" HIGH SNEEZE GUARD WITH LED TUBE. MFR. ADM, MODEL EP-22, BRUSHED STAINLESS STEEL, FLANGE WITH COVER, WITH LED LIGHTING BAR, & 1/4 TEMPERED GLASS. PROVIDE 3" x 4 1/2" x 16 1/2" UNDER COUNTER MOUNTED CABLE TRAY ADJACENT TO GROMET HOLE. VIVO CABLE TRAY, MODEL #DESK-AC06-1C, BLACK.

40 2" HOLE WITH STAINLESS STEEL GROMMET & POT FILL NOZZLE. 41 1/2" HOLE FOR REMOTE VALVE FOR POT FILL NOZZLE

42 PROVIDE 12"x12" SURFACE MOUNTED ACCESS PANEL TO MILLWORK CHASE. MILLWORK DRAWER WITH STAINLESS STEEL DRAWERS GLIDES, KNAPE-VOGT MODEL 6400 SS & (43) DRAWER PULLS, HAFELE, DARK OIL-RUBBED BRONZE, ITEM 116.07.319 AT DRAWERS ONLY.

STAINLESS STEEL DRAWER LINER. LINER SHALL BE THE FULL LENGTH & HEIGHT OF THE INSIDE OF THE DRAWER. 45 PROVIDE 14"x14" ACCESS OPENING FOR FLOOR SINK & WASTE DRAIN. (46) MAKE EDGE OF SCHEDULED SOLID SURFACE TOP FLUSH WITH WOOD PLANK FINISH.

NOT ALL NOTES ARE USED ON THIS SHEET

Buc-ee's Benton, LLC Saline County, Arkansas

TEL: (979) 230-2920

0

LAWRENCE S. LEVINSON, A.I.A.

	Houston, TX 77007 www.laarc.com
E/REVISION LOG:	_
DESCRIPTION	DATE
OWNER CHANGES	09/09/2024
OWNER CHANGES	04/23/2025
	OWNER CHANGES



04/23/2025

ISSUED FOR REVIEW:	04/26/2024
ISSUED FOR BID:	05/14/2024
ISSUED FOR PERMIT:	05/14/2024
Copyright 2024 Lawrence S. Levinson, AIA., Warning: This Copyright Law Under Section 102 of the U.S. Copyright an Protection Act of 1990. Unauthorized reproduction and dis portion of it, other than for use of this particular project, is	nd the Architectural Works Copyright tribution of this document or any

civil and criminal penalties, and will prosecuted to maximum extent possible under the law.

SWEET STREET - MILLWORK

DETAILS LAARC PROJECT NUMBER: 2025-000.000 $\langle 47 \rangle$ ADD 1/4" HIGH BY 1 1/2" WIDE SOLID SURFACE LEDGE TO FUDGE POT COUNTER. BENTON, ARKANSAS