

SHEET NOTES

- SEE SHEET dA-001 FOR GENERAL NOTES, SYMBOLS AND MATERIALS.
- SEE SHEET dA-003 FOR MANEUVERING CLEARANCES.
- SEE SHEET dA-004 FOR PARTITION TYPES.
- SEE SHEET dA-601 FOR DOOR SCHEDULE AND TYPES.
- DIMENSIONS OF EXTERIOR WALLS ARE TO INSIDE FACE OF CMU OR EXTERIOR FINISH FACE U.N.O.
- DIMENSIONS OF INTERIOR WALLS AND PARTITIONS ARE TO FACE OF STUD, FACE OF CMU OR FACE OF IMP U.N.O.
- DOOR OPENINGS SHALL BE LOCATED @ 8" FROM FACE OF ADJACENT PARTITION IN CMU PARTITIONS OR 5" FROM FACE OF PARTITION IN STUD AND PANEL PARTITIONS, U.N.O.
- CONTRACTOR SHALL LOCATE BLOCKING AND BACKING AS REQUIRED FOR WALL MOUNTED EQUIPMENT.
- VERIFY O.H. DOOR MANUFACTURER'S MECHANISM CLEARANCE PRIOR TO INSTALLING DOOR OPENING ADJACENT TO EXISTING COLUMNS OR PARTITIONS. DOOR OPENING MAY NEED TO BE SHIFTED FOR MECHANISM CLEARANCE.

POND3500 Parkway Lane
Suite 500
Peachtree Corners
Georgia 30092

Copyright © 2025 by Pond & Company. All rights reserved. No copying or duplication of these documents is allowed without the expressed written agreement of Pond & Company.

EOR/AOR SEAL

COA SEAL

CLIENT INFORMATION

Vantive

PROJECT NAME

**VANTIVE TUBING
CLEAN ROOM**1900 AR-201
MOUNTAIN HOME,
ARKANSAS 72653

KEYNOTES

KEY #	KEYNOTE DESCRIPTION
A22	MECHANICAL EQUIPMENT; SEE MECHANICAL DWGS
A31	PROPOSED 4" FLOOR MARKINGS
A36	EQUIPMENT PLATFORM SUPPORT COLUMNS. SEE STRUCTURAL DRAWINGS.
A46	FLOOR MOUNTED BOLLARDS, SEE STRUCTURAL DRAWINGS.
A48	INFILL WALL TO MATCH EXISTING CMU WALL; SEE STRUCTURAL DRAWINGS FOR DETAILS.
A57	PRE-ENGINEERED CANOPY; BASIS OF DESIGN, AVADEK.
A63	CONCRETE STAIR; SEE STRUCTURAL AND CIVIL DRAWINGS.
A69	ADA PUSH BUTTONS FOR AUTOMATIC DOOR OPERATION.
A74	STANDARD WALKWAY GUARD RAIL BY IDEALSHIELD OR SIMILAR TO MATCH EXISTING GUARD RAILS IN HEIGHT. V.I.F.

NOTE: FOR CLEANROOM, TUBING CHANGE ROOMS, AND TUBING MATERIAL LOCK, PROVIDE THE FOLLOWING FLOOR FINISH:

PRIMER: ULTRA-TREAD MVT SERIES N241 POLYURETHANE MODIFIED CONCRETE APPLIED AT 90-100 SQ. FT. PER KIT. BROADCAST TO REJECTION WITH CLEAN, DRY, BAGGED (30/50) FLINT SHOT, SILICA SAND, OR APPROVED EQUAL AGGREGATE, COLORED QUARTZ, OR DECORATIVE FLAKE. COLOR: GRAY OR NEUTRAL. PROVIDE SAMPLES FOR OWNER SELECTION.

INTERMEDIATE COAT: DECO-TREAD SERIES N222 COLOR QUARTZ-FILLED MODIFIED POLYAMINE EPOXY APPLIED AT 10-12 MILS DRY. COLOR: SUPPLIED AS CLEARCOAT. FINISH: GLOSS.

TOPCOAT: EVERTHANE SERIES 248 ALIPHATIC MOISTURE-CURED URETHANE APPLIED AT 2-3 MILS DRY.

SHEET LEGEND

	EXISTING WALLS/PARTITIONS TO REMAIN
	PROPOSED STUD WALLS/PARTITIONS
	IMP WALL
	PROPOSED CMU WALLS/PARTITIONS
	PROPOSED DOORS
	PROPOSED EQUIPMENT PLATFORM FLOOR FINISH TO MATCH EXISTING
	NOT IN SCOPE

DRAWING ISSUE

DATE	DESCRIPTION
24APRIL26	ISSUED FOR BID
27FEB26	ISSUED FOR BID
14NOV25	ISSUED FOR REVIEW

SHEET TITLE

DESIGNED BY:	TB
DRAWN BY:	MP
CHECKED BY:	JS
SUBMITTED BY:	JM
DATE:	04/24/2026
PROJECT #:	1241011

DESIGNED BY:	TB
DRAWN BY:	MP
CHECKED BY:	JS
SUBMITTED BY:	JM
DATE:	04/24/2026
PROJECT #:	1241011

SHEET TITLE
AREA 565 - LEVEL
1 - FLOOR PLAN

SHEET NUMBER

dA-131ORIGINAL SHEET SIZE:
36" X 42"

ISSUED FOR BID

A1 AREA 565 - LEVEL 1 - FLOOR PLAN

SCALE: 3/16" = 1'-0"