



1 CEILING PLAN
SCALE = 1/4" = 1'-0"

- GENERAL CEILING NOTES**
- REFER TO THIS PLAN FOR LOCATION AND DESCRIPTION OF CEILING TYPES.
 - REFER TO FINISH SCHEDULE FOR ACOUSTICAL CEILING INFORMATION.
 - THE STARTING POINT FOR THE GRID IS EITHER NOTED OR DIMENSIONED. IF THE STARTING POINT IS NOT INDICATED, THEN THE GRID IS CENTERED WITHIN THE ROOM.
 - REFER TO ENGINEERED LIGHTING PLAN FOR TYPES OF LIGHTING FIXTURES.
 - REFER TO MECHANICAL PLAN FOR LOCATION OF MECHANICAL SUPPLY AND RETURN AIR GRILLS.
 - INSTALL NEW SPRINKLER HEADS, OR TURN DOWN HEADS, AT AREAS OF NEW CONSTRUCTION AS REQUIRED PER CODE AND OCCUPANCY TYPE.

- GENERAL NOTES**
- ALL WORK SHALL COMPLY WITH THE REQUIREMENTS OF THE MUNICIPALITY AND ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.
 - ALL WORK AND ALL FINISHES, INCLUDING TYPE, COLOR AND LOCATION, SHALL BE COORDINATED WITH THE OWNER.
 - ALL DIMENSIONS ARE TO CENTERLINE OF COLUMNS, FACE OF BUILDING LINE OR STUD, TYPICAL UNLESS NOTED OTHERWISE (U.N.O.). WHEN NOTED AS EXISTING THE DIMENSIONS SHOWN ARE TO FACE OF EXISTING FINISH PRIOR TO START OF CONSTRUCTION.
 - VERIFY ALL DIMENSIONS, DOOR AND WINDOW SIZES AND LOCATIONS PRIOR TO LAYOUT WITH THE OWNER. COORDINATE ALL OWNER PROVIDED EQUIP.
 - ALL DOOR AND WINDOW DIMENSIONS ARE NOMINAL AND MUST BE COORDINATED WITH MANUFACTURERS. ROUGH OPENING DIMENSIONS ARE TO BE COORDINATED WITH DOOR AND WINDOW SHOP DRAWINGS.
 - VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS PRIOR TO START OF WORK. CONTRACTOR TO NOTIFY ARCHITECT TO ANY DISCREPANCY WITH THE PLANS AND SPECIFICATIONS PRIOR TO BEGINNING WORK.
 - PROVIDE FIRE EXTINGUISHERS PER NFPA-10 AND COORDINATE WITH LOCAL BUILDING AND/OR FIRE OFFICIALS.
 - PROVIDE KNOX BOX ON EXTERIOR OF BUILDING. COORDINATE EXACT LOCATION WITH LOCAL BUILDING AND/OR FIRE OFFICIALS.
 - PROVIDE WOOD BLOCKING IN STUD WALLS FOR ANCHORAGE OF GRAB BARS, PAPER HOLDERS, VANITIES, WALL MOUNTED DOOR STOPS, SINKS, SHELVING, TELEVISIONS, AND ANY OWNER PROVIDED EQUIPMENT OR FURNISHINGS. COORDINATE WITH OWNER PRIOR TO COVER-UP.
 - PROVIDE BATT INSULATION AT ALL EXTERIOR WALLS AND SOUND ATTENUATION BLANKETS AT ALL NEW WALLS AT TOILET AREAS UNLESS NOTED OTHERWISE.
 - PROVIDE 1 1/2" RIGID INSULATION FULL HEIGHT AT PERIMETER OF BUILDING STEM WALLS & BASEMENT WALLS, AND FOR 2'-0" HORIZONTAL UNDER SLABS. INSULATION SHALL MEET ALL STATE AND LOCAL ENERGY CODES.
 - TOILET ROOM TO BE PROVIDED WITH FORCED AIR VENTILATION TO THE EXTERIOR.
 - PROVIDE ROOM SIGNAGE AT ALL DOORS AS REQUIRED BY THE INTERNATIONAL BUILDING CODE, ANSI A117.1, AND THE AMERICANS WITH DISABILITY ACT. COORDINATE WITH OWNER FOR NAMES, NUMBERS, STYLE AND TYPE OF SIGN. ALL SIGNAGE TO HAVE RAISED BRAILLE CHARACTERS AS REQUIRED.



KEY ARCHITECTURE INC.
P.O. BOX 748 FAYETTEVILLE, ARKANSAS 72702
PH: 479.444.6066 FAX: 479.444.1445

PRELIMINARY NOT FOR CONSTRUCTION

Revision Schedule	Description
Rev. #	Date

NWA PEDIATRICS ADDITION
3730 S PINNACLE HILLS PKWY #3
ROGERS, AR 72758

MANA
3383 N MANA CT, SUITE 201
FAYETTEVILLE, AR 72703

DATE 02/23/26	DRAWN BY ELP
PROJECT # 2438	CHECKED BY JTK
SHEET	
A1.2	
CEILING PLAN	

These Drawings and Specifications are the exclusive property of Key Architecture, Inc. and are protected by Copyright. Use or reproduction is prohibited without written consent.