

Division 9 - Finishes	II	Privacy Function:	C	Installation: Furnish all labor, materials, tools and equipment to install acoustic drywall at walls and/or ceilings. Construct walls and/or ceilings using the acoustic drywall where shown on contract drawings. Install per manufacturer's recommendations and use QuietPuffy 380, manufactured by Serious Energy, and QuietSeal Pro, manufactured by Serious Energy, as recommended by manufacturer to ensure complete acoustic assembly.
	a	Manufacturer: Schlage		
	b	Product ID: ALX Series; BRK		
	c	Finish: US4/ 606, Satin Brass		
	d	Comments: REF Door Hardware Schedule for locations where Satin Chrome Hardware to be used	9.5	Title: See Materials Schedule
	III	Entry Function:	A	Installation: Lay tile in a grid pattern, unless otherwise described on drawings. Align joints where adjoining tiles on floor, base, walls and trim are the same size.
	a	Manufacturer: Schlage		
	b	Product ID: ALX Series; BRK		
	c	Finish: US4/ 606, Satin Brass	B	Excess material quantity: Provide 10 tiles/meshed-backed units or 10% of total installed quantity (whichever is less) new material for future maintenance and/or repair.
	d	Comments: REF Door Hardware Schedule for locations where Satin Chrome Hardware to be used	9.6	Grout: A Manufacturer: Laticrete or SIM B Product: Permacolor Grout C Color: See Materials Schedule
	IV	Butt Hinges:		Transition Strips at flooring/wall transitions: A Manufacturer: Schluter Systems (www.schluter.com, 1.800.472.4588) B Product:
	a	Manufacturer: Hager	I	Scheine: Located at all LVT/tile transitions a Color: Satin Brass Anodized
	b	Product ID: BB1279 4.5 x 4.5	II	Jolly: Located at exposed tile edges a Color: Satin Brass Anodized
	c	Finish: US4/ 606, Satin Brass	C	Size: Coordinate based on location
	d	Comments: REF Door Hardware Schedule for locations where Satin Chrome Hardware to be used	D	Mechanically fasten through the anchoring leg with screws and washers
	V	Frameless Glass Pivot Door	9.8	Paint: A Manufacturer: See Materials Schedule B Color: See Materials Schedule C Sheen:
	a	Manufacturer: Dorma	I	Structure: Dry fall
	i	Top Pivot: PT21M	II	Partitions: Eggshell
	ii	Top Patch: PT20M	III	Wood & Steel: Semi-gloss
	iii	Bottom Patch: PT10M	IV	Gypsum Wall Board Ceilings: Flat
iv	Recessed Floor Closer: BT580	D	Application: Two (2) coats over primer. I Samples: G.C. to provide a full-height sample minimum 4'-0" in width of each color for paint review and approval prior to ordering materials. II Special applications: Provide epoxy based paint on all walls within restrooms, unless noted otherwise.	
b	Finish: Satin Brass	E	Excess material quantity: Provide one (1) unopened gallon of each approved color for future maintenance and/or repair.	
VI	In-Slab Auto Door Bottom:	9.9	Wallcovering: See Materials Schedule	
a	Manufacturer: National Guard Products	A	Installation:	
b	Product ID: 335N 36	I	Provide Level 4 finish drywall w/ taped, bedded, and sanded smooth joints	
VII	Perimeter/Smoke Seals:	II	Do not proceed with installation if moisture content of wall exceeds 4% or if mold/mildew are present	
a	Manufacturer: National Guard Products	III	Do not install wallcovering over ballpoint pen writing, wax crayon, or other foreign matter on the wall as it may bleed through. Lead pencils are recommended for required markings	
b	Product ID: 5050B x 17'	IV	Examine full roll to ensure pattern and color are correct. Examine full roll for color uniformity prior to installation.	
VIII	Silencers:	V	Install per manufacturer recommendations	
a	Manufacturer: Rockwood	9.10	Resilient Plank Flooring: See Materials Schedule	
b	Product ID: 608	A	Provide 10% excess for future replacement.	
c	Finish: Gray	B	General Contractor shall confirm suitability of substrate prior to installation. Confirmation shall include, where applicable, testing of concrete slab for acceptable levels of moisture.	
IX	Wall Stop:	C	Excess material quantity: Provide two (2) unopened boxes or 10% of total installed quantity (whichever is less) new material for future maintenance and/or repair.	
a	Manufacturer: Hager	9.11	Resilient Wall Base (Coil-Type) and Floor Transition Strips:	
b	Product ID: 236W	A	Manufacturer: See Materials Schedule	
c	Finish: US4	B	Material: Rubber	
X	Concealed Overhead Closer	C	Color: See Materials Schedule. Transition strips to match wall base unless noted otherwise.	
a	Manufacturer: LCN	D	Size: I 4" Coil Stock. 4' length not acceptable unless otherwise specified.	
b	Product ID: 3130 Series Concealed Door Closer	E	Profile: Cove base.	
XI	Back-to-Back Pulls:	9.12	FRP & Trim: A Manufacturer: Glasliner FRP B Thickness: 0.090" C Color: Bright White D Class: 'C' General Purpose E Location: Provide at walls adj. to mop sink (up to 5'-0" AFF). Provide all finish transitions and edges as req'd.	
a	84" Pull:	9.13	Suspended Ceiling Grid and Acoustical Tile: See Materials Schedule	
i	Manufacturer: Strongar Hardware	A	Excess material quantity: Provide one (1) unopened case new material for future maintenance and/or repair.	
ii	Product: SH-PRO-LLPH-SB-84-SFIC-GL	9.14	Solid Surface Countertops:	
iii	Finish: Satin Brass	A	Manufacturer: See Materials Schedule	
iv	Location: Door 01	B	Product: See Materials Schedule	
v	Comments: Downward locking mechanism	C	Color: See Materials Schedule	
b	32" Pulls:	D	Finish: See Materials Schedule	
i	Manufacturer: Strongar Hardware	E	Edge Detail: See Materials Schedule	
ii	Product: SH-PRO-304-LPH-SB-32-1250	9.15	Quartz: See Materials Schedule	
iii	Finish: Satin Brass	A	Seams & Corners: Veining pattern to be matched at all seams in the quartz material	
iv	Location: Throughout	B	Mitering: All corners to be mitered; Veining pattern to transfer from horizontal to mitered vertical application	
XII	Pocket Door Kit w/ Soft Close:	C	Submittal: Awarded fabricator is required to provide slab smith drawing for sign off by design firm and end client prior to fabrication of materials.	
a	Manufacturer: Johnson Hardware	9.16	Translucent film: See Materials Schedule	
b	Product: 1500SC Series at 4 7/8" wall thickness			
XIII	ADA Paddle Pulls:			
a	Manufacturer: Trimco			
b	Product:			
i	Passage: 1069 (customized for 7-1/4" wall)			
ii	Pull Privacy: 1069FP (customized for 7-1/4" wall)			
c	Finish: Satin Brass			
XIV	Surface Mounted Closer:			
a	Manufacturer: LCN			
b	Product: 1461 Series			
c	Finish: Aluminum			
XV	Surface Mounted Overhead Stop:			
a	Manufacturer: Sargent			
b	Product: 590 Series			
c	Finish: Aluminum Painted			
8.4	Finish/material submittals: Provide samples of all exposed materials, including wood, hardware, and glazing.			
9.1	Finish Preparation: Provide all surface preparation for the proper installation of finishes per manufacturer's recommendations or, in the absence of available manufacturer's recommendations, follow industry quality standards.			
9.2	Floor Leveling: Provide allowance for floor leveling of up to 1".			
9.3	Gypsum Wallboard: ASTM C 36, in thickness indicated on plans, with manufacturer's standard edges.			
A	All gypsum wallboard at restroom areas shall be water resistant.			
B	Finish: Provide smooth, Level 4 finish at all gypsum wallboard walls, unless noted otherwise. Provide smooth, Level 5 finish at all non-white walls.			
C	Cementitious backer units: Comply with ANSI A118.9. Cementitious backer unit joint treatment materials - Comply with ASTM C 475.			
9.4	Acoustic Drywall:			
A	Manufacturer: Quietrock (www.quietrock.com, 214-842-9694)			
B	Model: Quietrock ES			