

SECTION 08 71 00.13 – DOOR HARDWARE SCHEDULE

HARDWARE GROUP NO. H3-400CGH

PROVIDE EACH PR DOOR(S) WITH THE FOLLOWING:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
8	EA	HINGE	5BB1 4.5 X 4.5	652	IVE
1	SET	CONST LATCHING BOLT	FB51P (TOP BOLT LENGTH AS REQ)	630	IVE
1	EA	DUST PROOF STRIKE	DP2	626	IVE
1	EA	PASSAGE SET	ND10S LON	626	SCH
1	EA	OH STOP & HOLDER	90H X SIZE AS REQ	630	GLY
1	EA	SURFACE CLOSER	4040XP SHCUSH	689	LCN
2	EA	KICK PLATE	8400 10" X 1" LDW B-CS	630	IVE
2	EA	ARMOR PLATE	8400 34" X 1" LDW B-CS	630	IVE
1	EA	GASKETING	188S H & J	BK	ZER
1	EA	ASTRAGAL	ACTIVE LEAF Z ASTRAGAL BY DOOR MANUFACTURER		
2	EA	<u>DOOR SWEEP</u>	<u>39A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>

HARDWARE GROUP NO. H3-401GHW

PROVIDE EACH SGL DOOR(S) WITH THE FOLLOWING:

<u>QTY</u>		<u>DESCRIPTION</u>	<u>CATALOG NUMBER</u>	<u>FINISH</u>	<u>MFR</u>
<u>3</u>	<u>EA</u>	<u>HINGE</u>	<u>5BB1HW 5 X 4.5</u>	<u>652</u>	<u>IVE</u>
<u>1</u>	<u>EA</u>	<u>PASSAGE SET</u>	<u>ND10S LON</u>	<u>626</u>	<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>SURFACE CLOSER</u>	<u>4040XP SHCUSH</u>	<u>689</u>	<u>LCN</u>
<u>1</u>	<u>EA</u>	<u>ARMOR PLATE</u>	<u>8400 34" X 1" LDW B-CS</u>	<u>630</u>	<u>IVE</u>
<u>1</u>	<u>EA</u>	<u>WALL STOP</u>	<u>WS406/407CCV</u>	<u>630</u>	<u>IVE</u>
<u>1</u>	<u>EA</u>	<u>GASKETING</u>	<u>188S H & J</u>	<u>BK</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>DOOR SWEEP</u>	<u>39A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>

HARDWARE GROUP NO. H3-501GW

PROVIDE EACH SGL DOOR(S) WITH THE FOLLOWING:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HINGE	5BB1HW 5 X 4.5	652	IVE
4	EA	CLASSROOM LOCK	ND70TD LON	626	SCH
4	EA	FSIC CORE	23-030 EV29-T	626	SCH
4	EA	SURFACE CLOSER	4040XP RW/PA AS REQ	689	LCN
4	EA	KICK PLATE	8400 10" X 2" LDW B-CS	630	IVE
4	EA	WALL STOP	WS406/407CCV	630	IVE
4	EA	GASKETING	188S H & J	BK	ZER
4	EA	DOOR SWEEP	39A LENGTH AS REQ	A	ZER

HARDWARE GROUP NO. H3-704

PROVIDE EACH PR DOOR(S) WITH THE FOLLOWING:

<u>QTY</u>		<u>DESCRIPTION</u>	<u>CATALOG NUMBER</u>	<u>FINISH</u>	<u>MFR</u>
<u>6</u>	<u>EA</u>	<u>HINGE</u>	<u>5BB1HW 4.5 X 4.5 NRP</u>	<u>630</u>	<u>IVE</u>
<u>1</u>	<u>EA</u>	<u>PANIC HARDWARE</u>	<u>LD-9847-L-LON</u>	<u>626</u>	<u>VON</u>
<u>1</u>	<u>EA</u>	<u>PANIC HARDWARE</u>	<u>LD-9847-EO</u>	<u>626</u>	<u>VON</u>
<u>1</u>	<u>EA</u>	<u>RIM CYLINDER</u>	<u>20-057 ICX W/CONST. CORE</u>	<u>626</u>	<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>FSIC CORE</u>	<u>23-030 EV29 T</u>	<u>626</u>	<u>SCH</u>
<u>2</u>	<u>EA</u>	<u>SURFACE CLOSER</u>	<u>4040XP SCUSH</u>	<u>689</u>	<u>LCN</u>
<u>2</u>	<u>EA</u>	<u>KICK PLATE</u>	<u>8400 10" X 1" LDW B-CS</u>	<u>630</u>	<u>IVE</u>
<u>2</u>	<u>EA</u>	<u>FLOOR STOP</u>	<u>FS18L</u>	<u>BLK</u>	<u>IVE</u>
<u>1</u>	<u>SET</u>	<u>MEETING STILE</u>	<u>328AA (2 PCS - 1 SET) HEIGHT AS REQ</u>	<u>AA</u>	<u>ZER</u>
<u>1</u>	<u>SET</u>	<u>GASKETING</u>	<u>328AA H & J</u>	<u>AA</u>	<u>ZER</u>
<u>2</u>	<u>EA</u>	<u>DOOR SWEEP</u>	<u>39A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>THRESHOLD</u>	<u>655A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>

HARDWARE GROUP NO. H3-705

PROVIDE EACH SGL DOOR(S) WITH THE FOLLOWING:

<u>QTY</u>		<u>DESCRIPTION</u>	<u>CATALOG NUMBER</u>	<u>FINISH</u>	<u>MFR</u>
<u>3</u>	<u>EA</u>	<u>HINGE</u>	<u>5BB1HW 4.5 X 4.5 NRP</u>	<u>630</u>	<u>IVE</u>
<u>1</u>	<u>EA</u>	<u>PANIC HARDWARE</u>	<u>LD-98-L-LON</u>	<u>626</u>	<u>VON</u>
<u>1</u>	<u>EA</u>	<u>RIM CYLINDER</u>	<u>20-057 ICX W/CONST. CORE</u>	<u>626</u>	<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>FSIC CORE</u>	<u>23-030 EV29 T</u>	<u>626</u>	<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>SURFACE CLOSER</u>	<u>4040XP SCUSH</u>	<u>689</u>	<u>LCN</u>
<u>1</u>	<u>EA</u>	<u>KICK PLATE</u>	<u>8400 10" X 2" LDW B-CS</u>	<u>630</u>	<u>IVE</u>
<u>1</u>	<u>EA</u>	<u>FLOOR STOP</u>	<u>FS18L</u>	<u>BLK</u>	<u>IVE</u>
<u>1</u>	<u>SET</u>	<u>GASKETING</u>	<u>328AA H & J</u>	<u>AA</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>DOOR SWEEP</u>	<u>39A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>THRESHOLD</u>	<u>655A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>

HARDWARE GROUP NO. H3-705W

PROVIDE EACH SGL DOOR(S) WITH THE FOLLOWING:

<u>QTY</u>		<u>DESCRIPTION</u>	<u>CATALOG NUMBER</u>	<u>FINISH</u>	<u>MFR</u>
<u>3</u>	<u>EA</u>	<u>HINGE</u>	<u>5BB1HW 5 X 4.5 NRP</u>	<u>630</u>	<u>IVE</u>
<u>1</u>	<u>EA</u>	<u>PANIC HARDWARE</u>	<u>LD-98-L-LON</u>	<u>626</u>	<u>VON</u>
<u>1</u>	<u>EA</u>	<u>RIM CYLINDER</u>	<u>20-057 ICX W/CONST. CORE</u>	<u>626</u>	<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>FSIC CORE</u>	<u>23-030 EV29 T</u>	<u>626</u>	<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>SURFACE CLOSER</u>	<u>4040XP SCUSH</u>	<u>689</u>	<u>LCN</u>
<u>1</u>	<u>EA</u>	<u>KICK PLATE</u>	<u>8400 10" X 2" LDW B-CS</u>	<u>630</u>	<u>IVE</u>
<u>1</u>	<u>EA</u>	<u>FLOOR STOP</u>	<u>FS18L</u>	<u>BLK</u>	<u>IVE</u>
<u>1</u>	<u>SET</u>	<u>GASKETING</u>	<u>328AA H & J</u>	<u>AA</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>DOOR SWEEP</u>	<u>39A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>THRESHOLD</u>	<u>655A</u>	<u>A</u>	<u>ZER</u>

OPERATIONAL DESCRIPTION: DOOR NORMALLY CLOSED AND LOCKED. ENTRY BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE. FREE EGRESS AT ALL TIME. UPON LOSS OF POWER, DOOR TO REMAIN LOCKED.

HARDWARE GROUP NO. H3-711CW

PROVIDE EACH SGL DOOR(S) WITH THE FOLLOWING:

<u>QTY</u>		<u>DESCRIPTION</u>	<u>CATALOG NUMBER</u>	<u>FINISH</u>	<u>MFR</u>
<u>3</u>	<u>EA</u>	<u>HINGE</u>	<u>5BB1HW 5 X 4.5 NRP</u>	<u>652</u>	<u>IVE</u>
<u>4</u>	<u>EA</u>	<u>PANIC HARDWARE</u>	<u>99-L-NL-LON</u>	<u>626</u>	<u>VON</u>
<u>4</u>	<u>EA</u>	<u>RIM CYLINDER</u>	<u>20-057 ICX W/CONST. CORE</u>	<u>626</u>	<u>SCH</u>
<u>4</u>	<u>EA</u>	<u>FSIC CORE</u>	<u>23-030 EV29 T</u>	<u>626</u>	<u>SCH</u>
<u>4</u>	<u>EA</u>	<u>SURFACE CLOSER</u>	<u>4040XP SCUSH</u>	<u>689</u>	<u>LCN</u>
<u>3</u>	<u>EA</u>	<u>SILENCER</u>	<u>SR64</u>	<u>GRY</u>	<u>IVE</u>

HARDWARE GROUP NO. (H3-714AV-D) H3-714AV

PROVIDE EACH PR DOOR(S) WITH THE FOLLOWING:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
2	EA	CONT. HINGE	112XY	710	IVE
2	EA	<u>HINGES</u>	<u>BY DOOR/FRAME</u> <u>MANUFACTURER</u>	<u>TBD</u>	<u>B/O</u>
4	EA	PANIC HARDWARE	3547A-EQ	313	VON
4	EA	PANIC HARDWARE	3547A-NL-OP-388	313	VON
2	EA	<u>KEYED PANIC DEVICE</u>	<u>PDU8501 X 3 PULL (10" AFF)</u> <u>BLACK GLOSS LETTERING</u>	<u>US32D</u>	<u>ROC</u>
(2)1	EA	RIM CYLINDER	20-057 ICX W/CONST. CORE	(613) <u>626</u>	SCH
(2)1	EA	FSIC CORE	23-030 EV29 T	(613) <u>626</u>	SCH
2	EA	LONG DOOR PULL	9264F 36" Q	613	IVE
2	EA	CONCEALED CLOSER	2030 WMS	(695) <u>689</u>	LCN
2	EA	FLOOR STOP	FS18L	BLK	IVE
1	SET	SEAL	PERIMETER SEAL BY FRAME MANUFACTURER		
1	SET	ASTRAGAL	MEETING STILE SEAL BY DOOR MANUFACTURER		
2	EA	DOOR SWEEP	39D LENGTH AS REQ	D	ZER
4	EA	THRESHOLD	103D LENGTH AS REQ	D	ZER
2	EA	<u>DOOR SWEEP</u>	<u>39A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>
1	EA	<u>THRESHOLD</u>	<u>103A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>

HARDWARE GROUP NO. H3-715AV

PROVIDE EACH SGL DOOR(S) WITH THE FOLLOWING:

<u>QTY</u>		<u>DESCRIPTION</u>	<u>CATALOG NUMBER</u>	<u>FINISH</u>	<u>MFR</u>
<u>1</u>	<u>EA</u>	<u>HINGES</u>	<u>BY DOOR/FRAME</u> <u>MANUFACTURER</u>	<u>TBD</u>	<u>B/O</u>
<u>1</u>	<u>EA</u>	<u>KEYED PANIC DEVICE</u>	<u>PDU8501 X 3 PULL (10" AFF)</u> <u>BLACK GLOSS LETTERING</u>	<u>US32D</u>	<u>ROC</u>
<u>1</u>	<u>EA</u>	<u>MORTISE CYLINDER</u>	<u>AS REQ</u>	<u>626</u>	<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>FSIC CORE</u>	<u>23-030 EV29 T</u>	<u>626</u>	<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>CONCEALED CLOSER</u>	<u>2030 WMS</u>	<u>689</u>	<u>LCN</u>
<u>1</u>	<u>EA</u>	<u>FLOOR STOP</u>	<u>FS18L</u>	<u>BLK</u>	<u>IVE</u>
<u>1</u>	<u>SET</u>	<u>SEAL</u>	<u>PERIMETER SEAL BY FRAME</u> <u>MANUFACTURER</u>		
<u>1</u>	<u>EA</u>	<u>DOOR SWEEP</u>	<u>39A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>THRESHOLD</u>	<u>103A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>

HARDWARE GROUP NO. H3-C205

PROVIDE EACH SGL DOOR(S) WITH THE FOLLOWING:

<u>QTY</u>		<u>DESCRIPTION</u>	<u>CATALOG NUMBER</u>	<u>FINISH</u>	<u>MFR</u>
<u>3</u>	<u>EA</u>	<u>HINGE</u>	<u>5BB1HW 4.5 X 4.5 NRP</u>	<u>630</u>	<u>IVE</u>
<u>1</u>	<u>EA</u>	<u>POWER TRANSFER</u>	<u>EPT-5</u>	<u>628</u>	<u>PRE</u>
<u>1</u>	<u>EA</u>	<u>EU MORTISE LOCK</u>	<u>L9092TEU LONA RX CON (FAIL</u> <u>SECURE)</u>	<u>626</u>	<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>FSIC CORE</u>	<u>23-030 EV29 T</u>	<u>626</u>	<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>SURFACE CLOSER</u>	<u>4040XP SCUSH</u>	<u>689</u>	<u>LCN</u>
<u>1</u>	<u>EA</u>	<u>ARMOR PLATE</u>	<u>8400 34" X 1" LDW B-CS</u>	<u>630</u>	<u>IVE</u>
<u>1</u>	<u>SET</u>	<u>GASKETING</u>	<u>328AA H & J</u>	<u>AA</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>DOOR SWEEP</u>	<u>39A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>THRESHOLD</u>	<u>655A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>HARNESS (IN DOOR)</u>	<u>ALLEGION CONNECT TYPE &</u> <u>LENGTH AS REQ</u>		<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>CREDENTIAL READER</u>	<u>CREDENTIAL READER BY</u> <u>ANOTHER SECTION</u>		
<u>1</u>	<u>EA</u>	<u>DOOR POSITION SWITCH</u>	<u>DOOR CONTACT BY ANOTHER</u> <u>SECTION</u>		
<u>1</u>	<u>EA</u>	<u>POWER SUPPLY</u>	<u>POWER SUPPLY BY ANOTHER</u> <u>SECTION</u>		

OPERATIONAL DESCRIPTION: DOOR NORMALLY CLOSED AND LOCKED. ENTRY BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE. FREE EGRESS AT ALL TIME. UPON LOSS OF POWER, DOOR TO REMAIN LOCKED.

HARDWARE GROUP NO. H3-C205I

PROVIDE EACH SGL DOOR(S) WITH THE FOLLOWING:

<u>QTY</u>		<u>DESCRIPTION</u>	<u>CATALOG NUMBER</u>	<u>FINISH</u>	<u>MFR</u>
<u>3</u>	<u>EA</u>	<u>HINGE</u>	<u>5BB1HW 4.5 X 4.5</u>	<u>630</u>	<u>IVE</u>
<u>1</u>	<u>EA</u>	<u>POWER TRANSFER</u>	<u>EPT-5</u>	<u>628</u>	<u>PRE</u>
<u>1</u>	<u>EA</u>	<u>EU MORTISE LOCK</u>	<u>L9092TEU LONA RX CON (FAIL</u> <u>SECURE)</u>	<u>626</u>	<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>FSIC CORE</u>	<u>23-030 EV29 T</u>	<u>626</u>	<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>SURFACE CLOSER</u>	<u>4040XP RW/PA AS REQ</u>	<u>689</u>	<u>LCN</u>
<u>1</u>	<u>EA</u>	<u>ARMOR PLATE</u>	<u>8400 34" X 1" LDW B-CS</u>	<u>630</u>	<u>IVE</u>
<u>1</u>	<u>EA</u>	<u>WALL STOP</u>	<u>WS406/407CCV</u>	<u>630</u>	<u>IVE</u>
<u>1</u>	<u>SET</u>	<u>GASKETING</u>	<u>328AA H & J</u>	<u>AA</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>DOOR SWEEP</u>	<u>39A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>THRESHOLD</u>	<u>655A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>HARNESS (IN DOOR)</u>	<u>ALLEGION CONNECT TYPE &</u> <u>LENGTH AS REQ</u>		<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>CREDENTIAL READER</u>	<u>CREDENTIAL READER BY</u> <u>ANOTHER SECTION</u>		
<u>1</u>	<u>EA</u>	<u>DOOR POSITION SWITCH</u>	<u>DOOR CONTACT BY ANOTHER</u> <u>SECTION</u>		
<u>1</u>	<u>EA</u>	<u>POWER SUPPLY</u>	<u>POWER SUPPLY BY ANOTHER</u> <u>SECTION</u>		

OPERATIONAL DESCRIPTION: DOOR NORMALLY CLOSED AND LOCKED. ENTRY BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE. FREE EGRESS AT ALL TIME. UPON LOSS OF POWER, DOOR TO REMAIN LOCKED.

HARDWARE GROUP NO. H3-C205W

PROVIDE EACH SGL DOOR(S) WITH THE FOLLOWING:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HINGE	5BB1HW 5 X 4.5 NRP	630	IVE
4	EA	POWER TRANSFER	EPT10 CON	689	VON
<u>1</u>	<u>EA</u>	<u>POWER TRANSFER</u>	<u>EPT-5</u>	<u>628</u>	<u>PRE</u>
1	EA	EU MORTISE LOCK	L9092TEU LONA RX CON (FAIL SECURE)	626	SCH
1	EA	FSIC CORE	23-030 EV29 T	626	SCH
1	EA	SURFACE CLOSER	4040XP SCUSH	689	LCN
1	EA	KICK PLATE	8400 10" X 2" LDW B-CS	630	IVE
1	SET	GASKETING	328AA H & J	AA	ZER
1	EA	DOOR SWEEP	39A	A	ZER
1	EA	THRESHOLD	655A	A	ZER
1	EA	HARNESS (IN DOOR)	ALLEGION CONNECT TYPE & LENGTH AS REQ		SCH
1	EA	CREDENTIAL READER	CREDENTIAL READER BY ANOTHER SECTION		
1	EA	DOOR POSITION SWITCH	DOOR CONTACT BY ANOTHER SECTION		
1	EA	POWER SUPPLY	POWER SUPPLY BY ANOTHER SECTION		

OPERATIONAL DESCRIPTION: DOOR NORMALLY CLOSED AND LOCKED. ENTRY BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE. FREE EGRESS AT ALL TIME. UPON LOSS OF POWER, DOOR TO REMAIN LOCKED.

HARDWARE GROUP NO. (H3-C214) H3-C214PW

PROVIDE EACH PR DOOR(S) WITH THE FOLLOWING:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
6	EA	HINGE	5BB1HW 4.5 X 4.5 NRP	630	IVE
<u>6</u>	<u>EA</u>	<u>HINGE</u>	<u>5BB1HW 5 X 4.5 NRP</u>	<u>630</u>	<u>IVE</u>
4	EA	POWER TRANSFER	EPT40 CON	689	VON
<u>1</u>	<u>EA</u>	<u>POWER TRANSFER</u>	<u>EPT-5</u>	<u>628</u>	<u>PRE</u>
1	SET	CONST LATCHING BOLT	FB51P	630	IVE
1	EA	DUST PROOF STRIKE	DP2	626	IVE
1	EA	EU MORTISE LOCK	L9092TEU LONA RX CON (FAIL SECURE)	626	SCH
1	EA	FSIC CORE	23-030 EV29 T	626	SCH
4	EA	OH STOP	90S X SIZE & MOUNTING AS REQ (INACTIVE LEAF)	630	GLY
4	EA	SURFACE CLOSER	4040XP SCUSH (ACTIVE LEAF)	689	LCN
<u>1</u>	<u>EA</u>	<u>SURFACE CLOSER</u>	<u>4040XP HEDA (ACTIVE LEAF ONLY)</u>	<u>689</u>	<u>LCN</u>
2	EA	KICK PLATE	8400 10" X 1" LDW B-CS	630	IVE
<u>2</u>	<u>EA</u>	<u>ARMOR PLATE</u>	<u>8400 34" X 1" LDW B-CS</u>	<u>630</u>	<u>IVE</u>
<u>2</u>	<u>EA</u>	<u>FLOOR STOP</u>	<u>FS18L</u>	<u>BLK</u>	<u>IVE</u>
1	EA	GASKETING	188S HEIGHT AS REQ (MOUNT ON ASTRAGAL)	BK	ZER
1	SET	GASKETING	328AA H & J	AA	ZER
1	EA	ASTRAGAL	ACTIVE LEAF Z ASTRAGAL BY DOOR MANUFACTURER		
2	EA	DOOR SWEEP	39A	A	ZER
1	EA	THRESHOLD	655A	A	ZER
1	EA	HARNESS (IN DOOR)	ALLEGION CONNECT TYPE & LENGTH AS REQ		SCH
1	EA	CREDENTIAL READER	CREDENTIAL READER BY ANOTHER SECTION		
2	EA	DOOR POSITION SWITCH	DOOR CONTACT BY ANOTHER SECTION		
1	EA	POWER SUPPLY	POWER SUPPLY BY ANOTHER SECTION		

OPERATIONAL DESCRIPTION: DOORS NORMALLY CLOSED AND LOCKED. ENTRY BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE. FREE EGRESS AT ALL TIME. UPON LOSS OF POWER, DOORS TO REMAIN LOCKED.

-PROVIDE 7/8" LIP STRIKE.

NOTE: FLOOR STOPS TO BE INSTALLED FLUSH AGAINST WALL SO DOORS CAN SWING 180 DEGREES.

HARDWARE GROUP NO. H3-C704

PROVIDE EACH PR DOOR(S) WITH THE FOLLOWING:

<u>QTY</u>		<u>DESCRIPTION</u>	<u>CATALOG NUMBER</u>	<u>FINISH</u>	<u>MFR</u>
<u>6</u>	<u>EA</u>	<u>HINGE</u>	<u>5BB1HW 4.5 X 4.5 NRP</u>	<u>630</u>	<u>IVE</u>
<u>2</u>	<u>EA</u>	<u>POWER TRANSFER</u>	<u>EPT-5</u>	<u>628</u>	<u>PRE</u>
<u>1</u>	<u>EA</u>	<u>ELEC PANIC HARDWARE</u>	<u>LD-RX-9847-L-M996-LON-FSE-CON</u>	<u>626</u>	<u>VON</u>
			<u>(FAIL SECURE)</u>		
<u>1</u>	<u>EA</u>	<u>ELEC PANIC HARDWARE</u>	<u>LD-RX-9847-EO-CON</u>	<u>626</u>	<u>VON</u>
<u>1</u>	<u>EA</u>	<u>RIM CYLINDER</u>	<u>20-057 ICX W/CONST. CORE</u>	<u>626</u>	<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>FSIC CORE</u>	<u>23-030 EV29 T</u>	<u>626</u>	<u>SCH</u>
<u>2</u>	<u>EA</u>	<u>SURFACE CLOSER</u>	<u>4040XP SCUSH</u>	<u>689</u>	<u>LCN</u>
<u>2</u>	<u>EA</u>	<u>KICK PLATE</u>	<u>8400 10" X 1" LDW B-CS</u>	<u>630</u>	<u>IVE</u>
<u>2</u>	<u>EA</u>	<u>FLOOR STOP</u>	<u>FS18L</u>	<u>BLK</u>	<u>IVE</u>
<u>1</u>	<u>SET</u>	<u>MEETING STILE</u>	<u>328AA (2 PCS - 1 SET) HEIGHT AS</u>	<u>AA</u>	<u>ZER</u>
			<u>REQ</u>		
<u>1</u>	<u>SET</u>	<u>GASKETING</u>	<u>328AA H & J</u>	<u>AA</u>	<u>ZER</u>
<u>2</u>	<u>EA</u>	<u>DOOR SWEEP</u>	<u>39A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>THRESHOLD</u>	<u>655A</u>	<u>A</u>	<u>ZER</u>
<u>2</u>	<u>EA</u>	<u>HARNESS (IN DOOR)</u>	<u>ALLEGION CONNECT TYPE &</u>		<u>SCH</u>
			<u>LENGTH AS REQ</u>		
<u>1</u>	<u>EA</u>	<u>CREDENTIAL READER</u>	<u>CREDENTIAL READER BY</u>		
			<u>ANOTHER SECTION</u>		
<u>2</u>	<u>EA</u>	<u>DOOR POSITION SWITCH</u>	<u>DOOR CONTACT BY ANOTHER</u>		
			<u>SECTION</u>		
<u>1</u>	<u>EA</u>	<u>POWER SUPPLY</u>	<u>POWER SUPPLY BY ANOTHER</u>		
			<u>SECTION</u>		

OPERATIONAL DESCRIPTION: DOORS NORMALLY CLOSED AND LOCKED. ENTRY BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE. FREE EGRESS AT ALL TIME. UPON LOSS OF POWER, DOORS TO REMAIN LOCKED.

HARDWARE GROUP NO. H3-C705

PROVIDE EACH SGL DOOR(S) WITH THE FOLLOWING:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HINGE	5BB1HW 4.5 X 4.5 NRP	630	IVE
4	EA	POWER TRANSFER	EPT10-CON	689	VON
<u>1</u>	<u>EA</u>	<u>POWER TRANSFER</u>	<u>EPT-5</u>	<u>628</u>	<u>PRE</u>
1	EA	ELEC PANIC HARDWARE	LD-RX-98-L-M996-LON-FSE-CON	626	VON
1	EA	RIM CYLINDER	20-057 ICX W/CONST. CORE	626	SCH
1	EA	FSIC CORE	23-030 EV29 T	626	SCH
1	EA	SURFACE CLOSER	4040XP SCUSH	689	LCN
1	EA	KICK PLATE	8400 10" X 2" LDW B-CS	630	IVE
1	EA	FLOOR STOP	FS18L	BLK	IVE
1	SET	GASKETING	328AA H & J	AA	ZER
1	EA	DOOR SWEEP	39A	A	ZER
1	EA	THRESHOLD	655A	A	ZER
1	EA	HARNESS (IN DOOR)	ALLEGION CONNECT TYPE & LENGTH AS REQ		SCH
1	EA	CREDENTIAL READER	CREDENTIAL READER BY ANOTHER SECTION		
1	EA	DOOR POSITION SWITCH	DOOR CONTACT BY ANOTHER SECTION		
1	EA	POWER SUPPLY	POWER SUPPLY BY ANOTHER SECTION		

OPERATIONAL DESCRIPTION: DOOR NORMALLY CLOSED AND LOCKED. ENTRY BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE. FREE EGRESS AT ALL TIME. UPON LOSS OF POWER, DOOR TO REMAIN LOCKED.

HARDWARE GROUP NO. H3-C705W

PROVIDE EACH SGL DOOR(S) WITH THE FOLLOWING:

<u>QTY</u>		<u>DESCRIPTION</u>	<u>CATALOG NUMBER</u>	<u>FINISH</u>	<u>MFR</u>
<u>3</u>	<u>EA</u>	<u>HINGE</u>	<u>5BB1HW 5 X 4.5 NRP</u>	<u>630</u>	<u>IVE</u>
<u>1</u>	<u>EA</u>	<u>POWER TRANSFER</u>	<u>EPT-5</u>	<u>628</u>	<u>PRE</u>
<u>1</u>	<u>EA</u>	<u>ELEC PANIC HARDWARE</u>	<u>LD-RX-98-L-M996-LON-FSE-CON</u>	<u>626</u>	<u>VON</u>
<u>1</u>	<u>EA</u>	<u>RIM CYLINDER</u>	<u>20-057 ICX W/CONST. CORE</u>	<u>626</u>	<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>FSIC CORE</u>	<u>23-030 EV29 T</u>	<u>626</u>	<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>SURFACE CLOSER</u>	<u>4040XP SCUSH</u>	<u>689</u>	<u>LCN</u>
<u>1</u>	<u>EA</u>	<u>KICK PLATE</u>	<u>8400 10" X 2" LDW B-CS</u>	<u>630</u>	<u>IVE</u>
<u>1</u>	<u>EA</u>	<u>FLOOR STOP</u>	<u>FS18L</u>	<u>BLK</u>	<u>IVE</u>
<u>1</u>	<u>SET</u>	<u>GASKETING</u>	<u>328AA H & J</u>	<u>AA</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>DOOR SWEEP</u>	<u>39A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>THRESHOLD</u>	<u>655A LENGTH AS REQ</u>	<u>A</u>	<u>ZER</u>
<u>1</u>	<u>EA</u>	<u>HARNESS (IN DOOR)</u>	<u>ALLEGION CONNECT TYPE & LENGTH AS REQ</u>		<u>SCH</u>
<u>1</u>	<u>EA</u>	<u>CREDENTIAL READER</u>	<u>CREDENTIAL READER BY ANOTHER SECTION</u>		
<u>1</u>	<u>EA</u>	<u>DOOR POSITION SWITCH</u>	<u>DOOR CONTACT BY ANOTHER SECTION</u>		
<u>1</u>	<u>EA</u>	<u>POWER SUPPLY</u>	<u>POWER SUPPLY BY ANOTHER SECTION</u>		

OPERATIONAL DESCRIPTION: DOOR NORMALLY CLOSED AND LOCKED. ENTRY BY VALID CREDENTIAL OR MANUAL KEY OVERRIDE. FREE EGRESS AT ALL TIME. UPON LOSS OF POWER, DOOR TO REMAIN LOCKED.

