

KEYED NOTES:

1 PROVIDE MULTI-POLE BREAKER FOR MULTIWIRE BRANCH CIRCUITS WHICH ARE TO REMAIN. FIELD VERIFY.

LIGHTING FIXTURE SCHEDULE								
TYPE	MANUFACTURER	CATALOG NUMBER	VOLTAGE	SOURCE	TOTAL FIXTURE LUMENS	MAXIMUM FIXTURE WATTAGE	DESCRIPTION	KEYED NOTES
A1	HE WILLIAMS	4DR-TL-L10-8-35-DIM-UNV-OW-OF-CS-N-F1	120	LED	1000	10	4" DIAMETER RECESSED DOWN LIGHT	
A3	HE WILLIAMS	4DR-TL-L20-8-35-DIM-UNV-OW-OF-CS-N-F1	120	LED	2000	17	4" DIAMETER RECESSED DOWN LIGHT	
B1	HE WILLIAMS	MX2D-4'00-L4/835-S-F-ACFS/Dxx-Sxx58D/B-DIM-UNV-HEW BLACK	120	LED	1500	14	4" LINEAR PENDANT	1
B1E	HE WILLIAMS	MX2D-4'00-L4/835-S-F-ACFS/Dxx-Sxx58D/B-DIM-UNV-HEW BLACK	120	LED	1500	14	4" LINEAR PENDANT	1,2
C	AFX	BRQP42LAJUDBK	120	LED	2750	40	4-LAMP PENDANT. FIELD SELECT 3500K COLOR TEMP.	
D	(NOT USED)	-	-	-	-	-	-	
GE	HE WILLIAMS	W4CR-12-L15-8-35-PC-WHT-DIM-UNV-W-WMS	120	LED	1250	12	4" DIAMETER EXTERIOR WALL-MOUNT CYLINDER WITH INTEGRAL PHOTOCELL	
HE	HE WILLIAMS	4CR-13-L15-8-35-BLK-DIM-UNV-L-W-CS-AD-WM	120	LED	1500	18	4" DIAMETER WALL MOUNT CYLINDER WITH INTEGRAL DRIVER	2
J1	HE WILLIAMS	MX2D-4'00-L4/835-S-F-ACFS/Dxx-Sxx58D/B-DIM-UNV-HEW BLACK	120	LED	1500	14	4" LINEAR PENDANT, ASYMMETRICAL OPTIC	1
K1	HE WILLIAMS	4DR-TL-L10-8-30-DIM-UNV-FW-OF-SG-N-F1	120	LED	1000	10	4" DIAMETER RECESSED DOWN LIGHT	
K1E	HE WILLIAMS	4DR-TL-L10-8-30-EM/7WRTS-DIM-UNV-FW-OF-SG-N-F1	120	LED	1000	10	4" DIAMETER RECESSED DOWN LIGHT WITH INTEGRAL 7W EMERGENCY BATTERY	
L1	HE WILLIAMS	MX2D-3'06-L4/835-S-F-ACFS/Dxx-Sxx58D/B-DIM-UNV-HEW BLACK	120	LED	1300	12	3'-6" LINEAR PENDANT	1
M2	METALUX	4-SNLED-LD5-27SL-LW-UNV-L840-CD-1	120/277	LED	2700	21	4' STRIP LIGHT, CHAIN-HUNG AT 9'-0", UIO	
S1	-	REFER TO SHULER SHOOK DRAWING SKE 012	120	-	-	-	WALL SCONCE	
S2	-	REFER TO SHULER SHOOK DRAWING SKE 012	120	-	-	-	36" RECESSED LINEAR WALLWASH	
S3	-	REFER TO SHULER SHOOK DRAWING SKE 012	120	-	-	-	36" RECESSED LINEAR DOWNLIGHT	
S4	-	REFER TO SHULER SHOOK DRAWING SKE 012	120	-	-	-	32" RECESSED LINEAR DOWNLIGHT	
S5	-	REFER TO SHULER SHOOK DRAWING SKE 012	120	-	-	-	ROUND RECESSED WALLWASH	
S6	-	REFER TO SHULER SHOOK DRAWING SKE 012	120	-	-	-	ROUND RECESSED ADJUSTABLE DOWNLIGHT	
S7	-	REFER TO SHULER SHOOK DRAWING SKE 012	120	-	-	-	INDUSTRIAL WALL-MOUNT	
S8	-	REFER TO SHULER SHOOK DRAWING SKE 012	120	-	-	-	4" LINEAR WALL-MOUNT	
T	COLUMBIA	NBT-24-35-LQ32-G-SF-ED1-U-FK24	120	LED	3200	23	2X4' FLAT PANEL	
XE	HE WILLIAMS	EXIT/EL-SF-R-CP-BLK-AC-D	120	LED	-	5	EXIT SIGN. AC ONLY. CHEVRONS AND FACES PER PLANS.	
XS	MULE LIGHTING	EGX-20-1-R-8	120	LED	-	-	EXIT SIGN. SELF-LUMINOUS, NO POWER REQUIRED. CHEVRONS AND FACES PER PLANS.	

LIGHTING FIXTURE SCHEDULE GENERAL NOTES:

1. PROVIDE FLANGE KIT AND MOUNTING HARDWARE AS REQUIRED.

LIGHTING FIXTURE SCHEDULE KEYED NOTES:

1. COORDINATE MOUNTING AND SUSPENSION LENGTH WITH CEILING. BOTTOM OF FIXTURE SHALL BE FLUSH WITH BOTTOM OF CEILING BAFFLES.
2. EMERGENCY LIGHTING FIXTURE IS BACKED UP BY A CENTRAL INVERTER. SEE EL101.

PANEL D		MOUNTING FLUSH		LOCATION		COMP LAB		MAIN BUS RATING 100		AMPS							
MAIN CB		POLES 3		FRAME 100		TRIP 100											
VOLTAGE 208Y/120		PHASE 3		MINIMUM BREAKER INTERRUPTING CAPACITY 10kA													
ACCESSORIES SN + EQP GND																	
DEVICE			BRANCH CIRCUIT				PHASE LOAD				BRANCH CIRCUIT			DEVICE			
							VOLT AMPS										
AMPS	TRIP	POLES	TYPE	LOAD	DESCRIPTION	VOLT AMPS	NO	A	B	C	NO	VOLT AMPS	DESCRIPTION	LOAD	TYPE	POLES	AMPS
20	1		L	L	COMP LAB,RR LTS	1174	1	1374			2	200	(E) EXTERIOR LIGHTS		L	1	20
20	1		L	L	LOBBY LTS	254	3		554		4	300	(E) EXTERIOR LIGHTS		L	1	20
20	1		L	L	LOBBY LTS	150	5				6	400	(E) EXTERIOR LIGHTS		L	1	20
20	1		R		COMP LAB RECEPS	720	7	1020			8	300	(E) EXTERIOR LIGHTS		L	1	20
20	1		R		COMP LAB RECEPS	720	9		1260		10	540	(E) LOBBY RECEPS		R	1	20
20	1		R		COMP LAB RECEPS	900	11			1260	12	360	(E) LOBBY RECEPS		R	1	20
20	1		R		COMP LAB RECEPS	720	13	1260			14	540	(E) LOBBY RECEPS		R	1	20
20	1		M		(E) UNKNOWN		15				16		(E) UNKNOWN		M	1	20
20	1		M		(E) UNKNOWN		17				18		(E) UNKNOWN		M	2	30
20	1		M		(E) UNKNOWN		19				20		-		M		-
20	1		M		(E) UNKNOWN		21		2600		22	2600	MSOU-1		H	2	40
20	1		M		(E) UNKNOWN		23			2600	24	2600	-		H		-
20	1	G	M		WATER COOLER	600	25	3351			26	2751	GPU-1		H	3	40
20	1				SPARE		27		2751		28	2751	-		H		-
20	1		M		RR PLUMBING SENSORS	200	29			2951	30	2751	-		H		-
20	1	R.O	M		FIRE ALARM CIRCUIT	400	31	1120			32	720	JANITOR,TLT,EXT RECEPS		R	1	20
15	2	L	M		WATER HEATER	750	33		750		34		SPACE				
-			M		-	750	35			750	36		SPACE				
15	2		H		MSFC-1.1,MSFC-1.2	60	37	60			38		SPACE				
-			H		-	60	39		60		40		SPACE				
					SPACE		41				42		SPACE				
TOTAL								8185	7975	8111	24 KVA (CONNECTED)			67 AMPS (CONNECTED)			
											24 KVA (DEMAND)			67 AMPS (DEMAND)			