

Quality People. Building Solutions.

Comfort Systems USA (Arkansas), Inc. P.O. Box 16620 Little Rock, AR 72231 Phone 501-834-3320 Fax 501-834-5416

Date: 5/17/2024

Return Request: 5/27/2024

Project: CALS Main Library Renovations **Supplier:** Coleman Industrial Construction

Manufacturer: Various

Submittal: HVAC Piping Insulation **Submittal Number:** 23 07 19-01

Drawing # and Installation: Mechanical Drawings

ARCHITECT

Polk Stanley Wilcox 801 South Spring St. Little Rock, AR 72201 501-378-0878

GENERAL CONTRACTOR

CDI 3000 Cantrell Rd. Little Rock, AR 72202 501-5666-4300 **ENGINEER**

Bernhard 1 Allied Drive, Bldg. 2, Suite 2600 Little Rock, AR 72202 501-666-6776

MECHANICAL SUBCONTRACTOR

Comfort Systems USA (Arkansas), Inc. 9924 Landers Rd. N. Little Rock, AR 72117 501-834-3320

Notes:			

CSUSA PROJECT NO. 23-8016

dpierce@comfortar.com

1001 Swift Ave North Kansas City MO. 64116



Phone: (816)741-8383 Fax: (816)741-0542 Email: office@cickc.com

April 30, 2024

Comfort Systems USA 9924 Landers Rd North Little Rock, AR 72117

Mr. Daniel Pierce

Re: Mechanical Insulation Submittals for CALS Main Reno, Little Rock, Arkansas.

Specs on prints.

The following items will be insulated with Johns Manville pipe insulation with ASJ + vapor barrier jacket. All fittings will have an additional PVC fitting cover. All Exposed Piping will be Jacketed with .020 PVC.

Item #1: Heating and Chilled Water----- 2" Thick

Thank You, Chad Bartlett



MICRO-LOK® HP HIGH-PERFORMANCE FIBERGLASS PIPE INSULATION

DATA SHEET

DESCRIPTION

Micro-Lok *HP* fiberglass pipe insulation is a high-performance insulation made from biosoluble glass fibers bonded with a thermosetting resin and produced in 36" (0.92 m) lengths. Micro-Lok *HP* insulation is used to insulate standard iron pipe, plastic pipe and copper tubing. The 3' (0.92 m) sections are available plain or with a factory-applied vapor-barrier jacket. The all-service (ASJ) vapor-retarder jacket includes a longitudinal, self-sealing closure lap. The jacket system is adhered to each fiberglass section using a specially formulated adhesive to ensure jacket securement.

The factory-installed tape system permits installation at ambient temperatures down to 20°F (-7°C) and will not soften or separate when exposed to high ambient temperatures and humidity.

USES

Micro-Lok *HP* fiberglass pipe insulation is suitable for installation over hot, cold, concealed and exposed piping systems with operating temperatures up to 850°F (454°C). Weather-protective jacketing is required for outdoor applications. Pipes operating below ambient temperatures require all joints to be sealed with the factory-applied, self-seal lap and butt strips. Micro-Lok HP is UL listed and labeled over plastic pipes for air plenum applications when used at 1.0" thickness or greater.

PHYSICAL PROPERTIES

Service Temp. Range (ASTM C411)	0°F to 850°F (-18°C to 454°C)
Moisture Sorption	<5% by weight
Corrosivity (ASTM C1617)	<5 ppm chloride standard
Shrinkage (ASTM C356)	None
Microbial Growth (ASTM C1338)	Does not promote microbial growth
Surface Burning	Composite FHC 25/50 per ASTM E84,
Characteristics	NFPA 255, CAN/ULC \$102.2
Limited Combustibility	NFPA 90A and 90B
Jacketing	ASTM C1136 (Type I & II)
Water Vapor Permeance	0.02 perms max.
(ASTM E96 – Procedure A)	
Burst Strength (ASTM D774)	55 lbs/in ² (4.6 Kg/cm ²)
Tensile Strength (ASTM D828)	45 lbs./in. (7.9N/mm) width min. (MD)
	30 lbs./in. (5.23N/mm) width min. (CD)

SPECIFICATION COMPLIANCE


- ASTM C547 Type I (Replaces HH-I-558B, Form D, Type III, Class 12, Class 13 up to 850°F [454°C])
- ASTM C585 Dimension Standard
- ASTM C1136 (Jacketing) (Replaces HH-B-100B, Type I & II)
- •MIL-DTL-32585 Type 1, Form 4, Facing A (unjacketed only)
- MIL-I-22344D, MIL-PRF-22344E
- Coast Guard/IMO Approved 164.109/56/0 (plain, unjacketed only excluding $^{7}/_{8}$ x $\frac{1}{2}$ [22 mm x 13 mm], $\frac{1}{2}$ x $\frac{1}{2}$ [13 mm x 13 mm])
- Bureau of Household Goods and Services CA-T1039 (CO)
- Firestop Assemblies: Meets requirement for jacketed fiberglass pipe insulation product density at or above 3.5 pcf.
- ASTM E84, CAN ULC S102.2 25/50 listed and labeled Intertek testing laboratories, listed and labeled Underwriter Laboratories
- NRC 1.36, ASTM C795, MIL-I-24244C, MIL-DTL-24244D*

 *When ordering material to comply with these specifications a statement of that fact must appear on the purchase order. Specific lot testing will be conducted and a certification of compliance can be provided.

Operating Temperature Limits: 0°F to 850°F (-18°C to 454°C)



THERMAL CONDUCTIVITY ("K") *



Mean	°F	75	100	200	300	400	500
Temperature	°C	24	38	93	149	204	260
Btu•in/(hr•ft²•°F)		0.23	0.24	0.28	0.34	0.44	0.55
W/m•°C		0.034	0.035	0.040	0.049	0.063	0.079

^{*} Apparent thermal conductivity values are determined by applying procedures dictated per ASTM C1045 on test data obtained using ASTM Test Method C335. All values are based on nominal manufacturing and testing parameters, are subject to normal variation, and are not guaranteed for specification purposes or otherwise.

SUSTAINABLE BUILDING ATTRIBUTES

Manufacturing Location Defiance, Ohio (43512)			
Recycled Content (glass only)	41%		
Recycled Content (total product)	28%		
Volatile Organic Compounds (ASTM D5116)	Total	0.22 g/l	
(Analysis ASTM D6196 & ASTM D5197)			
Fiberglass Pipe Insulation	Formaldehyde	0.009 ppm	
	Aldehydes	0.043 ppm	
Volatile Organic Compounds (Calculated)	Total	<49 g/l	
Self-Sealing Lap & Butt Strips			

SUSTAINABLE BUILDING CERTIFICATIONS

GREENGUARD®	Certified
GREENGUARD® GOLD	Certified
LEED® Credits	To see LEED info call technical support
LEED-NC	









MICRO-LOK® HP

HIGH-PERFORMANCE FIBERGLASS PIPE INSULATION

DATA SHEET

SIZE AVAILABILITY

Insulation	n Thickness	Iron Pipe S	ize Range	Copper Tub	ing Size Range	Notes:
in.	mm	in.	mm	in.	mm	*2½" and 23" IPS not available in this
1/2	13	1/2-6	13–152	5/8-41/8 [§]	16–105	insulation thickness.
1	25	1/2-24	13-610	5/8-61/8	16–156	** 22" and 23" IPS not available in this
1½	38	1/2-24	13-610	5/8-61/8	16–156	insulation thickness.
2	51	1/2-24	13-610	11/8-61/8	29–156	†21," 22" and 23" IPS not available in
21/2	64	1–24	25-610	13/8-61/8	35-156	this insulation thickness.
3	76	1–24	25-610	13/8-61/8	35–156	
31/2	89	1½-24*	38-610	_	_	"19" IPS not available in this
4	102	3-24**	76-610	_	_	insulation thickness.
41/2	114	3-24 [†]	76-610	_	_	§35/8" CTS not available in this
5	127	3-20**	76-508	_	_	insulation thickness.

ACOUSTIC - INSERTION LOSS

Insertion loss data for Johns Manville pipe insulation acoustic treatments tested per ASTM E1222

Frequency	1-in Micro-Lok HP	1-in Micro-Lok HP with Zeston PVC (20 mil)	1-in Micro-Lok HP with MLV (1 psf)	2-in Micro-Lok HP	2-in Micro-Lok HP with Zeston PVC (20 mil)	2-in Micro-Lok HP with MLV (1 psf)
Hz	dB	dB	dB	dB	dB	dB
315	2	1	10	1	0	12
400	2	4	13	0	8	17
500	3	5	14	1	10	19
630	5	11	21	6	14	21
800	7	13	20	8	15	22
1000	9	19	25	13	20	29
1250	10	20	28	14	22	31
1600	13	24	33	17	26	37
2000	15	27	35	20	29	39
2500	17	29	36	21	30	38
3150	19	30	36	23	32	40
4000	20	29	36	26	34	41
5000	22	30	36	29	34	38

ACOUSTIC - TRANSMISSION LOSS

Transmission loss data and sound transmission class (STC) for Johns Manville pipe insulation acoustic treatments tested per ASTM E90

Frequency	1-in Micro-Lok HP	1-in Micro-Lok HP with Zeston PVC (20 mil)	1-in Micro-Lok HP with MLV (1 psf)	2-in Micro-Lok HP	2-in Micro-Lok HP with Zeston PVC (20 mil)	2-in Micro-Lok HP with MLV (1 psf)
Hz	dB	dB	dB	dB	dB	dB
125	4	7	15	6	8	15
250	4	7	18	6	8	20
500	4	11	23	7	15	29
1000	7	19	32	12	25	38
2000	14	25	38	20	32	45
4000	21	29	44	30	38	51
STC	8	16	28	12	19	31

MICRO-LOK® HP

HIGH-PERFORMANCE FIBERGLASS PIPE INSULATION

DATA SHEET

QUALIFICATIONS FOR USE

A sufficient thickness of insulation must be used to keep the maximum surface temperature of Micro-Lok *HP* insulation below 150°F (66°C). In addition, at operating temperatures above 500°F (260°C), Micro-Lok *HP* pipe insulation must be applied in a thickness ranging from 2" (51 mm) minimum to 6" (152 mm) maximum.

During initial heat-up to operating temperatures above 350°F (177°C), an acrid odor and some smoke may be given off as the organic binders used in the fiberglass pipe insulation begin to decompose. When this occurs, caution should be exercised to ventilate the area well. This loss of binder does not directly affect the thermal performance of the pipe insulation, but the compressive strength and resiliency of the product are reduced. For applications with excessive physical abuse or vibration at high temperatures, consult your local Insulation Systems Market Development Manager for alternate material recommendations.

CHILLED WATER SYSTEMS

For chilled water systems, see 3-Part Specification, MECH-261.

APPLICATION RECOMMENDATIONS* MICRO-LOK HP PIPE INSULATION AND BUTT STRIPS

1. Do not apply Micro-Lok *HP* insulation if air temperature is below 20°F (-7°C) or above 130°F (54°C) due to the effect of temperature on tape performance. We recommend stapling when application falls outside this temperature range.

When stapling, we recommend mastic be applied over staples to prevent moisture penetration.

- 2. If stored below 20°F (-7°C) or above 130°F (54°C), insulation cartons should stand within the recommended temperature range for 24 hours prior to application.
- 3. Once release paper is removed, both adhesive and lap must be kept free of dirt and water, and the lap sealed immediately.
- 4. When adhered, the lap and butt strips must be pressurized by rubbing firmly with a plastic squeegee or the back of a knife blade to ensure positive closure.

*For complete application recommendations and installation instructions, see MECH-261 InsulSpec Specifications.



North American Sales Offices, Insulation Systems

Eastern Region and Canada P.O. Box 158 Defiance, OH 43512 800-334-2399

800-334-2399 Fax: 419-784-7866

Western Region

P.O. Box 5108 Denver, CO 80217 800-368-4431 Fax: 303-978-4661 Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The physical and chemical properties of Micro-Lok HP listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Any references to numerical flame spread or smoke developed ratings are not intended to reflect hazards presented by these or any other materials under actual fire conditions. Check with your customer service representative for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville thermal insulation and systems, visit www.jm.com/terms-conditions or call (800) 654-3103.



Mastics, Coatings, Adhesives, Sealants

CP-33 CHIL-OUT[™] Vapor Retarder Coating

Product Data Sheet

INDOOR & OUTDOOR WATER-BASED, VAPOR RETARDER COATING

DESCRIPTION

CP-33 is a water-based, vapor retarder coating for insulation on interior, exterior, low temperature, some dual temperature applications (such as chilled water and refrigerated pipe lines), HVAC ducts and low temperature equipment. It is fast drying and forms a tough, flexible dry film which protects insulated surfaces and helps retard the flow of vapor through an insulation system. It has a smooth, creamy consistency that spreads easily and can be applied in a relatively heavy coating or brushed out into a thin, smooth film.

USES

CP-33 can be used on most types of thermal insulations in both cold and dual temperature service. It is used to vapor seal the seams, overlaps and punctures from pins and staples in FSK, ASJ, white paper and polyester vapor retarder facings on insulation boards, duct wrap and pipe covering. It may also be used to seal cut ends of insulation to prevent moisture ingress and fiber release. It is compatible with fiber glass, mineral fiber, cellular glass, polyisocyanurate, polyurethane, polystyrene, phenolic, rubber foam and other insulations.

APPLICATION

CP-33 features easy application by trowel or brush. It may be applied with CHIL-GLAS® #10 Glass Fiber Reinforcing Mesh to increase film strength. See reverse side of product data sheet for application information.

ADVANTAGES

- Water-based for personal and environmental safety.
- Fast-drying contributes to maximum production rates.
- Non-flammable safe for transport, storage and usage.
- Quick and efficient cleanup of tools and metal with warm water before coating completely dries.
- Outdoor rated and UV resistant.

CERTIFIED

MAS Certified Green[®]

and Coatings

- California Dept. of Public Health Standard Method v1.2
- VOC Emissions and Content requirements to contribute to
 LEED v4 EQ Credit: Low Emitting Materials Paints
- VOC Content: 49 g/l, less water and exempt solvents
- Collaborative for High Performance Schools EQ 7.1
- Meets NFPA Standard 90A and 90B 25/50 requirements as a closure mastic





COLOR

White

AVERAGE WET WEIGHT (ASTM D1475)

11.9 lbs./U.S. gal. (1.4 kg/liter)

AVERAGE NON-VOLATILE (ASTM D2369)

55% by volume (68.5% by weight)

SERVICE TEMPERATURE RANGE

Temperature to which dry film is subjected. -20°F to 190°F (-29°C to 88°C)

APPLICATION & STORAGE TEMPERATURE RANGE

40°F to 100°F (4°C to 38°C)

DRYING TIME

Temperature, humidity and film thickness will affect drying time.

To Touch: 3 Hours Through: 24 Hours

COVERAGE

Varies with substrate and membrane. 4 U.S. gal./100 sq. ft. (1.6 l/m²)

CLEAN UP

Warm, soapy water while coating is still wet.

WATER VAPOR PERMEANCE (TYPICAL AVERAGE) Tested with reinforcing mesh.

ASTM F1249: 0.15 perms (0.10 metric perms) at 28 – 53 mils (1.1 – 1.27 mm) dry film thickness. Tested at 73°F, 50% RH.

ASTM E96, PROCEDURE A: 0.15 perms (0.10 metric perms) at 50 mils (1.25 mm) dry film thickness.

Meets the permeance requirements of ASTM C755-19, Section 7.2.2 for below ambient vapor retarder coatings when used as a closure mastic in conjunction with ASJ and other vapor retarder membranes.

SURFACE BURNING CHARACTERISTICS (ASTM E84)

Flame Spread: 5

Smoke Developed: 15

Tested as applied in a 4 in. strip at a rate of 25 sq. ft./U.S. gallon to inorganic reinforced cement board.

™ Trademark of H.B. Fuller Construction Products Inc.

Visit us on the web at www.fosterproducts.com

H.B. Fuller Construction Products Inc.

Suggested Specifications

Childers® CHIL-OUT™ CP-33

To seal seams, overlaps, punctures, penetrations and terminations of vapor retarder membrane jacketing:

CP-33 Vapor Retarder Coating shall be applied with a first tack coat applied at a coverage rate of 2 U.S. gals./100 sq. ft. (0.8 l/m²). While still wet, a layer of CHIL-GLAS® #10 Glass Fiber Reinforcing Mesh shall be embedded, with all seams overlapped a minimum of 2" (5.08 cm). A finish coat at a coverage rate of 2 U.S. gals./100 sq. ft. (0.8 l/m²) shall be applied so that the total wet film thickness is a minimum of 0.064". This will provide a minimum dry film thickness of 0.035".

NOTES TO SPECIFYING ENGINEER

- 1. CP-33 Vapor Retarder Coating, white, should be specified where white All Service Jacketing (ASJ), or other white coatings/finishes are specified on the adjoining pipe or equipment insulation.
- 2. CHIL-BYL® CP-76 or CHIL-JOINT® CP-70 Joint Sealant is recommended for use with CP-33 Vapor Retarder Coating. Confirm compatibility of joint sealant with insulation before choosing.
- 3. Do not use over copper clad wire.
- 4. All outdoor horizontal surfaces must be sloped at least 1/2 inch per foot to assure water run-off and prevent the ponding of rain water and melting snow or ice.

Application Guide and Suggested Procedures

1. USE OF MATERIAL

DO NOT THIN. Store the product in a warm and dry area. Protect from freezing until dry.

It is essential in applying vapor retarder sealing materials that the recommended film thickness be achieved. Therefore, do not try to spread the vapor retarder coating too thin.

2. THE CONDITION OF THE INSULATION TO BE COATED

Since CP-33 is a vapor retarder, it should never be applied over insulation containing moisture. Dusty or porous substrates should first be primed with CHIL-SEAL® CP-50A MV1, diluted 50% with water for proper bonding. Allow the primer to thoroughly dry before over-coating with CP-33 Vapor Retarder Coating.

3. HINTS FOR SUCCESS

A vapor retarder system is no better than its weakest link. It is extremely important that where the finish terminates at an uninsulated point, the finish of CP-33 Vapor Retarder Coating and glass fiber reinforcing mesh be flashed over the uninsulated section for a minimum of 4" (10.16 cm).

Where there is a possibility of the temperature of the uninsulated section exceeding 190°F (88°C) due to steam-off or other heated application, the vapor sealing at this joint shall be accomplished by using CHIL-BYL® CP-76 Joint Sealant.

The surface of extruded polystyrene and polyisocyanurate board stock may contain water-soluble inks that may bleed through water-based mastics. Test before applying CP-33 Vapor Retarder Coating.

CUSTOMER SERVICE: (800) 832-9002

IMPORTANT: H.B. Fuller Construction Products Inc. warrants that each of its products will be manufactured in accordance with the specifications in effect on the date of manufacture. WE MAKE NO OTHER WARRANTIES AND EXPRESSLY DISCLAIM ANY WARRANTIES OF MERCHANTIBILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a product fails to meet this limited warranty, purchaser's sole and exclusive remedy is replacement of the product or, at our option, refund of the purchase price. OUR ACCEPTANCE OF ANY ORDERS FOR THE PRODUCT IS EXPRESSLY CONDITIONAL UPON PURCHASER'S ASSENT TO THE TERMS ON THE APPLICABLE INVOICE.

ADEQUATE TESTS: The information contained herein we believe is correct to the best of our knowledge and tests. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that adequate tests be performed by you to determine if this product meets all of your requirements. The warranted shelf life of our products is twelve months from date of shipment to the original purchaser or as otherwise provided on the certificate of analysis.

For professional use only. Keep out of reach of children.

Consult Safety Data Sheet and container label for further information.





Technical Data Sheet

3M[™] Venture Tape[™] Facing Tape 1540CW

		•		•
Product	1)	△c~ri	nti	\cap r
1 1 O G G C L		cscii	ρ u	\mathbf{O}

3M™ Venture Tape™ 1540CW is a kraft/scrim/foil (ASJ) laminate coated with a cold weather acrylic pressure sensitive adhesive.

Product Features

- Cold weather adhesive performs well over a wide temperature range
- Mold inhibitor helps maintain adhesive strength and effectiveness
- High puncture and tear resistance ensures long life and durability.
- Conforms well to curved and irregular surfaces

Technical Information Note

Total Tape Thickness (mm)

The following technical information and data should be considered representative or typical only and should not be used for specification purposes. Typical Physical Properties Property Values Additional Information Backing ASJ Adhesive Type Acrylic Liner Release Liner Color White Backing Thickness (mm) View ^ 0.16 mm Test Method: ASTM D3652 Total Tape Thickness (mil) View ^ 7.5 mil Test Method: ASTM D3652

0.19 mm

View ^



Test Method: ASTM D3652

Backing Thickness	6.5 mil	View ^
Test Method: ASTM D3652		
Water Vapor Transmission	0.02 Perms	View ^
Test Method: ASTM E96		
ypical Performance Characteristics		
Property	Values	Additional Information
Tensile Strength	70.1 N/cm	View ^
Test Method: ASTM D3759		
180° Peel Adhesion	Exceeds the strength o f tape backing oz/in	View ^
Test Method: ASTM D3330		
Notes: 12 in/min (300 mm/min)		
Tensile Strength (lb/in)	40 lb/in	View ^
Test Method: ASTM D3759		
Elongation at Break (%)	2 %	View ^
Test Method: ASTM D3759		
Long Term Temperature Resistance	116 °C	
Minimum Long Term Temperature Resistance	-40 °C	
Long Term Temperature Resistance	240 °F	
Minimum Long Term Temperature Resistance	-40 °F	
Certifications/Standards		
Dranarti	Voluce	۸ ما ماند : مرم ما ارد از در سرم دان در در ا
Property	Values	Additional Information



Certifications

• UL723 Classified (15/10 Flame/Smoke Rating)

[UL file #R10984]

• CAN/ULC Classified (15/10 Flame/Smoke

Rating) [UL file #R10984]

Codes & Test Standards

Meets ASTM C1136, Type 1, II, III, IV. *ASTM C1136 testing based in part on third party test data of the product backing

Storage and Shelf Life

Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40 to 50% relative humidity are recommended. To obtain best performance, use this product within 24 months from date of manufacture.

Bottom Matter

3M Industrial Adhesives and Tapes Division 3M Center, Building 225-3S-06 St. Paul, MN 55144-1000 800-362-3550

Trademarks

3M and Venture Tape are trademarks of 3M Company.

Handling/Application Information

Application Examples

- Closure system on ASJ faced duct piping systems
- Vapor seal on ASJ faced ductboard and pipe insulation

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/p/d/b40067987/
Safety Data Sheet SDS	https://www.3m.com/3M/en_US/company-us/SDS-search/results/? gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=1540CW

Family Group

Link Tags:

1540CW

Products	Adhesive Type	Liner	Color	Backing Thickness (mm)	Tensile Strength	Long Term Temperature Resistance	Minimum Long Term Temperature Resistance
1540CW	Acrylic	Release Liner	White	0.16 mm	70.1 N/cm	240 °F	-40 °C

ISO Statement



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use.

Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.



ZESTON® PVC JACKETING

JACKETING FOR COMMERCIAL AND INDUSTRIAL APPLICATIONS

DATA SHEET

DESCRIPTION

Made from the same PVC material as the fitting covers, Zeston® jacketing is designed to fit seamlessly over the Zeston fitting covers.

AVAILABLE SHAPES AND SIZES

Zeston PVC Roll Jacketing is available in standard thicknesses of 10, 15, 20 and 30 mil (0.3, 0.4, 0.5 and 0.8 mm), and in standard widths of 35½ and 48 inches (902 and 1219 mm). Zeston roll jacketing is made from high impact UV-resistant (white only) polyvinyl chloride material designed to provide an inherent vapor retarder and protection to insulated pipes. Color roll jacketing is not recommended for outdoor applications.

Zeston PVC Cut & Curled™ Jacketing is available in thicknesses of 20 and 30 mil (0.5 and 0.8 mm). It is available in factory-cut sizes to fit up to 30 inches (762 mm) O.D. All sections of the Zeston PVC Cut & Curled jacketing are 48 inches (1219 mm) in length and are factory curled to the insulation size to fit snugly over longitudinal pipe. Cut & Curled jacketing is available with or without self-sealing lap tape (SSL) on the longitudinal seam. White only Zeston Cut & Curled jacketing contains a UV inhibitor. The 30 mil (0.8mm) thickness is recommended for outdoor applications. Color Cut & Curled jacketing is not recommended for outdoor applications.

ADVANTAGES

Exceptional Durability. The tough, durable Zeston PVC Jacketing resists damage from impact and will withstand humidity, salt water, adverse weather conditions and most industrial fumes. In addition, the jacketing will not support combustion.

ACOUSTIC PERFORMANCE

When paired with Johns Manville Micro-Lok HP and Micro-Lok HP Ultra pipe insulation, Johns Manville Zeston jacketing provides superior acoustical performance. See page 2 for more details.



Operating Temperature Limits:

PVC: up to 150°F (66°C) Flame Spread: 25 or less Smoke Developed: 50 or less

Grade: weatherable

Color: white and colors (color for indoor use only)

Finish: gloss

Corrosion Resistance. Unlike aluminum or most stainless steel jacketing materials, Zeston PVC Jacketing is immune to galvanic or electrolytic corrosion.

Ease of Maintenance. The jacketing is easily washed down with soap and water and most commercial cleaners. The ability to be easily cleaned, combined with the nontoxic, odorless and tasteless properties of the material and its attractive appearance, make it especially suitable for food, beverage and pharmaceutical applications.

SPECIFICATION COMPLIANCE

L-P-535E,* Composition A, Type USDA, Agriculture Canada New York City MEA #7-87 II, Grade GU

ICB0

L-P-1035A,* Composition A, SBCCI Type II. Grade GU BOCA Canada: CAN S102-M88 ASTM D1784, Class 16354-C CGSB 51-GP-53M

*Impact strength determined by Gardner—SPI test method rather than Izod, since Gardner is more appropriate for PVC sheeting materials.

ZESTON® PVC JACKETING

JACKETING FOR COMMERCIAL AND INDUSTRIAL APPLICATIONS

DATA SHEET

PHYSICAL PROPERTIES

Property	Value	ASTM Test Method	
Specific Gravity	1.48	D792	
Tensile Strength at Yield, psi (kPa)	6,000 (41370)	D638	
Elongation at Yield (MD), %	3.0	D638	
Tensil Modulus, psi (kPA)	470,000 (3,240,650)	D638	
Flexural Strength, psi (kPA)	11,600 (79,982)	D638*	
Flexural Modulus, psi (kPa)	460,000 (3,171,700)	D790	
Flame Spread	25 or less	E84	
Smoke Developed	50 or less	E84	
Electrical Conductance	Non-Conductor	D257	
Gardner - SPI Impact, in. lb/mil by Ductile Failure	10 mil (0.3mm) 1.3	D3679**	
	15 mil (0.4mm) 1.4		
	20 mil (0.5mm) 1.5		
	30 mil (0.8mm) 1.6		

Note: Chemical resistance data available on request.

ACOUSTIC - INSERTION LOSS

Insertion loss data for Johns Manville pipe insulation acoustic treatments tested per ASTM E1222

Frequency	1-in Micro-Lok HP with Zeston PVC (20 mil)	2-in Micro-Lok HP with Zeston PVC (20 mil)
Hz	dB	dB
315	1	0
400	4	8
500	5	10
630	11	14
800	13	15
1000	19	20
1250	20	22
1600	24	26
2000	27	29
2500	29	30
3150	30	32
4000	29	34
5000	30	34

ACOUSTIC - TRANSMISSION LOSS

Transmission loss data and sound transmission class (STC) for Johns Manville pipe insulation acoustic treatments tested per ASTM E90

Frequency	1-in Micro-Lok HP with Zeston PVC (20 mil)	2-in Micro-Lok HP with Zeston PVC (20 mil)	1-in Micro-Lok HP with Zeston PVC (30 mil)	2-in Micro-Lok HP with Zeston PVC (30 mil)
Hz	dB	dB	dB	dB
125	7	8	8	8
250	7	8	9	10
500	11	15	13	18
1000	19	25	22	27
2000	25	32	28	35
4000	29	38	32	40
STC	16	19	19	21



717 17th St. Denver, CO 80202 (800) 654-3103 JM.com

NORTH AMERICAN SALES OFFICES, INSULATION SYSTEMS

Eastern Region

P.O. Box 158 Defiance, OH 43512 (800) 334-2399 Fax: (419) 784-7866

Western Region and Canada

P.O. Box 5108 Denver, CO 80217 (800) 368-4431 Fax: (303) 978-4661 Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Any references to numerical flame spread or smoke developed ratings are not intended to reflect hazards presented by these or any other materials under actual fire conditions. Check with the Regional Sales Office nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville thermal insulation and systems, visit www.jm.com/terms-conditions or call (800)654-3103.

^{*} min 0.125" (3mm) thick specimen

^{** 4} lb. [1.8 kg] weight, 8 lb. [3.6 kg] for 30 mil [0.8 mm])



Revision Date 03/22/2022 Print Date 03/22/2022 Version 2.1

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Trade name ZESTON® Perma-Weld® White Adhesive

Manufacturer or supplier's details

Company Johns Manville Address P.O. Box 5108

Denver, CO USA 80127

Telephone +1-303-978-2000

Emergency telephone

number

24-Hour Number: +1-800-424-9300 (CHEMTREC)

Company Johns Manville Canada Inc.

Address 5301 42 Avenue

Innisfail. AB Canada T4G 1A2

+1-303-978-2000 Telephone

Emergency telephone 24-Hour Number: +1-800-424-9300 (CHEMTREC)

number

Recommended use of the chemical and restrictions on use

Recommended use Adhesives

Restrictions on use For professional users only. Prepared by productsafety@jm.com

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200 (OSHA HCS 2012) and the **Hazardous Products Regulations (WHMIS 2015)**

Flammable liquids Category 2

Serious eye damage Category 1

Carcinogenicity Category 2

Specific target organ toxicity

- single exposure

: Category 3 (Respiratory system, Central nervous system)

GHS label elements

Hazard pictograms









Signal word Danger

Hazard statements H225 Highly flammable liquid and vapour.

H318 Causes serious eye damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer if inhaled.



Version 2.1 Revision Date 03/22/2022 Print Date 03/22/2022

Precautionary statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist or vapours.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
acetone; 2-propanone	67-64-1	>= 30 - < 60
tetrahydrofuran	109-99-9	>= 10 - < 30
titanium dioxide	13463-67-7	>= 1 - < 5



Version 2.1 Revision Date 03/22/2022 Print Date 03/22/2022

2-butanone | 78-93-3 | >= 1 - < 5

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Handle in accordance with good industrial hygiene and safety

practice.

Show this safety data sheet to the doctor in attendance.

Move out of dangerous area.

Do not leave the victim unattended.

If inhaled : Remove to fresh air immediately. Get medical attention

immediately.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : In case of contact, flush skin with plenty of water for at least 5

minutes.

Call a physician if irritation develops or persists.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 30 minutes.

If easy to do, remove contact lens, if worn.

Protect unharmed eye.

Continue rinsing eyes during transport to hospital.

If swallowed : DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Gently wipe or rinse the inside of the mouth with water. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician or Poison Control Centre

immediately.

Most important symptoms and effects, both acute and

delayed

Causes serious eye damage.

May cause respiratory irritation.

May cause drowsiness or dizziness.
Suspected of causing cancer if inhaled.

Repeated exposure may cause skin dryness or cracking.

If potential for exposure exists refer to Section 8 for specific

Protection of first-aiders : If potential for exposure exists refer to Sec

personal protective equipment.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO2)

Dry chemical Foam Water spray

Unsuitable extinguishing

media

High volume water jet

Hazardous combustion

products

carbon oxides

Hydrogen chloride gas chlorine compounds titanium/titanium oxides

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Ground and bond container and receiving equipment.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking. Keep container tightly closed.



Version 2.1 Revision Date 03/22/2022 Print Date 03/22/2022

Take action to prevent static discharges.

Use explosion-proof electrical/ ventilating/ lighting equipment.

Use non-sparking tools.

In the event of fire, cool tanks with water spray.

Prevent fire extinguishing water from contaminating surface

water or the ground water system.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas.

Keep people away from and upwind of spill/leak.

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Pay attention to flashback.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Refer to protective measures listed in sections 7 and 8.

Should not be released into the environment. Environmental precautions

Methods and materials for containment and cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Use explosion-proof equipment.

Electrical equipment should be protected to the appropriate

Take measures to prevent the build up of electrostatic charge. Use only in area provided with appropriate exhaust ventilation. Keep away from open flames, hot surfaces and sources of

ianition.

Vapours are heavier than air and may spread along floors. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than

the occupational exposure limits.

Advice on safe handling For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Conditions for safe storage

Keep containers tightly closed in a dry, cool and well-

ventilated place.

To maintain product quality, do not store in heat or direct

sunlight.

Use explosion-proof equipment.

Keep away from sources of ignition - No smoking.

Keep away from oxidizing agents and strongly acid or alkaline Materials to avoid

materials.

US/EN 4/14



 Version 2.1
 Revision Date 03/22/2022
 Print Date 03/22/2022

Recommended storage

temperature

: < 99.9 °F / < 37.7 °C

Storage period : 12 Months

Further information on : Keep containers tightly closed in a dry, cool and well-

storage stability ventilated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone; 2-propanone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA
tetrahydrofuran	109-99-9	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		TWA	200 ppm 590 mg/m3	NIOSH REL
		ST	250 ppm 735 mg/m3	NIOSH REL
		TWA	200 ppm 590 mg/m3	OSHA
titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
2-butanone	78-93-3	TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		TWA	200 ppm 590 mg/m3	NIOSH REL
		ST	300 ppm 885 mg/m3	NIOSH REL
		TWA	200 ppm 590 mg/m3	OSHA

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Samplin g time	Permissible concentratio n	Basis
acetone; 2-propanone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
tetrahydrofuran	109-99-9	Tetrahydrof uran	Urine	End of shift (As soon as possible	2 mg/l	ACGIH BEI



Version 2.1 Revision Date 03/22/2022 Print Date 03/22/2022

				after exposure ceases)		
2-butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI

Engineering measures : Use only in an area equipped with explosion proof exhaust

ventilation.

Provide exhaust ventilation close to floor level.

Maintain air concentrations below occupational exposure

standards.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where

concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Solvent-resistant gloves

Remarks : Please observe the instructions regarding permeability and

breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

Eye protection : Wear safety glasses with side shields or goggles.

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Wear protective clothing, such as long-sleeved shirts and

pants.

Remove and wash contaminated clothing before re-use.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Written instructions for handling must be available at the work

place.

Contaminated work clothing should not be allowed out of the

workplace.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Colour : white
Odour : acetone-like
Odour Threshold : No data available



Version 2.1 Revision Date 03/22/2022 Print Date 03/22/2022

рΗ No data available Melting point/freezing point : -108 - -87 °C

Initial boiling point and boiling : 56.1 °C

range

Flash point : -21 - -7 °C

Evaporation rate No data available Flammability (solid, gas) Not applicable

Upper explosion limit : 12.8 %(V)

Lower explosion limit : 1.4 %(V)

Vapour pressure 2.41 hPa

Relative vapour density No data available Relative density No data available : 0.929 g/cm³ Density

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents Partition coefficient: n-

octanol/water

Auto-ignition temperature

Thermal decomposition

Viscosity

Viscosity, dynamic 900 - 1,100 mPa.s

No data available Viscosity, kinematic

SECTION 10. STABILITY AND REACTIVITY

No dangerous reaction known under conditions of normal use. Reactivity

May form peroxides in the presence of air.

Chemical stability Stable under normal conditions.

Possibility of hazardous

reactions

Conditions to avoid Heat, flames and sparks.

Electrostatic discharge

: No data available

: No data available

: No data available

: 230 °C

Oxidizing agents Incompatible materials

Strong acids and strong bases

Strong reducing agents

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

: Acute toxicity estimate : > 5,000 mg/kg Acute oral toxicity

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 10 mg/l

Exposure time: 4 h

US/EN 7/14



Version 2.1 Revision Date 03/22/2022 Print Date 03/22/2022

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

acetone; 2-propanone:

Acute oral toxicity : LD50 (Rat, female): 5,800 mg/kg

GLP: no

Acute inhalation toxicity : LC50 (Rat, female): 76.0 mg/l

Exposure time: 4 h
Test atmosphere: vapour

GLP: no

Acute dermal toxicity : LD50 (Guinea pig, male and female): > 7,426 mg/kg

GLP: no

tetrahydrofuran:

Acute oral toxicity : LD50 (Rat, male and female): 1,650 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 14.7 mg/l

Exposure time: 6 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute

inhalation toxicity

Remarks: No mortality was observed.

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

titanium dioxide:

Acute oral toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.09 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : Method: Expert judgement

Assessment: The substance or mixture has no acute dermal

toxicity

2-butanone:

Acute oral toxicity : LD50 (Rat, male and female): 2,193 mg/kg

Method: OECD Test Guideline 423

Acute inhalation toxicity : Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit, male): > 8,054 mg/kg

Method: OECD Test Guideline 402

GLP: no



Version 2.1 Revision Date 03/22/2022 Print Date 03/22/2022

Serious eye damage/eye irritation

Components:

acetone; 2-propanone:

Species: Rabbit Result: Eye irritation Exposure time: 24 h

Assessment: Irritating to eyes.

Method: Draize Test

Serious eye damage/eye irritation

tetrahydrofuran: Species: Rabbit

Result: Irreversible effects on the eye

Method: Draize Test

GLP: no

Serious eye damage/eye irritation

2-butanone:Species: Rabbit
Result: irritating

Method: OECD Test Guideline 405

Respiratory or skin sensitisation

Components:

tetrahydrofuran:

IARC Group 2B: Possibly carcinogenic to humans

tetrahydrofuran 109-99-9

titanium dioxide 13463-67-7

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA (29 CFR 1910 Subpart Z, Toxic and

Hazardous Substances).

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

STOT - single exposure

Components:

acetone; 2-propanone:

Exposure routes: inhalation (vapour) Target Organs: Nervous system

Assessment: May cause drowsiness or dizziness.

STOT - single exposure

tetrahydrofuran:

Exposure routes: Inhalation

Target Organs: Respiratory system



Version 2.1 Revision Date 03/22/2022 Print Date 03/22/2022

Assessment: May cause respiratory irritation.

STOT - single exposure

2-butanone:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

Further information

Product:

Remarks: Repeated exposure may cause skin dryness or cracking.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

tetrahydrofuran:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,160 mg/l

End point: mortality Exposure time: 96 h

Test Type: flow-through test Method: OECD Test Guideline 203

GLP: no

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 3,485 mg/l

End point: mortality
Exposure time: 48 h
Test Type: static test
Analytical monitoring: no

Method: OECD Test Guideline 202 GLP: No information available.

Toxicity to algae/aquatic

plants

ECx (Scenedesmus quadricauda (Green algae)): 3,700 mg/l

Exposure time: 8 d Test Type: static test Analytical monitoring: no

Toxicity to fish (Chronic

toxicity)

NOEC (Pimephales promelas (fathead minnow)): 216 mg/l

Exposure time: 33 d

Test Type: flow-through test Analytical monitoring: yes GLP: No information available.

2-butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l

End point: mortality Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203



Version 2.1 Revision Date 03/22/2022 Print Date 03/22/2022

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 308 mg/l

End point: Immobilization Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 2,029

ma/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 201

Persistence and degradability

Components:

acetone; 2-propanone:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 100 %

Bioaccumulative potential

Components:

acetone; 2-propanone:

Partition coefficient: n-

octanol/water

log Pow: -0.24 (68 °F / 20 °C)

tetrahydrofuran:

Partition coefficient: n-octanol/water

log Pow: 0.45 (77 °F / 25 °C)

pH: 7

2-butanone:

Partition coefficient: n-

octanol/water

log Pow: 0.3 (104 °F / 40 °C) Method: OECD Test Guideline 117

Mobility in soil
No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82

Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was

manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +

B).

SECTION 13. DISPOSAL CONSIDERATIONS



Version 2.1 Revision Date 03/22/2022 Print Date 03/22/2022

Disposal methods

Waste from residues : Dispose of contents/container to an approved facility in

accordance with local, regional, national and international

regulations.

The hazard and precautionary statements displayed on the

label also apply to any residues left in the container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

Land transport

USDOT (Special Provision 149): UN1133, Adhesives, 3, II

TDG: UN1133, Adhesives, 3, II

LIMITED QUANTITY if shipped in inner packagings not over 5.0 L (1.3 gallons) net capacity each, packed in a strong outer packaging.

Sea transport

IMDG: UN1133, Adhesives, 3, II

Air transport

IATA/ICAO: UN1133, Adhesives, 3, II

SECTION 15. REGULATORY INFORMATION

TSCA list

TSCA - 5(a) Significant New Use Rule List of : No substances are subject to a

Chemicals Significant New Use Rule.

U.S. Toxic Substances Control Act (TSCA) Section : No substances are subject to TSCA 12(b) Export Notification (40 CFR 707, Subpart D) 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
tetrahydrofuran	109-99-9	1000	3333

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Carcinogenicity

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)



Version 2.1 Revision Date 03/22/2022 Print Date 03/22/2022

SARA 302 : This material does not contain any components with a section

302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

acetone; 2-propanone 67-64-1 30 - 60 % 2-butanone 78-93-3 1 - 5 %

California Prop. 65

WARNING: This product can expose you to chemicals including tetrahydrofuran, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed as

active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

DSL : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information

Revision Date : 03/22/2022

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -



Version 2.1 Revision Date 03/22/2022 Print Date 03/22/2022

Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods: IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA -National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD -Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory: TSCA - Toxic Substances Control Act (United States): UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



ZESTON 2000® SERIES WHITE PVC INSULATED FITTING COVERS AND JACKETING

DATA SHEET

FEATURES

Zeston 2000® series white PVC is intended for the protection of insulated or bare pipes. The system has long-lasting protection, an attractive finished appearance, and easy installation. It meets most requirements for federal, state and local fire-safety codes and is accepted for commercial, institutional, industrial, and residential projects in all parts of the US. Zeston 2000 Series fittings are also available with Hi-Lo Temp fiber glass inserts.

APPLICATIONS

Commercial, institutional and industrial applications

CONSTRUCTION

Zeston 2000 Series is manufactured from high-impact, gloss white, UV-resistant polyvinyl chloride jacketing.

APPLICATION RECOMMENDATIONS

- Wrap the Hi-Lo Temp fiber glass insert completely around the pipe fitting without overly compressing it or leaving any voids
- Ensure that the insulation insert covers all exposed surfaces
- Install the Zeston PVC fitting cover over the pipe fitting and fiber glass insert by securing the throat of the Zeston PVC insert using either serrated tacks, Perma-Weld adhesive or Zeston Z-Tape
- If applied in an outdoor setting or exposed to the sun, precautions should be taken to account for expansion joints

QUALIFICATIONS FOR USE

Hot Systems

- Use proper insulation thickness to ensure PVC covers are kept below 150°F (66°C)
- PVC covers should be kept away from contact with and/or exposure to sources of direct or radiated heat
- For fittings where operating temperatures exceed 250°F (121°C) or where pipe insulation thickness is greater than 1½" (38mm), two or more layers of Hi-Lo Temp insulation inserts are required beneath the fitting cover (refer to MECH-261 Zeston Hi-Lo Temp Inserts)

Cold Systems

- An approved vapor-barrier compatible with PVC must be applied between pipe insulation and fitting cover and on fitting cover throat overlap. Please refer to Insulspec MECH-261 on jm.com
- For fittings where operating temperature is below 45°F (7°C) or where the pipe insulation thickness is greater than 1½ "
 (38mm), two or more layers of Hi-Lo Temp insulation inserts are required beneath fitting cover (refer to MECH-261 Zeston Hi-Lo Temp Inserts)



Refrigerant Systems and Cold Systems In Severe Ambient Conditioning

- Mitered pipe insulation segments, fabricated or pre-molded insulation shapes may be used in lieu of Hi-Lo temp insulation inserts
- An intermediate vapor-barrier compatible with PVC is required to completely seal the insulation prior to installing the Zeston 2000 PVC fitting cover
- Care should be taken to ensure the vapor barrier mastic is applied between the pipe insulation and the fitting cover and on the fitting cover throat overlap seam

Totally Sealed Systems (USDA Approval)

- 20 or 30 mil (0.5 mm or 0.8mm) Zeston PVC jacketing should be applied to pipe insulation in conjunction with Zeston fitting covers
- Circumferential and longitudinal jacket and fitting cover seams should be sealed with Zeston Perma-Weld solvent welding adhesive
- Circumferential seams should be a minimum of 1" (25mm) overlap and longitudinal seams should be 1½" - 2" (38mm to 51mm) overlap
- Upon completion, all seams should visually be checked for seal and, if necessary, touched up
- Slip joints are periodically required between fixed supports ans on continuous long runs of straight piping.
- To implement a slip joint, increase the circumferential overlap to 8" to 10" (203 mm to 254 mm) and apply a flexible white caulking in the overlap area to maintain a sealed system
- Refer to Zeston installation instructions CI-35 at www.jm.com

ZESTON 2000® SERIES WHITE PVC

INSULATED FITTING COVERS AND JACKETING

PERFORMANCE SPECIFICATIONS

Electrical Conductance	Non-conductor
Elongation at Yield (MD), %	3.0
Flame Spread	25 or less
Smoke Developed	50 or less
Flexural Modulus, psi (kPa)	430,000 (2,964,750)
Flexural Strength, psi (kPa)	11,0000 (75,850)
	10 mil (0.3 mm) 1.3
Gardner - SPI Impact,	15 mil (0.4 mm) 1.4
in.lb/mil by Ductile Failure	20 mil (0.5 mm) 1.5
	30 mil (0.8 mm) 1.6
Specific Gravity	1.48
Tensile Modulus, psi (kPa)	425,000 (2,930,270)
Tensile Strength at Yield, psi (kPa)	6,000 (41,370)

SPECIFICATION COMPLIANCE

ASTM	D257 (Electrical surface resistance)
	D638 (Tensile strength)
	D790 (Flexural Strength)
	D792 (Density & specific gravity)
	D1784 (Specification for rigid PVC)
	D3679 (Specification for rigid PVC)
	E84 (Surface burning characteristics)
	E136 25/50 non-combustibility (fiber glass
	inserts)
Agriculture Canada	Pass (Canada Department of Agriculture)
Canada	CGSB51-GP-53M
CAN/ULC	S102
L-P*: Composition	535E (Federal standard for PVC)
A, Type II, Grade GU	1035A (US Army standard PVC)
New York City MEA	#7-87 (Toxicity test)
USDA	US Department of Agriculture

COMPRESSED THERMAL CONDUCTIVITY ZESTON HI-LO TEMP INSULATION INSERTS

Mean Tem	perature	"K"	
°F	°C	BTU•in/(hr•ft2•°F)	W/M•°C
75	24	0.23	0.033
150	66	0.27	0.039
300	149	0.40	0.058



717 17th St. Denver, CO 80202 (800) 654-3103 JM.com Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Any references to numerical flame spread or smoke developed ratings are not intended to reflect hazards presented by these or any other materials under actual fire conditions. Check with the Regional Sales Office nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville thermal insulation and systems, visit www.jm.com/terms-conditions or call (800)654-3103.



ZESTON® HI-LO TEMP INSULATION INSERTS

FIBERGLASS INSULATION INSERTS

DATA SHEET

DESCRIPTION

Zeston® Hi-Lo Temp fiberglass insulation inserts are flexible, pre-cut inserts for PVC pipe fittings. They are sized for each specific PVC fitting and are a lower-cost alternative to preformed or fabricated insulated elbows. The inserts are designed to meet the thermal requirements of ASTM C553 and ASHRAE 90.1.

Zeston Hi-Lo Temp Insulation Inserts are manufactured from rotary-process fiberglass bonded with a Formaldehyde-freeTM resin. They are cut to size to be used in conjunction with JM's Zeston PVC fittings. Zeston Hi-Lo Temp Insulation Inserts are flexible, odorless, and vibration resistant. They can save time and labor during installation and are designed to meet corresponding pipe insulation thermal value. The Zeston Hi-Lo Temp Insulation Inserts are made with a formaldehyde-free binder; however, all bonded fibrous insulation products made with formaldehyde-free binders will result in some formaldehyde emissions at temperatures that exceed 450°F.

USES

Zeston Hi-Lo Temp Insulation Inserts are used to insulate PVC fittings in operating temps between 0°F-850°F/-18°C-454°C. JM recommends installing one (1) Zeston Hi-Lo Temp Insulation Insert for every 1" of corresponding pipe insulation thickness. The insulation insert may emit minimal smoke and odor during the initial exposure to elevated temperatures. Keep the area well-ventilated during the initial heat-up.

PHYSICAL PROPERTIES

- 2" thick 1.0 PCF density
- Formaldehyde-free[™] binder
- Insulation is a white, light-weight, highly resilient, blanket-type thermal insulation manufactured from rotary process fiber glass
- Inserts are tabbed on sizes 2-10 and cut all the way through for largesize fitting inserts, to accommodate easy separation and resist tearing

Service Temp. Range (ASTM C411)
 0°F - 850°F/-18°C - 454°C

Corrosivity (ASTM 1617)

Pass

Limited Combustibility
 <3500 BTU/LB

Microbial Growth (ASTM C1338)

Moisture Sorption
 <5% by weight

• pH 7.5 - 12

• Surface Burning Characteristics (ASTM E84) \leq 25/50 (flame/smoke)

Uncompressed Insulation thickness/density 2" Thick/1 PCF Density



COMPRESSED THERMAL CONDUCTIVITY

Mean Ter	nperature	K	
°F	°C	BTU • in/(hr • ft² • °F)	W/m•°C
75	24	.23	.033
150	66	.27	.039
300	149	.40	.058

SPECIFICATION COMPLIANCE

ASTM C553 ASHRAE 90.1 ASTM E84 25/50 rating NRC 1.36, ASTM C795, MIL-DTL-24244*

*Before ordering material to comply with these specifications, a statement of the fact must appear on the purchase oder. Specific lot testing will be conducted and a certification of compliance can be provided.

SUSTAINABLE BUILDING ATTRIBUTES

Recycled Content: 20%





717 17th St. Denver, CO 80202 (800) 654-3103 JM.com Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Any references to numerical flame spread or smoke developed ratings are not intended to reflect hazards presented by these or any other materials under actual fire conditions. Check with the Regional Sales Office nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville thermal insulation and systems, visit www.jm.com/terms-conditions or call (800)654-3103.