

The diagram illustrates several methods for indicating roof slope and associated details:

- Top Left:** A circular detail callout labeled "1" and "A101" with a "SIM" (section) symbol. Arrows point to "DETAIL NUMBER, TYP." and "SHEET NUMBER, TYP."
- Middle Left:** A horizontal line with an arrow pointing right, labeled "SLOPE".
- Bottom Left:** A horizontal line with an arrow pointing right, labeled "1/4" - 12"
- Bottom Left (Inset):** A detail of a prefinished metal gutter with a down spout, labeled "D.S."
- Top Right:** The heading "DETAIL KEY".
- Middle Right:** The text "POSITIVE SLOPE TO DRAIN GREATER OR EQUAL TO MANUFACTURER'S MINIMUM SLOPE RECOMMENDATIONS".
- Bottom Right:** The text "SPECIFIC SLOPE REQUIRED INDICATED".
- Bottom Right (Inset):** The text "PREFINISHED METAL GUTTER WITH DOWN SPOUT INDICATED".

1. ARCHITECTURAL ROOF PLAN IS FOR GENERAL COORDINATION OF SLOPE, MATERIAL, AND ARCHITECTURAL FEATURES. WHILE SOME MEP ITEMS MAY BE GRAPHICALLY INDICATED, REFER TO MECHANICAL, PLUMBING, AND ELECTRICAL SHEETS FOR LOCATIONS OF PIPING, CURBS, VENTS, DUCTS, FANS, AND OTHER MEP ITEMS IN THE PROJECT SCOPE.
2. MINIMUM SLOPE FOR STANDING SEAM METAL ROOFING SHALL BE 1/4" PER FOOT PER AFPC/IBC 1507.4.2-3
3. ALL ROOF FLASHING TO BE IN ACCORDANCE WITH MANUFACTURER RECOMMENDATIONS.



THIS PAGE IS BEST
VIEWED IN COLOR

A110