SECTION 23 34 23

HVAC POWER VENTILATORS

PART 1 GENERAL

1.01 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.02 SECTION INCLUDES

A. Ceiling exhaust fans.

1.03 RELATED REQUIREMENTS

- A. Section 23 05 13 Common Motor Requirements for HVAC Equipment.
- B. Section 23 05 48 Vibration And Seismic Controls For HVAC Piping And Equipment.
- C. Section 23 33 00 Air Duct Accessories: Backdraft dampers.
- D. Section 26 05 83 Wiring Connections: Electrical characteristics and wiring connections.
- E. Section 26 27 26 Wiring Devices: Electrical characteristics and wiring connections.

1.04 REFERENCE STANDARDS

- A. AMCA (DIR) (Directory of) Products Licensed Under AMCA International Certified Ratings Program; 2015.
- B. AMCA 99 Standards Handbook; 2016.
- C. AMCA 204 Balance Quality and Vibration Levels for Fans; 2020.
- D. AMCA 210 Laboratory Methods of Testing Fans for Certified Aerodynamic Performance Rating; 2016.
- E. AMCA 300 Reverberant Room Method for Sound Testing of Fans; 2014.
- F. AMCA 301 Methods for Calculating Fan Sound Ratings from Laboratory Test Data; 2014.
- G. NEMA 250 Enclosures for Electrical Equipment (1000 Volts Maximum); 2020.
- H. UL 705 Power Ventilators; Current Edition, Including All Revisions.

1.05 SUBMITTALS

- A. See Section 01 30 00 Administrative Requirements, for submittal procedures.
- B. Product Data: Provide data on fans and accessories including fan curves with specified operating point clearly plotted, power, RPM, sound power levels at rated capacity, and electrical characteristics and connection requirements.
- C. Manufacturer's Instructions: Indicate installation instructions.

1.06 QUALITY ASSURANCE

A. Manufacturer Qualifications: Company specializing in manufacturing the type of products specified in this section, with minimum three years of documented experience.

1.07 FIELD CONDITIONS

A. Permanent ventilators may not be used for ventilation during construction.

PART 2 PRODUCTS

2.01 POWER VENTILATORS - GENERAL

- A. Static and Dynamically Balanced: AMCA 204 Balance Quality and Vibration Levels for Fans.
- B. Performance Ratings: Determined in accordance with AMCA 210 and bearing the AMCA Certified Rating Seal.
- C. Sound Ratings: AMCA 301, tested to AMCA 300 and bearing AMCA Certified Sound Rating Seal.

- D. Fabrication: Comply with AMCA 99.
- E. UL Compliance: UL listed and labeled, designed, manufactured, and tested in accordance with UL 705.
- F. Electrical Components: Listed and classified by Underwriters Laboratories Inc. as suitable for the purpose specified and indicated.
- G. Enclosed Safety Switches: Comply with NEMA 250.

2.02 CEILING EXHAUST FANS

- A. Centrifugal Fan Unit: V-belt or direct driven with galvanized steel housing lined with acoustic insulation, resiliently mounted motor, gravity backdraft damper in discharge.
- B. Disconnect Switch: Cord and plug in housing for thermal overload protected motor and wall mounted solid state speed controller.
- C. Grille: Molded white plastic.

PART 3 EXECUTION

3.01 INSTALLATION

- A. Install in accordance with manufacturer's instructions.
- B. Provide sheaves required for final air balance.
- C. Install backdraft dampers on inlet to roof-mounted and externally-mounted wall exhausters.
- D. Provide backdraft dampers on outlet from cabinet and ceiling exhauster fans and as indicated.
- E. Provide backdraft dampers or motorized dampers in the wall housing or wall collar of sidewall propeller fans.

END OF SECTION