

LIFE SAFETY GENERAL NOTES

- ALL WORK SHALL CONFORM TO ALL APPLICABLE CODES, ORDINANCES, AND STATUTES.
- REFER TO CONSULTANT ENGINEER DRAWINGS AND SPECIFICATIONS FOR ADDITIONAL INFO.
- THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING AND PROVIDING ALL REQUIRED LIFE SAFETY SYSTEMS INCLUDING MEANS OF EGRESS, FIRE EXTINGUISHERS, FIRE ALARM AND DETECTION SYSTEM DURING THE COURSE OF CONSTRUCTION. SYSTEMS SHALL BE IN COMPLIANCE WITH LOCAL BUILDING CODES. LOCATE AND MOUNT EMERGENCY EXIT SIGNAGE PER LOCAL FIRE DEPARTMENT/INSPECTOR'S REQUIREMENTS. COORDINATE WITH ELECTRICAL DRAWINGS AND SPECIFICATIONS PRIOR TO PURCHASE AND INSTALLATION. THE CONTRACTOR SHALL COORDINATE EXIT SIGN LOCATIONS SHOWN ON THE LIFE SAFETY PLANS AND ELECTRICAL PLANS AND NOTIFY ARCHITECT OF DISCREPANCIES IMMEDIATELY AND PRIOR TO INSTALLING EXIT SIGNS. GC SHALL BE RESPONSIBLE FOR LOCATING AND COORDINATING ALL EXIT SIGNS WITH ELECTRICAL FUTURES. REFER TO ELECTRICAL DRAWINGS FOR ADDITIONAL INFORMATION. SEE SPECIFICATION SECTION 10.44.00 FOR FIRE EXTINGUISHER AND FIRE EXTINGUISHER CABINET INFO.
- ALL FIRE EXTINGUISHER CABINETS SHALL HAVE SIGNAGE ON THE OUTSIDE FACE OF CABINET DOOR STATING "FIRE EXTINGUISHER" IN COLOR AND SIZE ACCEPTABLE TO LOCAL FIRE DEPARTMENT. AHA AND/OR APPROVED BY ARCHITECT. INSTALL FIRE EXTINGUISHER PLAQUE ABOVE EACH FIRE EXTINGUISHER. BOTTOM OF HOOK AND BRACKET FIRE EXTINGUISHERS SHALL BE 27" A.F.F. G.C. SHALL BE RESPONSIBLE FOR PROVIDING, LOCATING, AND COORDINATING ALL TEMPORARY FIRE EXTINGUISHERS WITH LOCAL FIRE DEPARTMENT/INSPECTOR/AHA FOR SHELL PROJECT SPACES.
- PROVIDE FIRE RATED FIRE EXTINGUISHER CABINETS WITH FIRE RATING EQUIVALENT OF HOST WALL WHERE RATED HOST WALL OCCURS. FOR FIRE EXTINGUISHERS MOUNTED TO EXTERIOR EQUIPMENT, GC SHALL COORDINATE LOCATION AND CONFIRM DEVICES CAN BE DIRECT MOUNTED TO EQUIPMENT, OR PROVIDE APPLICABLE DETAIL FOR MOUNTING PER EQUIPMENT MANUFACTURER REQUIREMENTS. REFERENCE CODES SHEETS FOR PROJECT DATA AND CODE INFORMATION. REFERENCE 000-SERIES SHEETS REGARDING ACCESSIBILITY STANDARDS INFORMATION.
- GENERAL CONTRACTOR SHALL COORDINATE WITH OWNER AND AHA FOR EVACUATION PLAN REQUIREMENTS. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING AND INSTALLING REQUIRED EVACUATION PLANS THROUGHOUT FACILITY PER AHA AND/OR OWNER DIRECTION. CONTRACTOR SHALL CONSTRUCT AND INSTALL WOOD FRAMES, 1X17 IN. COLOR AND LAMINATED EVACUATION PLANS. COORDINATE WITH OWNER FOR QUANTITY AND LOCATIONS.
- INTERIOR FINISHES: INTERIOR WALL AND CEILING FINISHES SHALL BE CLASSIFIED IN ACCORDANCE WITH ASTM E84. SUCH INTERIOR FINISH MATERIAL SHALL BE GROUPED IN THE FOLLOWING CLASSES IN ACCORDANCE WITH THEIR FLAME SPREAD AND SMOKE DEVELOPED INDEXES.
- FOR LATER PHASE RENOVATION/REMODEL PROJECTS, CONFIRM LOCATION OF EXISTING FIRE SPRINKLER HEADS LAYOUT AND DESIGN AS REQUIRED TO COMPLY WITH FIRE PROTECTION/SPRINKLER CODE REQUIREMENTS. THIS FACILITY IS PRIVATELY OWNED AND NOT OPEN TO THE PUBLIC. THE FACILITY IS OPERATIONAL 24 HOURS A DAY 7 DAYS A WEEK. SECURITY MONITORS THE FACILITY 24 HOURS A DAY 7 DAYS A WEEK AND AN EMERGENCY TEAM IS AVAILABLE DURING THESE TIME PERIODS.

| ISSUES |                               |
|--------|-------------------------------|
| 1      | 11/12/2025 CONCEPTUAL         |
| 2      | 12/17/2025 SCHEMATIC DESIGN   |
| 3      | 12/17/2025 STILL MILL ORDER   |
| 4      | 01/23/2026 DESIGN DEVELOPMENT |
| 5      |                               |
| 6      |                               |
| 7      |                               |
| 8      |                               |
| 9      |                               |
| 10     |                               |
| 11     |                               |
| 12     |                               |
| 13     |                               |

REVISIONS

| NO. | DATE | DESCRIPTION |
|-----|------|-------------|
| 1   |      |             |
| 2   |      |             |
| 3   |      |             |
| 4   |      |             |
| 5   |      |             |
| 6   |      |             |
| 7   |      |             |
| 8   |      |             |
| 9   |      |             |
| 10  |      |             |
| 11  |      |             |
| 12  |      |             |
| 13  |      |             |

NOT FOR CONSTRUCTION

This document is incomplete and may not be used for regulatory approval, permit or construction.  
Date of issue: 01/23/2026


ARK01  
DESIGN DEVELOPMENT  
CLARKSVILLE, AR 72830

|   |   |   |
|---|---|---|
| L | K | J |
| G | E | C |
| H | F | D |
| P | N | M |


LIFE SAFETY PLAN - LEVEL TWO - OVERALL

OCCUPANCY CLASSIFICATION LEGEND

S-2 STORAGE (LOW HAZARD)



2 OCCUPANCY CLASSIFICATION - LEVEL TWO  
1" = 80'-0"



FIRE & SMOKE WALL LEGEND

- CODE REQUIRED: INDICATED BY COLOR
- UNRATED ASSEMBLY
  - 1 HOUR RATED ASSEMBLY
  - 2 HOUR RATED ASSEMBLY
  - INTUMESCENT COATING

LIFE SAFETY LEGEND

- TRAVEL DISTANCE - EXIT ACCESS
- TRAVEL DISTANCE - COMMON PATH
- TRAVEL DISTANCE TAG
- PATH ID
- EGRESS VS. COMMON PATH

OCCUPANCY CLASSIFICATION LEGEND

- S-2 STORAGE (LOW HAZARD)
- B BUSINESS (ACCESSORY OCCUPANCY)

CODE SUMMARY LEGEND

- ILLUMINATED EMERGENCY EXIT SIGN, REF. TO ELEC.
- ILLUMINATED EMERGENCY EXIT SIGN, REF. TO ELEC. (WALL MOUNTED)
- EXIT DISCHARGE
- EYE WASH STATION
- AED CABINET
- EXIT
- KNOX BOX COORDINATE LOCATION REQUIREMENT WITH LOCAL BUILDING CODE
- FIRE EXTINGUISHER

PATH OF TRAVEL DISTANCES LEVEL 2

| PATH ID | DISTANCE  | TRAVEL PATH TYPE |
|---------|-----------|------------------|
| 2-1     | 248' - 2" | EXIT ACCESS      |
| 2-2     | 311' - 1" | EXIT ACCESS      |
| 2-3     | 332' - 4" | EXIT ACCESS      |
| 2-4     | 337' - 8" | EXIT ACCESS      |

1 LIFE SAFETY FLOOR PLAN  
3/64" = 1'-0"